



COMPACTED SUBGRADE
(REMOVE ALL SOFT AND UNSTABLE AREAS)
2% MIN. CROSS SLOPE ON SUBGRADE

200mm OF GRANULAR "A" TO EXTEND
300mm BEYOND EDGE OF ASPHALT
(COMPACTED THICKNESS)

75mm OF HL-3 ASPHALT TO 98% S.P.D.
(COMPACTED THICKNESS)

EDGE OF ASPHALT TO BE HAND
TAMPED TO A 45 DEGREE ANGLE

50mm OF TOPSOIL AND SOD
OVER GRANULAR BASE TO ASPHALT EDGE

NOTES:

1. PATHWAY SURFACE TO BE SMOOTH AND EVEN THROUGHOUT
2. ALL COMPACTION TO BE 98% S.P.D. UNLESS OTHERWISE NOTED
3. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE NOTED
4. THIS DETAIL TO BE USED IN CONJUNCTION WITH THE APPROVED LAYOUT DRAWING.
5. WIDTH OF PATHWAY TO BE CONFIRMED WITH COMMUNITY SERVICES

NO. REVISION

DATE



SCALE: N.T.S.
DATE: JANUARY 2001
DRAWN BY: P & D
NUMBER: 02510-1

ASPHALT PEDESTRIAN PATHWAY