



NOTES:

1. DROPPED CURBS ARE TO BE PROVIDED FOR WIDTH OF ALL PEDESTRIAN CROSSING ZEBRA MARKINGS.
2. TACTILE WALKING SURFACE INDICATORS ARE TO BE INSTALLED AT ALL PEDESTRIAN CROSSINGS IN CONJUNCTION WITH ALL ROAD AND SIDEWALK CONSTRUCTION, RECONSTRUCTION AND RESURFACING PROJECTS.
3. EACH LOCATION IS SITE SPECIFIC AND CONSULTATION WITH THE CITY OF MISSISSAUGA MAY BE REQUIRED FOR NON TYPICAL INTERSECTIONS AND PEDESTRIAN CROSSINGS.
4. REFER TO 2240.037 FOR DETAILS ABOUT LOCATION OF TACTILE WALKING SURFACE INDICATORS, CURB CUTS, AND SIDEWALK RAMPS.
5. TACTILE WALKING SURFACE INDICATORS ARE TO BE PLACED 150mm FROM BACK OF CURB TO THE FRONT END CORNERS. A MAXIMUM SPACING OF 200mm FROM THE BACK OF CURB TO THE FRONT EDGE OF THE TACTILE PLATE IS ALLOWED.

All dimensions are in millimetres unless otherwise shown.



SIGNALIZED INTERSECTION
CONFIGURATIONS OF
PEDESTRIAN CROSSINGS

EFF. DATE	DEC 2015	SCALE	N.T.S.
REV.		STANDARD No.	2240.033