



NOTES:

- A. 3.0m MINIMUM FOR SIGNALIZED INTERSECTIONS, 2.5m MINIMUM FOR NON SIGNALIZED INTERSECTIONS WITH PEDESTRIAN CROSSING PAVEMENT MARKINGS, 2.1m MINIMUM FOR NON SIGNALIZED INTERSECTIONS WITHOUT PEDESTRIAN CROSSING PAVEMENT MARKINGS.
- B. WHEN DISTANCE IS LESS THAN 1.2m USE CONTINUOUS DROPPED CURB AT INTERSECTION CORNER. WHEN DISTANCE IS GREATER THAN OR EQUAL TO 1.2m USE TWO SEPARATED DROPPED CURBS AT INTERSECTION CORNER.
- 1. DROPPED CURB TO BE PROVIDED FOR ENTIRE WIDTH OF ALL PEDESTRIAN CROSSINGS.
- 2. TACTILE WALKING SURFACE INDICATORS TO BE PROVIDED ONLY WITHIN WIDTH OF PEDESTRIAN CROSSINGS.
- 3. TACTILE WALKING SURFACE INDICATORS ARE TO BE INSTALLED AT ALL PEDESTRIAN CROSSINGS IN CONJUNCTION WITH ALL ROAD AND SIDEWALK CONSTRUCTION, RECONSTRUCTION AND RESURFACING PROJECTS.
- 4. EACH LOCATION IS SITE SPECIFIC AND CONSULTATION WITH THE CITY OF MISSISSAUGA MAY BE REQUIRED FOR NON TYPICAL INTERSECTIONS AND PEDESTRIAN CROSSINGS.
- 5. REFER TO 2240.033 FOR VARIOUS CONFIGURATIONS OF PEDESTRIAN CROSSINGS AT SIGNALIZED INTERSECTIONS AND 2240.034 FOR CONTROLLED NON SIGNALIZED INTERSECTIONS.
- 6. TACTILE WALKING SURFACE INDICATORS ARE TO BE PLACED 150mm FROM BACK OF CURB TO THE FRONT END CORNERS. A MAXIMUM SPACING OF 200mm FROM THE BACK OF CURB TO THE FRONT EDGE OF THE TACTILE PLATE IS ALLOWED.



LOCATION OF DROPPED CURBS AT CONTROLLED INTERSECTIONS

| | | | |
|-----------|----------|--------------|----------|
| EFF. DATE | DEC 2015 | SCALE | N.T.S. |
| REV. | | STANDARD No. | 2240.037 |

All dimensions are in millimetres unless otherwise shown.