

NOTES

METRIC

ALL DIMENSIONS IN MILLIMETRES

- SIGN TO BE ERECTED IMMEDIATELY AFTER STORMWATER MANAGEMENT FACILITY. CONSTRUCTION AND OPERATION OF THE
- LOCATIONS INDICATED WITH 12MM HEX HEAD BOLTS & NUTS WITH FLAT WASHERS BOTH SIDES. SIGN TO BE MOUNTED TO SUPPORTS AT

2

MOUNTED IN A MANNER ENSURING STABILITY. OF THE CITY OF MISSISSAUGA, BE SURFACE TRANSPORTATION & WORKS DEPARTMENT SIGNS MAY, AT THE DISCRETION OF THE

Ŋ

REQUIRED PRIOR TO INSTALLATION, SEE DESIGN REQUIREMENT 2.09.02 REGARDING THE WORDING OF THE MESSAGE DEPARTMENT OF THE CITY OF MISSISSAUGA APPROVAL OF THE TRANSPORTATION & WORKS

۵,

SUPPORTS **BL ANK SPECIFICATIONS** MATERIAL SIGN COLOUR IZOOXIZOOXZO EXTERIOR GRADE PLYWOOD IOOXIOO WOOD



FACILITY W.	STORMWATER
WARNING SIGN	MANAGEMENT

STANDARD

FACILITY WARNING SIGN	WARNING SIGN	SIGN	
ATE 2002-01-01	SCALE	_	N.T.S.
	STANDARD No. 2940.02	No	2940.02

BACKGROUND

WHITE

MESSAGE AND BORDER

PANTONE 3020

EFF. D REV.