

900 LAKESHORE ROAD WEST
MISSISSAUGA, ON

[illegible][illegible]

1. INTERNAL ROADWAYS MUST BE CONSTRUCTED OF A HARD SURFACE MATERIAL SUCH AS ASPHALT, CONCRETE, OR LOCKSTONE AND DESIGNED TO SUPPORT A MINIMUM OF 35 TONNES. THE WEIGHT OF A FULLY LOADED WASTE COLLECTION VEHICLE. A LETTER CERTIFIED BY A PROFESSIONAL ENGINEER THAT THE STRUCTURE CAN SAFELY SUPPORT FULLY LOADED WASTE COLLECTION VEHICLE WEIGHING 35 TONNES WILL BE PROVIDED.

2. THE MAXIMUM GRADE PERMITTED ALONG THE WASTE COLLECTION VEHICLE ACCESS ROUTE IS 8 PERCENT.

3. AN UNOBSTRUCTED DISTANCE OF 18 METRES IS PROVIDED TO ENABLE THE WASTE COLLECTION VEHICLE TO WHOLLY ENTER THE COLLECTION POINT. THE APPROACH AND COLLECTION POINT IS TO BE LEVEL (+/-2%) AND THE SAME WIDTH AS THE COLLECTION AREA. THE OVERHEAD CLEARANCE OF THE COLLECTION AREA IS 7.5 METRES AND OUTSIDE OF THE COLLECTION AREA IS 4.4 METRES, FREE FROM OBSTRUCTIONS SUCH AS SPRINKLER SYSTEMS, DUCTS, BALCONIES, WIRES, AND TREES.

4. MAXIMUM WALKING DISTANCE FOR OWNERS OF RESIDENTIAL UNITS TO WASTE CHUTES IS LESS THAN 100 METERS

NUMBERS OF UNITS: 188

3 CU/YD BINS FOR COMPACTED GARBAGE 1 BIN / 54 UNITS
TOTAL BINS REQUIRED: 4

3 CU/YD BINS FOR RECYCLING 1 BIN / 45 UNITS
TOTAL BINS REQUIRED: 5



An aerial photograph of a residential neighborhood. A black triangle is superimposed on the image, pointing to a specific location on a road or driveway. The surrounding area includes houses, trees, and a larger building complex on the right side.

TAMP

CLIENT



SCALE: As indicated

DRAWN BY: FC

DRAWING TITLE

DRAWING NO

A005