



#### **PREPARED FOR:**

Edenshaw Elizabeth Developments Limited 129 Lakeshore Rd. E., Suite 201, 2nd Floor Mississauga, ON L5G 1E5

### **ATTENTION:**

Mr. Steven Soldano

23 Elizabeth St. N., 42, 44 & 46 Park St. E. | Mississauga, Ontario **Grounded Engineering Inc. File No.** 20-088 (Rev.1) **Issued** July 31, 2020



# **TABLE OF CONTENTS**

1	EXE	CUTIVE SUMMARY	5	
2	INTF	RODUCTION	6	
	2.1	SITE DESCRIPTION	6	
	2.2	PROPERTY OWNERSHIP	6	
	2.3	CURRENT AND PROPOSED FUTURE USES	7	
	2.4	APPLICABLE SITE CONDITION STANDARD	7	
3	BAC	KGROUND INFORMATION	8	
•	3.1	PHYSICAL SETTING		
	3.2	PAST INVESTIGATIONS		
4	SCO	PE OF THE INVESTIGATION	0	
_	4.1	OVERVIEW OF SITE INVESTIGATION		
	4.2	Media Investigated		
	4.2	4.2.1 Rationale for Exclusion and Inclusion of Media		
		4.2.2 Overview of Field Investigation of Media		
	4.3	PHASE ONE CONCEPTUAL SITE MODEL		
	4.4	DEVIATIONS FROM SAMPLING AND ANALYSIS PLAN	10	
	4.5	IMPEDIMENTS	11	
5	INVE	STIGATION METHOD	11	
	5.1	General		
	5.2	DRILLING	11	
	5.3	SOIL - SAMPLING	11	
		5.3.1 Equipment Used		
	5.4	SOIL - FIELD SCREENING MEASUREMENTS	12	
		5.4.1 Geological Description	12	
	5.5	GROUNDWATER – FIELD MEASUREMENT OF WATER QUALITY PARAMETERS		
	5.6	GROUNDWATER – MONITORING WELL INSTALLATION	12	
	5.7	GROUNDWATER - SAMPLING	13	
	5.8	SEDIMENT – SAMPLING		
	5.9	ANALYTICAL TESTING	13	
	5.10	RESIDUE MANAGEMENT PROCEDURES	13	
	5.11	ELEVATION SURVEYING	14	
	5.12	QUALITY ASSURANCE AND QUALITY CONTROL MEASURES	14	
		5.12.1 Containers, Preservation, Labelling, Handling and Chain of Custody		
		5.12.2 Equipment Cleaning Procedures		
		5.12.3 Field Quality Control Measures and Deviations		
6	REV	IEW AND EVALUATION	15	
	6.1	GEOLOGY		
		6.1.1 Material in Geological Units	16	



		6.1.2	Properties of Aquifers and Aquitards	17
		6.1.3	Rationale for Choice of Aquifers and Aquitards Investigated	17
	6.2	GROU	UNDWATER: ELEVATIONS AND FLOW DIRECTION	17
	6.3	Grou	UNDWATER: HYDRAULIC GRADIENTS	18
	6.4	FINE-	-MEDIUM SOIL TEXTURE	18
	6.5		- FIELD SCREENING	
	6.6		– QUALITY	
	0.0	6.6.1	Location and Depth of Samples	
		6.6.2	Comparison to Applicable Standards	
		6.6.3	Contaminants of Concern	
		6.6.4	Contamination Impact on Other Media	
		6.6.5	Chemical or Biological Transformations	
		6.6.6	Presence of Light or Dense Non-Aqueous Phase Liquids	
	6.7	GROU	UND WATER – QUALITY	20
		6.7.1	Location and Depth of Samples	20
		6.7.2	Comparison to Applicable Standards	21
		6.7.3	Contaminants of Concern	21
		6.7.4	Contamination Impact on Other Media	22
		6.7.5	Chemical or Biological Transformations	
		6.7.6	Presence of Light or Dense Non-Aqueous Phase Liquids	22
	6.8	SEDI	MENT – QUALITY	22
	6.9	QUAL	LITY ASSURANCE AND QUALITY CONTROL RESULTS	22
		6.9.1	Subsection 47 (3) of the Regulation	22
		6.9.2	Laboratory Qualification of Results	23
		6.9.3	Overall Quality of Field Data	23
	6.10		PHASE TWO CONCEPTUAL SITE MODEL	23
7	CON	CLUS	SIONS	23
•	7.1		ATURES	
	7.1	SIGNA	ATURES	24
8	REF	EREN	CES	25
9	LIMI	ΓΑΤΙΟ	NS AND RESTRICTIONS	25
			ORT USE	



#### **TABLES**

- Table 1 Water Levels
- Table 2 Soil Analysis Metals
- Table 3 Soil Analysis Hydride Metals
- Table 4 Soil Analysis Boron
- Table 5 Soil Analysis Hexavalent Chromium
- Table 6 Soil Analysis Cyanide
- Table 7 Soil Analysis Electrical Conductivity
- Table 8 Soil Analysis Mercury
- Table 9 Soil Analysis Sodium Adsorption Ratio
- Table 10 Soil Analysis pH
- Table 11 Soil Analysis Petroleum Hydrocarbons
- Table 12 Soil Analysis Benzene, Toulene, Ethylbenzene, Xylene
- Table 13 Ground Water Analysis Metals
- Table 14 Ground Water Analysis Hydride Metals
- Table 15 Ground Water Analysis Hexavalent Chromium
- Table 16 Ground Water Analysis Cyanide
- Table 17 Ground Water Analysis Mercury
- Table 18 Ground Water Analysis Chloride
- Table 19 Ground Water Analysis Sodium
- Table 20 Ground Water Analysis Petroleum Hydrocarbons
- Table 21 Ground Water Analysis Benzene, Toulene, Ethyl Benzene, and Xylene

# **FIGURES**

- Figure 1 Site Location
- Figure 2 PCA and APEC Locations
- Figure 3 Borehole and Monitoring Well Locations
- Figure 4 Groundwater Elevations and Contours
- Figure 5 Cross Section Locations
- Figure 6 Cross Section A-A'
- Figure 7 Cross Section B-B'
- Figure 8 Human Health Conceptual Site Model
- Figure 9 Ecological Conceptual Site Model

#### **APPENDICES**

- Appendix A Phase One Conceptual Site Model
- Appendix B Sampling and Analysis Plan
- Appendix C Borehole Logs
- Appendix D Grain Size Analysis
- Appendix E Certificates of Analysis
- Appendix F Phase Two Conceptual Site Model



# 1 Executive Summary

Edenshaw Elizabeth Developments Limited retained Grounded Engineering Inc. to complete a Phase Two Environmental Site Assessment (ESA) of the property located northwest of the intersection of Elizabeth St. N., and Park St. E., Mississauga, Ontario (Property). The Property includes the following municipal addresses:

- 23 Elizabeth Street North
- 42 Park Street East
- 44 Park Street East
- 46 Park Street East

The Phase Two ESA was conducted for purpose of due diligence/refinancing and for filing a Record of Site Condition (RSC). The Phase Two ESA is prepared in accordance with Ontario Regulation 153/04 (O.Reg. 153/04).

The results of the Phase Two ESA are summarized below:

Applicable Site Condition Standards	Ministry of Environment, Conservation and Parks (MECP) Table 3 Standards for Residential, Parkland, Institutional Land Use (Table 3 RPI)
Soil Potential Contaminants of Concern (PCoCs) Investigated	Metals     Hydride-forming Metals     Antimony (Sb), Arsenic (As), Selenium (Se)     Selected Other Regulated Parameters (ORPs)     Electrical Conductivity (EC), Sodium Adsorption Ratio (SAR),     Boron-hot water soluble (B-HWS), Cyanide (CN-), Mercury (Hg), Hexavalent Chromium (Cr(VI)), low or high pH     Petroleum Hydrocarbons (PHCs)     Volatile Organic Compounds II (BTEX)
Groundwater PCoCs Investigated	<ul> <li>Metals</li> <li>Hydride-forming Metals         <ul> <li>Antimony (Sb), Arsenic (As), Selenium (Se)</li> </ul> </li> <li>Selected Other Regulated Parameters (ORPs)         <ul> <li>Cyanide (CN-), Sodium (Na), Chloride (Cl), Mercury (Hg), Hexavalent Chromium (Cr(VI))</li> </ul> </li> <li>Petroleum Hydrocarbons (PHCs)</li> <li>Volatile Organic Compounds II (BTEX)</li> </ul>
Applicable Site Condition Standards Met for Soil? (Yes/No)	Yes
Applicable Site Condition Standards Met for Groundwater? (Yes/No)	Yes

A Record of Site Condition (RSC) can be filed for the Property at this time.



# 2 Introduction

# 2.1 Site Description

Edenshaw Elizabeth Developments Limited retained Grounded Engineering Inc. to complete a Phase Two Environmental Site Assessment (ESA) of the property located northwest of the intersection of Elizabeth St. N., and Park St. E., Mississauga, Ontario (Property). The Property includes the following municipal addresses:

- 23 Elizabeth Street North
- 42 Park Street East
- 44 Park Street East
- 46 Park Street East

The site location is presented in Figure 1.

The Property is rectangular in shape, with a total area of 0.18 ha. The Property is bounded by Elizabeth St. N. to the northwest and Park St. E. to the southeast. The Property is currently developed with four (4) residential dwellings each with a basement. The Property is considered to be residential land use by the Ontario Ministry of the Environment, Conservation, and Parks (MECP). The Phase Two ESA has been prepared for purpose of due diligence/financing and for filing a Record of Site Condition (RSC). The Phase Two ESA is prepared in accordance with Ontario Regulation 153/04 (O.Reg. 153/04).

# 2.2 Property Ownership

The Property information is provided below:

	23 Elizabeth Street North Mississauga
Municipal Address	42 Park Street East Mississauga
	44 Park Street East Mississauga
	46 Park Street East Mississauga
Laral Decemention	Plan 300-E Pt Lot 8
Legal Description	Plan 300-E Pt Lot 8 RP 43R2685 Part 1,2,3 and 4
	• 13463-0092 (LT)
PIN(s)	• 13463-0001(LT)
FIN(S)	• 13463-0002(LT)
	• 13463-0003(LT)
Current Land Use	Residential
	Leslie Calhoun
Property Owner Information	Tara Prouty and Patrick Alleguede



	Margaret-Anne Murphy
	Edenshaw Elizabeth Developments Limited
Person who has engaged the	Edenshaw Elizabeth Developments Limited
Qualified Person to conduct the	129 Lakeshore Rd. E., Suite 201, 2nd Floor
Phase One ESA	Mississauga, ON L5G 1E5

# 2.3 Current and Proposed Future Uses

The Property is considered to be residential land use by the Ontario Ministry of the Environment, Conservation and Parks (MECP). It is understood that the Phase Two Property will be redeveloped with a 22-storey high rise residential building and a P6-underground parking. As part of the future development, a 13 m<sup>2</sup> triangular parcel along the intersection of Elizabeth Street North and Park Street East will be conveyed to the City of Mississauga as proposed road-widening.

# 2.4 Applicable Site Condition Standard

The applicable site condition standard for the Phase Two Property is determined to be Table 3 Site Condition Standard for Residential/Parkland/Institutional in non-potable groundwater condition for coarse textured soil due to the following reason:

Current Land Use	Residential Land Use
Future Land Use	Residential Land Use
Soil Texture	Coarse
Potable Water Source	Lake Ontario
Bedrock Depth	Bedrock is located at a depth of greater than 2 m.
Property located within 30 m of a surface water body (Yes/No)	No
Property located in or adjacent to a provincial park or an Area of Natural Significance (Yes/No)	No

Grounded Engineering Inc. notified the Peel Region Clerk of the intention to use non-potable groundwater standards. No objections have been received on July 17, 2020 to the use of non-potable groundwater standards.



# 3 Background Information

# 3.1 Physical Setting

The Ministry of Natural Resources and Forestry (MNRF) and Ministry of Energy, Northern Development and Mines (MENDM) database were searched to obtain topographic and geological maps of Ontario for review. The information obtained are summarized below:

Records	Information
Topographic Maps	The Property is relatively flat lying with an approximate elevation of 80± masl.
Hydrology	The nearest water body is Mary Fix Creek located approximately 150 m to the west of the Property. Credit River is located approximately 390 m to the south of the Property. Lake Ontario is located approximately 450 m to the southeast. As part of the Lake Ontario Waterfront Watershed, groundwater from the Property is expected to flow south towards Credit River then southeast towards Lake Ontario. Surface water is expected to flow into catch basins on and adjacent to the Property.
	Overburden: The overburden at the Property consisting of half coarse-textured glaciolacustrine deposits is comprised of sand, gravel, minor silt and clay. The other half is modern alluvial deposits comprised of clay, silt, sand, gravel and organic remains.
Geological Maps	Bedrock:  The bedrock at the Property is of the Georgian Bay Formation, which is comprised of shale, limestone, dolostone and siltstone.
	Depth to Bedrock:  Based on the subsurface investigation, depth to bedrock on site is approximately 7± m.

Maps from MNRF were reviewed to determine if water bodies were present on the Property and within the Study Area. The Ontario Ministry of Natural Resources National Heritage Information Centre database for Areas of Natural or Scientific Interest (ANSIs) was also reviewed as part of the Phase Two ESA. The information is summarized below:

Water Bodies	Property:  No water bodies are located on the Property.  Study Area:  Mary Fix Creek located approximately 150 m to the west of the Property.
Wetlands	<ul> <li>Property:         <ul> <li>No Provincially Significant, Non-Provincially Significant, and Unevaluated wetlands are located on the Property.</li> </ul> </li> <li>Study Area:         <ul> <li>No Provincially Significant, Non-Provincially Significant, and Unevaluated wetlands are located within the Study Area.</li> </ul> </li> </ul>



ANSIs	Property:
	No Provincially Significant Life Science and Earth Science ANSIs are located on the
	Property.
	Study Area:
	No Provincially Significant Life Science and Earth Science ANSIs are located within the
	Study Area.

The Areas of Natural Significances (ANSIs) and water bodies on or adjacent to the Property is shown in Figure 2.

# 3.2 Past Investigations

The following environmental report was provided for review for the Property. The findings of the report are summarized below:

#### Report 1

Title and File No.	Phase One Environmental Site Assessment, 23 Elizabeth St. N., 44, 42 & 46 Park St. E., Mississauga, Ontario. File No. 20-088
Report Date	May 8, 2020
Prepared By	Grounded Engineering Inc.
Prepared for	Edenshaw Elizabeth Developments Limited
Description of Data,	- The Phase One ESA was conducted in accordance with O.Reg. 153/04
Analysis or	- Mary Fix Creek located approximately 150 m to the west of the Property.
Findings	<ul> <li>Potentially contaminating activities (PCAs) were found on sites located with the Study Area but not on the Phase One Property.</li> </ul>
	- No Area of Potential Environmental Concern (APEC) were identified on the Property.
	- A Phase Two ESA will not be required prior to the submission of a Record of Site
	Condition (RSC). An RSC can be submitted based on the Phase One ESA alone.

The PCAs and APEC locations are provided in Figure 2.

# 4 Scope of the Investigation

# 4.1 Overview of Site Investigation

The scope of the Phase Two ESA is as follow:

Boreholes and Monitoring Wells	<ul> <li>Advancing of 4 boreholes to depths of 8.6 to 23.2 m below ground surface (mbgs)</li> <li>Installation of 4 of monitoring wells</li> </ul>
Parameters Investigated for Soil	<ul> <li>Metals</li> <li>Hydride-forming Metals         <ul> <li>Antimony (Sb), Arsenic (As), Selenium (Se)</li> </ul> </li> <li>Selected Other Regulated Parameters (ORPs)         <ul> <li>Electrical Conductivity (EC), Sodium Adsorption Ratio (SAR), Boron-hot water soluble (B-HWS), Cyanide (CN-), Mercury (Hg), Hexavalent Chromium (Cr(VI)), low or high pH</li> </ul> </li> </ul>



	<ul><li>Petroleum Hydrocarbons (PHCs)</li><li>Volatile Organic Compounds II (BTEX)</li></ul>
Parameters Investigated for Groundwater	<ul> <li>Metals</li> <li>Hydride-forming Metals         <ul> <li>Antimony (Sb), Arsenic (As), Selenium (Se)</li> </ul> </li> <li>Selected Other Regulated Parameters (ORPs)         <ul> <li>Cyanide (CN-), Sodium (Na), Chloride (Cl), Mercury (Hg), Hexavalent Chromium (Cr(VI))</li> </ul> </li> <li>Petroleum Hydrocarbons (PHCs)</li> <li>Volatile Organic Compounds II (BTEX)</li> </ul>

- 3 soil samples were submitted for grain size analysis and soil classification
- All boreholes and monitoring wells are surveyed to a geodetic benchmark
- All monitoring wells are developed and sampled
- Groundwater level measurements are conducted in all monitoring wells to determine groundwater elevation on the Property

# 4.2 Media Investigated

#### 4.2.1 Rationale for Exclusion and Inclusion of Media

Media	Included/Excluded	Rationale	
Soil	Included	Based on the Phase One ESA, no APECs were identified on the Property. Soil sampling was conducted for due diligence/refinancing purpose.	
Sediment	Excluded	Surface water bodies were not presented on the Property. No sediment sampling was conducted during the Phase Two ESA.	
Groundwater	Included	Based on the Phase One ESA, no APECs were identified on the Property. Soil sampling was conducted for due diligence/refinancing purpose.	
Surface Water	Excluded	Surface water bodies were not presented on the Property. No surface water sampling was conducted during the Phase Two ESA.	

#### 4.2.2 Overview of Field Investigation of Media

Soil sampling was conducted during the drilling investigation. Groundwater sampling was conducted in the monitoring wells installed.

# 4.3 Phase One Conceptual Site Model

The Phase One Conceptual Site Model (CSM) prepared as part of the Phase One ESA report is provided in Appendix A.

# 4.4 Deviations From Sampling and Analysis Plan

No deviations from the sampling and analysis plan were observed. The Sampling and Analysis Plan is provided in Appendix B.



# 4.5 Impediments

No impediments were encountered during the Phase Two ESA.

# 5 Investigation Method

#### 5.1 General

The Phase Two ESA followed the methods outlined in the Ontario Ministry of the Environment and Climate Change "Guidance on Sampling and Analytical Methods for Use at Contaminated Sites in Ontario" (December 1996).

The methods used in the Phase Two ESA did not differ from the associated standard operating procedures.

# 5.2 Drilling

The Phase Two ESA drilling information is provided below:

Boreholes	BH1 to BH4	
Date of Work	May 25 to 26, 2020 and June 2 to 3, 2020	
Name of the Contractor(s)	Kodiak Drilling and Landshark Drilling	
Equipment Used	<ul> <li>Track Mounted B57</li> <li>Mini Mole</li> <li>Hollow-stem augers (BH1)</li> <li>Solid-stem augers (BH2 to BH4)</li> <li>Mud rotary and rock coring (BH1)</li> <li>2-inch split spoon soil sampling device</li> </ul>	
Measures for Cross- contamination Prevention	The split spoon sampling device was washed between each sample to prevent potential cross-contamination	
Sampling Frequency	Please refer to the borehole logs in Appendix C for the sampling frequency	

The borehole locations are provided in Figure 3.

# 5.3 Soil - Sampling

#### 5.3.1 Equipment Used

Below is the equipment used during the soil sampling.



- Sampling containers supplied by the laboratories
- Nitrile gloves
- Cooler with ice
- RKI EAGLE 2 gas monitor

# 5.4 Soil - Field Screening Measurements

Hydrocarbon vapour concentrations were screened in each soil sampling, using an RKI Eagle 2 gas monitor. The monitor is calibrated to *n*-hexane prior to field screening as per the calibration procedure outlined by RKI Instruments in "Eagle 2 Operator's Manual, Part Number:71-0154RK" released March 12, 2019. The monitor has a range of 0 to 40,000 parts per million (ppm) and an accuracy of +/- 5%.

Based on field screening measurements and visual and olfactory examination of all soil samples, selected samples were submitted for petroleum hydrocarbon (PHCs) and benzene, ethylbenzene, toluene and xylene (BTEX) laboratory analysis. Complete field screening readings are provided on the borehole logs in Appendix C.

#### 5.4.1 Geological Description

The borehole logs in Appendix C provide an overall geological description of each soil sample collected during the Phase Two ESA.

# 5.5 Groundwater - Field Measurement of Water Quality Parameters

Water quality parameters including temperature, pH, specific conductivity, total dissolved solids were measured using a Hanna Instruments portable meter (Boreholes 1, 2, 3 and 4) prior to sampling.

# 5.6 Groundwater - Monitoring Well Installation

The Phase Two ESA monitoring well installation information is provided below:

Monitoring Wells	BH1 to BH4	
Date of Work	May 25 to 26, 2020 and June 2 to 3, 2020	
Name of the Contractor(s)	Kodiak Drilling and Landshark Drilling.	
Equipment Used	<ul> <li>Track Mounted B57</li> <li>Mini Mole</li> <li>Hollow-stem augers (BH1)</li> <li>Solid-stem augers (BH2 to BH4)</li> <li>Mud rotary and rock coring (BH1)</li> <li>2-inch split spoon soil sampling device</li> </ul>	



Measures for Cross- contamination Prevention	The split spoon sampling device was washed between each sample to prevent potential cross-contamination
Sampling Frequency	No ground water samples were collected during drilling event.
Well Construction	The wells were constructed with 50 mm (2 in.) ID PVC screens and risers. Filter sand was placed around the well screen to approximately 0.3 to 0.6 m above the top of the screen. The wells were then backfilled with bentonite to approximately 0.3 m below ground surface (mbgs). The wells were finished with flush mounts.
Well Development	The monitoring wells were developed on June 5, 2020. Well development was conducted with a hydrolift pump, Low Density Polyethylene (LDPE) tubing and foot valve. A total volume of 395 L of water was removed during the well development. Stabilization of parameters (pH, conductivity, temperature, etc.) of the purged water was monitored before a sample to ensure the samples are representative of the formation water.

The monitoring well locations are provided in Figure 3.

# 5.7 Groundwater - Sampling

The monitoring well was purged and sampled using a bladder pump. The groundwater was purged before sampling to ensure extraction of representative formation groundwater. Stabilization of water quality parameters of the purged water was monitoring before a sample was taken to maintain the equilibrium with the surrounding formation water and produce samples that are representative of the formation water.

Sampling methodology from the Ontario Ministry of the Environment, Conservation and Parks (MECP) "Guidance on Sampling and Analytical Methods for Use at Contaminated Sites In Ontario", MECP "Guide for Completing Phase Two Environmental Site Assessments under Ontario regulation 153/04" and MECP "Protocol for Analytical Methods Used in the Assessment of Properties under Par XV.1 of the Environmental Protection Act" were followed in the collection of the groundwater samples.

# 5.8 Sediment - Sampling

No sediment sampling was conducted as part of this investigation.

# 5.9 Analytical Testing

Analytical Testing of all soil and groundwater samples was conducted by SGS Canada Inc.

# **5.10 Residue Management Procedures**

Residues form the filed investigation were managed accordingly as provided below:

Residues	Management Procedures



Soil Cuttings	Soil cuttings generated during the drilling activities were placed in drums and were removed form the property by the client.
Groundwater	The purged water generated during the well development was allowed to re-infiltrate into the ground on site.
Fluids from Equipment Cleaning	The fluids from cleaning were removed from the Property and disposed by the drilling contractor.

# 5.11 Elevation Surveying

The elevations of the boreholes on the Property were for horizontal coordinates and geodetic elevations with a Trimble R10 Receiver connected to the Global Navigation Satellite System and the Can-Net Virtual Reference Station Network. The elevation of each borehole on the Property is presented on the borehole logs in Appendix C. The groundwater elevation is presented in Figure 4.

# **5.12 Quality Assurance and Quality Control Measures**

#### 5.12.1 Containers, Preservation, Labelling, Handling and Chain of Custody

The following laboratory supplied sample containers were used for all sampling conducted on the Property.

Parameter/Group	Containers	
- aramoto, orosp	Soil	Groundwater
Inorganic Parameters: Chromium hexavalent (CrVI), cyanide (CN-), pH, electrical conductivity (EC) Soil only: boron, hot water soluble (B-HWS), sodium adsorption ratio (SAR) Water only: chloride	250 g soil jar	500 mL PET 60 mL plastic (CrVI) 120 mL plastic (CN-)
Metals		250 mL HDPE (Metals)
Mercury (Hg)		60 mL amber glass (Hg)
Petroleum hydrocarbons (PHCs) F1/ BTEX	100 g soil jar 2 x 40 mL pre-weighed methanol 5 g soil plug	2 x 40 mL amber vial (zero headspace)
PHCs (F2-F4)	100 g soil jar	2 x 100 mL bottles fill to top of label
Toxicity characteristic leaching procedure (TCLP)	250 g soil jar	-

All sampling containers were equipped with laboratory supplied labels. The labels indicated the following information:

Sample ID



- Company name
- Date
- Project number

Samples were placed in coolers with ice after collection for transportation to the laboratory. Sample hold times were met for all submitted soil and groundwater samples. Laboratory supplied Chain of Custody forms were completed for all samples submitted for analysis.

# 5.12.2 Equipment Cleaning Procedures

Equipment	Cleaning Procedures
Soil sampling	Split spoon sampling device was washed between samples to prevent potential cross-contamination.
Groundwater sampling	Water level meter/ water quality monitoring meter was cleaned between monitoring wells.  The bladder of the bladder pump was switched out between monitoring wells.

All other dedicated equipment (nitrile gloves, terracores samplers, tubing) were change between each sample to avoid cross-contamination.

#### 5.12.3 Field Quality Control Measures and Deviations

For quality control purpose, the following actions were taken:

- At least one (1) duplicate sample is submitted for laboratory analysis for every ten (10) samples submitted for laboratory analysis for each sampled medium.
- Daily calibration of field instruments prior to sampling.

No deviations from the quality assurance and quality control measures had occurred.

# 6 Review and Evaluation

# 6.1 Geology

Detailed geological information for the Property is presented on the borehole logs in Appendix C. The geology at the Property is summarized below.

Geological Unit Thickness (Estimate)	
Borehole	BH1 to BH4 Thickness Range (m)
Earth Fill	0.8 to 1.5



Silt and Sand	3.0 to 7.6
Silty Clay (Glacial Till)	4.6 to 7.6
Sandy Silt (Glacial Till)	7.6 to 10.4
Bedrock	8.6 to at least 23.2

Geological Unit Elevations		
Borehole	BH1 to BH4 Elev. Top Range (masl)	Elev. Bottom Range (masl)
Earth Fill	83.4	80.3
Silt and Sand	82.7	75.9
Silty Clay (Glacial Till)	78.2	75.3
Sandy Silt (Glacial Till)	76.6	72.9
Bedrock	74.2	58

# 6.1.1 Material in Geological Units

Geological Units	Description
Earth Fill	Underlying the surficial materials, the boreholes observed a layer of earth fill that extends to depths of 0.8 to 1.1 metres below grade (Elev. 82.7 to 80.3 metres). The earth fill varies in composition but generally consists of silty sand, with trace gravel and trace rootlets. The earth fill is typically dark brown to brown, and moist.
Native Silt and Sand	Native Silt and Sand was encountered in all borehole locations underlying the Earth Fill. The Native Silty Sand unit extends down to depths of 3.0 to 7.6 m below grade (Elev. 75.9 to 78.2 m). The silty sand unit contains trace gravel and trace clay.
Glacial Till	Underlying the silt and sand unit, all the boreholes encountered an undisturbed native glacial till deposit. The upper portion of the till has a matrix of cohesive silty clay (encountered in all but Borehole 3). The till transitions to a cohesive sandy silt till. The till was encountered at 3.0 to 6.1 metres below grade (Elev. 76.8 to 78.2 m).  The upper cohesive till is generally grey, and moist to wet. The upper till contains trace to some gravel and trace sand. The lower cohesionless sandy silt till is generally grey, and moist to wet. This layer contains some clay and some gravel.
Bedrock	The top of inferred bedrock was encountered at depths ranging from 7.6 to 10.4 m in all boreholes across the site (Elev. 72.9 to 74.2± m). Boreholes 2 to 4 inferred the top of weathered bedrock through auger cuttings, split spoon samples, and auger grinding/resistance observations. Boreholes 2 to 4 were terminated due to auger and sampler refusal (at target investigation depth) at elevations ranging



Geological Units	Description
	from Elev. 72.8 to 73.8 m. Borehole 1 recovered rock core from Elev. 71.0 to 58.0 m.  The bedrock beneath the site is the Georgian Bay Formation ("GBF"), which broadly comprises thin to medium bedded grey shale and limestone of Ordovician age. The shale is interbedded with calcareous shale, limestone, dolostone, and calcareous sandstone (conventionally grouped together as "limestone") which are typically laterally discontinuous.

#### 6.1.2 Properties of Aquifers and Aquitards

Aquifers/Aquitards	Description
Earth Fill	The Earth Fill on the Property is considered to be an unconfined aquifer. The earth fill likely drains into the catch basins onsite or storm water systems adjacent to the Property.
Native Silty Sand	The Native Silty Sand underlying the Earth Fill is considered to be an unconfined aquifer.
Glacial Till	The Glacial till underlying the Native Silty Sand is considered to be an aquitard.
Bedrock	The Bedrock is considered to be an aquitard.

### 6.1.3 Rationale for Choice of Aquifers and Aquitards Investigated

The silt and sand and till units were chosen for investigation. This stratum was chosen for investigation because:

- Possibility of free ground water present.
- The likelihood of horizontal migration of groundwater across the site.
- The likelihood of vertical migration of groundwater.

#### 6.2 Groundwater: Elevations and Flow Direction

The monitoring wells were located throughout the Property to satisfy site coverage. Screened intervals of the monitoring wells were selected for the collection of groundwater samples within the desired stratum.

Interface probe measurements were taken and no light non-aqueous phase liquids (LNAPL) or dense non-aqueous phase liquids (DNAPL) were detected. No free-flowing products was encountered on the Property.

Based on the groundwater elevations measured on the Property, the groundwater was determined to flow locally to the south. Regional groundwater flow is expected to flow to the south towards Credit River then eventually Lake Ontario. Groundwater elevation is provided on the borehole logs



in Appendix C and on Table 1. The groundwater flow direction and contour are present in Figure 4.

Additional groundwater data will be required to assess seasonal variability in water quantity and flow direction. Buried utilities are located on the Property above the static water table. It is unlikely that the buried utilities would influence the groundwater flow.

# 6.3 Groundwater: Hydraulic Gradients

Horizontal Hydraulic Gradients	The horizontal hydraulic gradient at the Property was determined to be approximately 0.1 m/m.										
Vertical Hydraulic	The vertical hydraulic gradient at the Property was determined to be approximately 0.3										
Gradients	m/m downwards.										
	■ Earth Fill 1 x 10 <sup>-6</sup> m/s										
Hydraulic	■ Silty Sand 1 x 10 <sup>-7</sup> m/s										
Conductivity	■ Silty Clay (Glacial Till) 3.1 x 10 <sup>-8</sup> m/s										
	<ul> <li>Sandy Silt (Glacial Till) 9.39 x 10<sup>-8</sup> m/s</li> </ul>										

The grain size analysis and rising head test completed at the Property are provided in Appendix D.

#### 6.4 Fine-Medium Soil Texture

Fine-medium soil texture was not used during the Phase Two ESA. All chemical results were compared to the coarse textured standards. Grain size analysis were completed for selected soil samples from the boreholes at the Property. The grain size analysis is provided in Appendix D.

# 6.5 Soil - Field Screening

Hydrocarbon vapour concentrations were screened in each soil sampling, using an RKI Eagle 2 gas monitor. The monitor is calibrated to *n*-hexane prior to field screening as per the calibration procedure outlined by RKI Instruments in "Eagle 2 Operator's Manual, Part Number:71-0154RK" released March 12, 2019. The monitor has a range of 0 to 40,000 parts per million (ppm) and an accuracy of +/- 5%.

Based on field screening measurements and visual and olfactory examination of all soil samples, selected samples were submitted for petroleum hydrocarbon (PHCs) and benzene, ethylbenzene, toluene and xylene (BTEX) laboratory analysis. Complete field screening readings are provided on the borehole logs in Appendix C.



# 6.6 Soil - Quality

### 6.6.1 Location and Depth of Samples

Sample	De	pth	Strata	Metals	H-Metals	ORPs	DUC-/DTEV
ID	mbgs	masl	Strata	Metals	n-ivietais	URPS	PHCs/BTEX
BH1 SS2	0.8 - 1.4	80.4-79.8	Silt and Sand	√	√	√	√
BH1 SS3	1.5 - 2.1	79.7-79.1	Silt and Sand	√	√	√	
BH1 SS5	3.0 - 3.7	78.1-77.5	Glacial Till				√
BH2 SS2	0.8 - 1.2	80.6-80.2	Fill	√	√	√	√
BH2 SS4	2.3 - 2.9	79.1-78.5	Silt and Sand	√	√	√	√
BH3 SS4	2.3 - 2.6	81.2-80.9	Silt and Sand	√	√	√	√
BH3 SS6	4.6 - 4.8	78.9-78.7	Silt and Sand	√	√	√	√
BH4 SS5	3.0 - 3.5	80.3-79.8	Silt and Sand	√	√	√	√
BH4 SS8	7.6 - 8.1	75.7-75.3	Glacial Till	√	√	√	√

# 6.6.2 Comparison to Applicable Standards

The Phase One found that there are <u>no</u> Potential Contaminants of Concern (PCoCs) in the soils. The following parameters were tested for due diligence/refinancing purposes:

- Metals
- Hydride-forming Metals
  - o (Sb), (As), (Se)
- Selected ORPs
  - EC, SAR, B-HWS, CN-, Hg, Cr(VI), pH
- PHCs
- BTEX

The results of the analysis were compared to the applicable Site Condition Standard for the Phase Two Property (Table 3 RPI). The laboratory certificates of analysis are provided in Appendix E, and the results of the soil chemical analysis are provided in Tables 2 to 12 and presented on Figures 6 and 7.

Comparison Table (Table 3 RPI Standard)								
Parameter Analyzed Exceed/Meet Note:								
Metals	Meet	None						



Comparison Table (Table 3 RPI Standard)								
Parameter Analyzed	Exceed/Meet	Note:						
Hydride-forming Metals	Meet	None						
ORPs	Meet	None						
PHCs	Meet	None						
втех	Meet	None						

#### 6.6.3 Contaminants of Concern

No Contaminants of Concern were identified within the earth fill and native soil on the Property.

#### 6.6.4 Contamination Impact on Other Media

No Contaminants of Concern were identified within the earth fill and native soil on the Property. It is unlikely that other media on the Property will be impacted.

# 6.6.5 Chemical or Biological Transformations

No chemical or biological transformations are likely to occur since no Contaminants of Concern were identified in the soil on the Property.

### 6.6.6 Presence of Light or Dense Non-Aqueous Phase Liquids

No light non-aqueous phase liquids (LNAPL) or dense non-aqueous phase liquids (DNAPL) were detected in the soil on the Property.

# 6.7 Ground Water - Quality

### 6.7.1 Location and Depth of Samples

Sample ID	Screer	n Depth	Screen Strata	Metals	H-Metals	ORPs	PHCs/BTEX
Sample ID	mbgs	masl	Screen Strata	ivietais	n-ivietais	ORFS	PHCS/BTEX
BH1	20.1-23.2	61.0-58.0	Bedrock	√	√	√	√
BH2	5.5-8.5	75.9-72.9	Glacial Till	√	√	√	√
внз	5.6-8.7	77.8-74.8	Silt and Sand to Glacial Till	√	√	√	√
ВН4	5.6-8.7	77.7-74.7	Silty Sand to Glacial Till	√	√	√	√



Field filtering as per the requirements of the MECP "Protocol for Analytical Methods Used in the Assessment of Properties under Part XV.1 of the Environmental Protection Act" July 2011, was completed.

#### 6.7.2 Comparison to Applicable Standards

Selected groundwater samples were analyzed for Potential Contaminants of Concern (PCoCs) of the following:

- Metals
- Hydride-forming Metals
  - o Sb, As, Se
- Selected ORPs
  - CN-, Hg, Cr(VI), Na, Cl
- PHCs
- BTEX

The results of the analysis were compared to the applicable Site Condition Standard for the Phase Two Property (Table 3 RPI). The laboratory certificates of analysis are provided in Appendix E, and the results of the groundwater chemical analysis are provided in Tables 13 to 21.

Comparison Table (Table 3 RPI Standard)										
Parameter Analyzed	Exceed/Meet	Note:								
Metals	Meet	None								
Hydride-forming Metals	Meet	None								
ORPs	Meet	BH1								
PHCs	Meet	None								
втех	Meet	None								

#### 6.7.3 Contaminants of Concern

No Contaminants of Concern were identified in the groundwater on the Property.

The QP deemed the Na and CI parameter in groundwater to be met as per the O.Reg.153/04 49.1 "The qualified person determined, based on a phase one environmental site assessment or a phase two environmental site assessment, that a substance has been applied to surface for the safety vehicular or pedestrian traffic under conditions of snow or ice or both".



#### 6.7.4 Contamination Impact on Other Media

No Contaminants of Concern were identified with the groundwater on the Property. It is unlikely that other media on the Property will be impacted.

#### 6.7.5 Chemical or Biological Transformations

No chemical or biological transformations are likely to occur since no Contaminants of Concern were identified in the groundwater on the Property.

#### 6.7.6 Presence of Light or Dense Non-Aqueous Phase Liquids

No light non-aqueous phase liquids (LNAPL) or dense non-aqueous phase liquids (DNAPL) were detected in the soil on the Property.

# 6.8 Sediment - Quality

Sediment was not present at the Property thus was not investigated as part of the Phase Two ESA.

# 6.9 Quality Assurance and Quality Control Results

Quality Assurance (QA) and Quality Control (QC) were maintained as per described in Section 5.12 above. In addition, laboratory results were compared to MECP standards for QA/QC under Ontario Regulation 153/04 which requires laboratory results to meet specific method detection limit (MDL) conditions. The sampling and analysis performed conformed with the following guidelines:

- 1. Ministry of the Environment, Conservation and Parks Guidance on Sampling and Analytical Methods for Use at Contaminated Sites in Ontario.
- 2. Protocol of Analytical Methods Used in the Assessment of Properties under Part XV.1 of the Environmental Protection Act of Ontario.

Duplicated samples were submitted at a rate of 10% for both soil and groundwater samples.

All the samples collected and submitted for analysis adhered to the holding times, preservation methods, storage requirement and container type as specified by the guidelines listed above.

#### 6.9.1 Subsection 47 (3) of the Regulation

All certificates of analysis or analytical reports received pursuant to clause 47 (2) (b) of the regulation comply with subsection 47 (3). A certificate of analysis or analytical report has been received for each sample submitted for analysis. All certificates of analysis or analytical reports received have been in full in an appendix to the Phase Two ESA report.



#### 6.9.2 Laboratory Qualification of Results

The laboratory did not make any significant comments that changed the outcome of the analytical results regarding the soil and groundwater samples.

#### 6.9.3 Overall Quality of Field Data

The overall quality of the field data was deemed to be acceptable by the Qualified Person.

# 6.10 Phase Two Conceptual Site Model

Phase Two Conceptual Site Model (CSM) is prepared for the Property and is provided in Appendix F.

# 7 Conclusions

The location and concentration of contamination is provided below:

Land	No exceedances of the applicable Site Condition Standards were identified in the soil on the Property.
Groundwater	No exceedances of the applicable Site Condition Standards were identified in the ground water on the Property.

No exceedances of the applicable Site Condition Standards were identified for the soil and groundwater on the Property. As such, no remediation or a risk assessment (RA) will be required. A Record of Site Condition (RSC) can be field for the Property.

Whether applicable Site Condition Standards and standards specified in a risk assessment for contaminants on, in or under the Phase Two Property were met as of the certification date is provided below:

Soil	Earth Fill	The applicable Site Condition Standards were met in the earth fill located on the Property.
3011	Native	The applicable Site Condition Standards were met in the native located on the Property.
Groundwater		The applicable Site Condition Standards were met in the groundwater located on the Property.



# 7.1 Signatures

The Phase Two ESA has been completed in accordance with 0. Reg. 153/04 by, Jessie Hui Chung Wu, M.Env.Sc., under the direction and supervision of Matthew Bielaski, P. Eng., QP RA-ESA. The findings and conclusions presented in this report have been determined based on the information that was obtained and reviewed from previous investigations provided and on the current investigation for the Phase Two Property.

We trust that this report meets your requirements at present.

For and on behalf of our team,



Jessie Hui Chung Wu, M.Env.Sc.

Matthew Bielaski, P.Eng., QP RA-ESA Principal

100131738



### 8 References

- 1. Armstrong, D.K. and Dodge, J.E.P. 2007. Paleozoic Geology Map of Southern Ontario. Ontario Geological Survey. Miscellaneous Release--Data 219.
- 2. Chapman, L.J. and Putnam, D.F. 2007. The Physiography of Southern Ontario. Ontario Geological Survey. Miscellaneous Release--Data 228.
- 3. Gao, C., Shirota, J., Kelly, R. I., Brunton, F.R., van Haaften, S. 2006. Bedrock topography and overburden thickness mapping, southern Ontario. Ontario Geological Survey. Miscellaneous Release--Data 207.
- 4. Ontario Geological Survey 2011. 1:250,000 scale bedrock geology of Ontario. Ontario Geological Survey. Miscellaneous Release---Data 126-Revision 1.
- 5. Ontario Geological Survey. 2010. Surficial geology of Southern Ontario. Ontario Geological Survey. Miscellaneous Release—Data 128-Revised.
- 6. Ontario Geological Survey. 2000. Quaternary geology, seamless coverage of the Province of Ontario. Ontario Geological Survey. Data Set 14---Revised.
- 7. Grounded Engineering Inc. Phase One Environmental Site Assessment, 20 Elizabeth St., N., 44, 42 & 46 Park St. E., Mississauga, Ontario. File No. 20-088 (Rev.1). May 8, 2020.

# 9 Limitations and Restrictions

The Phase Two ESA report was prepared for the purpose of identifying potential environmental concerns, including an assessment of the likelihood that the environmental quality of the soil and groundwater at the Property may have been adversely affected by past or present practices at the Property, and/or those of the adjacent properties prior to development of the Property. Any use of which a third party makes of this report, or any reliance on or decision to be made based on it, are the responsibility of such third parties. Grounded Engineering Inc. does not assume any responsibility for errors, omissions, damages or other limitation pertaining to third parties.

The information presented in this report is based on information collected during the completion of the subsurface investigation conducted by Grounded Engineering Inc. It is based on conditions at the Property at the time of the inspection. The subsurface conditions were assessed based on information collected at specific borehole and monitoring well locations. The actual subsurface conditions between sampling points may be different.

The conclusions presented in this report are based on work undertaken by trained professional and technical staff and are the product of professional care and competence. The report cannot be construed as legal advice or as an absolute guarantee.

If new information regarding the environmental condition of the Phase Two Property is identified during future work, or outstanding responses from regulatory agencies indicate outstanding issues on file with respect to the Phase Two Property, Grounded Engineering Inc. should be notified so that we may re-evaluate the findings of this assessment and provide amendments.



# 9.1 Report Use

The authorized users of this report are Edenshaw Elizabeth Developments Limited, for whom this report has been prepared. Grounded Engineering Inc. maintains the copyright and ownership of this document. Reproduction of this report in any format or medium requires explicit prior authorization from Grounded Engineering Inc.

# **TABLES**



Table 1: GROUNDWATER ELEVATION 23 Elizabeth St. N.

Consultant	Monitoring Well ID	05-Jun-20	10-Jun-20	12-Jun-20	18-Jun-20	20-Jul-20	
Consultant	Well id	<b>GW Elevation (masl)</b>	<b>GW Elevation (masl)</b>	<b>GW Elevation (masl)</b>	<b>GW Elevation (masl)</b>	GW Elevation (masl)	
	BH1	76.3	73.4	68.4	68.5	68.6	
Grounded	BH2	76.4	76.4	76.5	76.5	76.7	
Engineering	BH3	80.2	79.7	79.4	79.8	79.5	
	BH4	80.5	80.4	80.4	80.3	79.9	

NA – Monitoring wells could not be located or monitored

NM – Not Measured

TABLE 2 SOIL QUALITY ANALYSIS METALS 23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name					BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID #		MECP Table 3			CA14778- JUN20	CA14778- JUN20	CA14830- JUN20	CA14830- JUN20	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20
	Units	2011 Criteria	RDL	Maximum	8	9	8	9	8	9	10	11	12
Date		RPI CT			2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)					1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)					79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter													
Barium	µg/g	390	0.01	60	43	35	50	55	25	12	13	60	13
Beryllium	µg/g	4	0.02	0.62	0.33	0.27	0.36	0.33	0.15	0.12	0.13	0.62	0.15
Boron	μg/g	120	1	12	3	2	4	6	3	2	3	12	3
Cadmium	µg/g	1.2	0.02	0.12	0.07	0.05	0.10	0.07	0.03	0.04	0.04	0.12	0.03
Chromium	μg/g	160	0.5	22	13	12	16	16	6.8	5.8	5.4	22	6.5
Cobalt	μg/g	22	0.01	14	7.7	5.9	7.9	7.4	3.7	2.7	3.4	14	4.1
Copper	µg/g	140	0.1	29	18	15	19	18	9	9	9	29	9
Lead	μg/g	120	0.1	11	6.2	4.8	11	5.6	3.3	2.5	2.6	7.3	3.2
Molybdenum	μg/g	6.9	0.1	0.4	0.2	0.3	0.4	0.2	0.1	0.1	0.1	0.3	0.2
Nickel	μg/g	100	0.1	31	16	12	16	15	7	5	6	31	7
Silver	μg/g	20	0.01	< 0.01	< 0.05	< 0.05	< 0.05	< 0.05	<0.05	< 0.05	<0.05	<0.05	< 0.05
Thallium	μg/g	1	0.02	0.14	0.09	0.08	0.09	0.09	0.04	0.03	0.03	0.14	0.04
Uranium	µg/g	23	0.002	0.66	0.38	0.35	0.38	0.41	0.46	0.36	0.31	0.66	0.31
Vanadium	µg/g	86	3	27	22	19	27	24	12	12	11	27	12
Zinc	μg/g	340	0.7	67	35	26	47	33	15	11	14	67	16

TABLE 3 SOIL QUALITY ANALYSIS HYDRIDE METALS 23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name					BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID#	Units	MECP Table 3 2011 Criteria RPI CT	RDL	Maximum	CA14778- JUN20 8	CA14778- JUN20	CA14830- JUN20	CA14830- JUN20 9	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20 10	CA14915- MAY20	CA14915- MAY20
Date					2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)					1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)					79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter													
Antimony	μg/g	7.5	0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Arsenic	μg/g	18	0.5	4.6	2.7	2.3	2.8	2	2.2	1.1	1.1	4.6	1.2
Selenium	μg/g	2.4	0.7	< 0.7	< 0.7	< 0.7	< 0.7	< 0.7	< 0.7	< 0.7	< 0.7	< 0.7	< 0.7

Comments:
Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition

RDL - Reported Detection Limit; G / S - Guideline / Standard

<150

Detection limit exceeded Standard <150 150 Sample result exceeded Standard

TABLE 4
SOIL QUALITY ANALYSIS
BORON - HOT WATER SOLUBLE
23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name				Maximum	BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID #	Units	MECP Table 3 2011 Criteria RPI CT	RDL		CA14778- JUN20 8	CA14778- JUN20 9	CA14830- JUN20 8	CA14830- JUN20 9	CA14915- MAY20 8	CA14915- MAY20 9	CA14915- MAY20 10	CA14915- MAY20	CA14915- MAY20 12
Date	Ī				2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)	Ī				1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)	Ī				79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter	Ĭ												
Boron (Hot Water Soluble)	μg/g	1.5	0.5	8.0	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5	8.0	< 0.5

#### Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition RDL - Reported Detection Limit; G / S - Guideline / Standard

Detection limit exceeded Standard 150 Sample result exceeded Standard

TABLE 5 SOIL QUALITY ANALYSIS HEXAVALENT CHROMIUM 23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name					BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID#	Units	MECP Table 3	RDL	Maximum	CA14778- JUN20 8	CA14778- JUN20 9	CA14830- JUN20 8	CA14830- JUN20 9	CA14915- MAY20 8	CA14915- MAY20 9	CA14915- MAY20 10	CA14915- MAY20 11	CA14915- MAY20 12
Date	Ī	2011 Criteria RPI CT			2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)	Ī				1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)	Ī				79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter													
Chromium VI	μg/g	8	0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2

#### Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition RDL - Reported Detection Limit; G / S - Guideline / Standard

Detection limit exceeded Standard 150 Sample result exceeded Standard

TABLE 6 SOIL QUALITY ANALYSIS CYANIDE 23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name				Maximum	BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID#	Units	MECP Table 3 2011 Criteria	RDL		CA14778- JUN20 8	CA14778- JUN20 9	CA14830- JUN20 8	CA14830- JUN20 9	CA14915- MAY20 8	CA14915- MAY20 9	CA14915- MAY20 10	CA14915- MAY20 11	CA14915- MAY20 12
Date	1	RPICT			2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)	1				1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)	1				79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter	1												•
Cyanide (CN-)	µg/g	0.051	0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05

Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition RDL - Reported Detection Limit; G/S - Guideline / Standard

- 150

Detection limit exceeded Standard

Sample result exceeded Standard

TABLE 7 SOIL QUALITY ANALYSIS ELECTRICAL CONDUCTIVITY 23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

			î.										
Sample Name		MECP Table 3 2011 Criteria RPI CT			BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID #	Units		RDL	Maximum	CA14778- JUN20 8	CA14778- JUN20 9	CA14830- JUN20 8	CA14830- JUN20 9	CA14915- MAY20 8	CA14915- MAY20 9	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20 12
Date					2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)	Ī				1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)					79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter													
Electrical Conductivity	mS/cm	0.7	0.002	0.51	0.46	0.51	0.15	0.16	0.16	0.14	0.15	0.22	0.22

#### Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition RDL - Reported Detection Limit; G / S - Guideline / Standard

Detection limit exceeded Standard 150 Sample result exceeded Standard

TABLE 8
SOIL QUALITY ANALYSIS
MERCURY
23 Elizabeth St N
Mississauga, Ontario
PROJECT #20-088

Sample Name				Maximum	BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4- SS5
COC ID #	Units	MECP Table 3 2011 Criteria	RDL		CA14778- JUN20 8	CA14778- JUN20 9	CA14830- JUN20 8	CA14830- JUN20 9	CA14915- MAY20 8	CA14915- MAY20 9	CA14915- MAY20 10	CA14915- MAY20 11	CA14915- MAY20 12
Date		RPI CT			2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)		1			1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)					79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter													
Mercury	μg/g	0.27	0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05

Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition RDL - Reported Detection Limit;

G / S - Guideline / Standard

Otto Detection limit exceeded Standard

Otto Detection limit exceeded Standard

Sample result exceeded Standard

TABLE 9
SOIL QUALITY ANALYSIS
SODIUM ADSORPTION RATIO
23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name					BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID#	Units	MECP Table 3	RDL	Maximum	CA14778- JUN20 8	CA14778- JUN20 9	CA14830- JUN20 8	CA14830- JUN20 9	CA14915- MAY20 8	CA14915- MAY20 9	CA14915- MAY20 10	CA14915- MAY20 11	CA14915- MAY20 12
Date		2011 Criteria RPI CT			2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)	Ī				1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)					79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter	1												
Sodium Adsorption Ratio		5	0.2	3.5	3.2	3.5	< 0.2	0.6	0.4	0.3	0.3	1.1	0.4

#### Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition RDL - Reported Detection Limit; G / S - Guideline / Standard

Detection limit exceeded Standard

150 Sample result exceeded Standard
SAR were determined on the DI water extract obtained from the 2:1 leaching procedure (2 parts DI water:1 part soil).

TABLE 10 SOIL QUALITY ANALYSIS pH 23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name					BH1-SS2	BH1-SS3	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID#	Units	MECP Table 3	RDL	Maximum	CA14778- JUN20 8	CA14778- JUN20 9	CA14830- JUN20 8	CA14830- JUN20 9	CA14915- MAY20 8	CA14915- MAY20 9	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20
Date	1	2011 Criteria RPI CT			2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)		1			1.4	2.1	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)	Ī				79.8	79	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter	Ī												
рН	-	-	0.05	8.22	7.84	7.79	7.85	7.83	8.06	8.14	7.86	8.22	8.06

## Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition RDL - Reported Detection Limit; G / S - Guideline / Standard

Detection limit exceeded Standard

150
Sample result exceeded Standard
SAR were determined on the DI water extract obtained from the 2:1 leaching procedure (2 parts DI water:1 part soil).

TABLE 11 SOIL QUALITY ANALYSIS BENZENE, TOULENE, ETHYLBENZENE, XYLENE 23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name					BH1-SS2	BH1-SS5	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4-SS5
COC ID #	Units	MECP Table 3	RDL	Maximum	CA14778- JUN20 8	CA14778- JUN20 10	CA14830- JUN20 8	CA14830- JUN20 9	CA14915- MAY20 8	CA14915- MAY20	CA14915- MAY20 10	CA14915- MAY20	CA14915- MAY20 12
Date		2011 Criteria RPI CT			2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)		141.01			1.4	3.7	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)					79.8	77.5	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter													
Moisture	%	-	1	21.6	15.6	21.6	14.3	8.4	3.1	15.6	17.3	9.9	16.7
Benzene	μg/g	0.21	0.02	< 0.02	< 0.02	< 0.02	< 0.02	< 0.02	< 0.02	< 0.02	< 0.02	< 0.02	< 0.02
Ethylbenzene	μg/g	2	0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Toluene	μg/g	2.3	0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Xylene Mixture	μg/g	3.1	0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
m/p-xylene	μg/g	-	0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
o-xylene	μg/g	-	0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05

## Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition

RDL - Reported Detection Limit; G / S - Guideline / Standard

<150 Detection limit exceeded Standard

150 Sample result exceeded Standard

Results are based on sample dry weight.

Linearity is within 15%.

Extraction and holding times were met for this sample.

Quality Control Data is available upon request.

NV- No Value

TABLE 12 SOIL QUALITY ANALYSIS PETROLEUM HYDROCARBONS 23 Elizabeth St N Mississauga, Ontario PROJECT #20-088

Sample Name					BH1-SS2	BH1-SS5	BH2/SS2	BH2/SS4	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP-BH4- SS5
COC ID #		MECP			CA14778- JUN20	CA14778- JUN20	CA14830- JUN20	CA14830- JUN20	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20	CA14915- MAY20
	Units	Table 3 2011 Criteria	RDL	Maximum	8	10	8	9	8	9	10	11	12
Date		RPI CT			2-Jun-20	2-Jun-20	8-Jun-20	9-Jun-20	25-May-20	25-May-20	25-May-20	25-May-20	25-May-20
Depth of Sample (m)					1.4	3.7	1.2	2.9	2.6	4.8	3.5	8.1	3.5
Elev of Sample (masl)					79.8	77.5	80.2	78.5	80.9	78.7	79.8	75.3	79.8
Parameter													
Moisture	%	-	1	21.6	15.6	21.6	14.3	8.4	13.1	15.6	17.3	9.9	16.7
F1 (C6 to C10)	μg/g	55	10	< 10	< 10	< 10	< 10	< 10	< 10	< 10	< 10	< 10	< 10
F1-BTEX (C6-C10)	μg/g	55	10	< 10	<10	<10	< 10	< 10	<10	<10	<10	<10	<10
F2 (C10 to C16)	μg/g	98	10	22	<10	<10	< 10	< 10	<10	<10	<10	22	<10
F3 (C16 to C34)	μg/g	300	50	57	< 50	< 50	< 50	< 50	< 50	< 50	< 50	57	< 50
F4 (C34 to C50)	μg/g	2800	50	< 50	< 50	< 50	< 50	< 50	< 50	< 50	< 50	< 50	< 50
Total Hydrocarbons (C6-C50)	μg/g	-											
Gravimetric Heavy Hydrocarbons	μg/g	2800	200	< 200									
Chromatogram returned to baseline at nC50	-	-	•		YES								
				·									

#### Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for Residential/Parkland/Institutional Land Use in a Coarse-Textured Soil Condition

RDL - Reported Detection Limit; G / S - Guideline / Standard

<150 Detection limit exceeded Standard

150 Sample result exceeded Standard

Results are based on sample dry weight.

The C6-C10 fraction is calculated using toluene response factor.

The C10 - C16, C16 - C34, and C34 - C50 fractions are calculated using the average response factor for n-C10, n-C16, and n-C34.

Gravimetric Heavy Hydrocarbons are not included in the Total C16-C50 and are only determined if the chromatogram of the C34 - C50 hydrocarbons indicates that hydrocarbons >C50 are present.

Total C6 - C50 results are corrected for BTEX contributions.

This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.

nC6 and nC10 response factors are within 30% of Toluene response factor.

nC10, nC16 and nC34 response factors are within 10% of their average. C50 response factor is within 70% of nC10 + nC16 + nC34 average.

Linearity is within 15%.

Extraction and holding times were met for this sample.

Fractions 1-4 are quantified with the contribution of PAHs. Under Ontario Regulation 153, results are considered valid without determining the PAH contribution if not requested by the client.

Quality Control Data is available upon request.

TABLE 13 **GROUND WATER QUALITY ANALYSIS** METALS SITE 23 Elizabeth St N Mississauga, ONTARIO PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	DUP
COC ID #		MECP			CA14202-JUN20	CA14202-JUN20	CA14202-JUN20	CA14202-JUN20	CA14202-JUN20
Date	Units	Table 3	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20
Depth of Sample (m)	Units	2011 Criteria	KUL	waximum	20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	20.1-23.2
Elev of Sample (masl)		CT			61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	61.0-58.0
Parameter									
Barium	μg/L	29000	0.02	365	349	49	160	93	365
Beryllium	μg/L	67	0.007	0.01	0.01	<0.007	<0.007	<0.007	0.01
Boron (total)	μg/L	45000	2	1490	1440	1050	250	111	1490
Cadmium	μg/L	2.7	0.003	0.13	0.130	0.004	< 0.003	0.008	0.110
Chromium Total	μg/L	810	0.03	1.13	1.13	0.17	0.24	0.24	0.98
Cobalt	μg/L	66	2	1.73	1.730	0.059	0.276	0.635	1.690
Copper	μg/L	87	0.02	6.9	6.60	1.80	0.80	3.20	6.90
Lead	μg/L	25	0.01	0.07	0.01	0.04	0.04	0.05	0.07
Molybdenum	μg/L	9200	0.01	16.4	10.90	16.40	3.97	2.05	11.00
Nickel	μg/L	490	0.1	5.3	5.200	0.300	1.400	3.800	5.300
Silver	μg/L	1.5	0.002	0.07	< 0.05	< 0.05	< 0.05	< 0.05	0.070
Thallium	μg/L	510	0.005	0.06	0.060	0.019	0.005	0.024	0.060
Uranium	μg/L	420	0.002	3.06	1.26	0.70	1.45	3.06	1.35
Vanadium	μg/L	250	0.01	1.5	0.46	1.50	0.48	0.35	0.45
Zinc	μg/L	1100	2	14	14	3	2	4	14
İ									

## Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for All Property Use in a Coarse Textured Soil Condition

RDL - Reported Detection Limit; G / S - Guideline / Standard

- 150

Sample result exceeded Standard

Sample result exceeded Standard

TABLE 14 GROUND WATER QUALITY ANALYSIS HYDRIDE METALS SITE 23 Elizabeth St N Mississauga, ONTARIO PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	DUP	
COC ID#		MECP			CA14202-	CA14202-	CA14202-	CA14202-	CA14202-	
COC ID #		Table 3			JUN20	JUN20	JUN20	JUN20	JUN20	
Date	Units	2011 Criteria	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20	
Depth of Sample (m)		CT			20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	20.1-23.2	
Elev of Sample (masl)		C1			61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	61.0-58.0	
Parameter										
Antimony	μg/L	20000	0.02	1.5	1.01	1.5	1.05	0.63	1.02	
Arsenic	μg/L	1900	0.2	2.6	0.5	2.6	1.8	0.6	0.4	
Selenium	μg/L	63	0.04	0.77	0.77	0.17	0.04	0.36	0.46	

## Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for All Property Use in a Coarse Textured Soil Condition RDL - Reported Detection Limit; G / S - Guideline / Standard

<150</p>
Detection limit exceeded Standard

Sample result exceeded Standard

TABLE 15 GROUND WATER QUALITY ANALYSIS HEXAVALENT CHROMIUM SITE 23 Elizabeth St N Mississauga, ONTARIO PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	DUP
COC ID#		MECP			CA14202-	CA14202-	CA14202-	CA14202-	CA14202-
COC ID #		Table 3			JUN20	JUN20	JUN20	JUN20	JUN20
Date	Units	2011 Criteria	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20
Depth of Sample (m)		CT			20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	20.1-23.2
Elev of Sample (masl)		C1			61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	61.0-58.0
Parameter									
Chromium VI	μg/L	140	0.2	< 0.2	< 20	< 0.2	< 0.2	< 0.2	< 20

Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for All Property Use in a Coarse Textured Soil Condition RDL - Reported Detection Limit; 6 / S - Guideline / Standard

<150
Detection limit exceeded Standard

3150
Sample result exceeded Standard

TABLE 16
GROUND WATER QUALITY ANALYSIS
CYANIDE
SITE 23 Elizabeth St N
Mississauga, ONTARIO
PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	DUP
COC ID#	11-14-	MECP Table 3	PD1		CA14202- JUN20	CA14202- JUN20	CA14202- JUN20	CA14202- JUN20	CA14202- JUN20
Date	Units	2011 Criteria	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20
Depth of Sample (m)		CT			20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	20.1-23.2
Elev of Sample (masl)					61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	61.0-58.0
Parameter									
Cyanide (CN-)	μg/L	66	2	< 2	<2	<2	<2	<2	<2
							_		

Results compared to MECP 2011 Table 3 Site Condition Standards for All Property Use in a Coarse Textured Soil Condition RDL - Reported Detection Limit; G / S - Guideline / Standard Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Condition RDL - Reported Detection Limit; and Coarse Textured Soil Coarse RDL - Reported Detection Limit; and Coarse RDL - Reported Detection Limi

Sample result exceeded Standard

NV-No Value

TABLE 17 **GROUND WATER QUALITY ANALYSIS** MERCURY SITE 23 Elizabeth St N Mississauga, ONTARIO PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	DUP
COC ID#		MECP			CA14202-	CA14202-	CA14202-	CA14202-	CA14202-
COC ID#		Table 3			JUN20	JUN20	JUN20	JUN20	JUN20
Date	Units	2011 Criteria	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20
Depth of Sample (m)					20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	20.1-23.2
Elev of Sample (masl)		СТ	Ì		61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	61.0-58.0
Parameter									
							.0.04		
Mercury	μg/L	0.29	0.01	< 0.01	<0.01	<0.01	<0.01	<0.01	<0.01

### Comments:

150 Sample result exceeded Standard

TABLE 18 **GROUND WATER QUALITY ANALYSIS** CHLORIDE SITE 23 Elizabeth St N Mississauga, ONTARIO PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	DUP
COC ID#		MECP Table 3			CA14202- JUN20	CA14202- JUN20	CA14202- JUN20	CA14202- JUN20	CA14202- JUN20
Date	Units	2011 Criteria	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20
Depth of Sample (m)		СТ			20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	20.1-23.2
Elev of Sample (masl)					61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	61.0-58.0
Parameter									
Chloride	ug/L	2300000	200	21000000	21000000	140000	120000	64000	20000000

#### Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for All Property Use in a Coarse Textured Soil Condition

RDL - Reported Detection Limit; G / S - Guideline / Standard

DetectioN limit raised, RDL = 2500μg/L, Dilution required due to high concentration of test analyte(s)

Detection limit exceeded Standard

Sample result exceeded Standard

NV-No Value

TABLE 19
GROUND WATER QUALITY ANALYSIS SODIUM
SITE 23 Elizabeth St N
Mississauga, ONTARIO
PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	DUP
COC ID#		MECP			CA14202-	CA14202-	CA14202-	CA14202-	CA14202-
-		Table 3			JUN20	JUN20	JUN20	JUN20	JUN20
Date	Units	2011 Criteria	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20
Depth of Sample (m)		CT Criteria			20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	20.1-23.2
Elev of Sample (masl)		01			61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	61.0-58.0
Parameter									
Sodium	μg/L	490,000	10	<u>8090000</u>	8090000	97200	43600	30100	7880000

### Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for All Property Use in a Coarse Textured Soil Condition

RDL - Reported Detection Limit; G / S - Guideline / Standard

DetectioN limit raised, RDL = 5000μg/L, Dilution required due to high concentration of test analyte(s)

<150 150 Detection limit exceeded Standard

NV-No Value

Sample result exceeded Standard

TABLE 20 **GROUND WATER QUALITY ANALYSIS** PETROLEUM HYDROCARBONS SITE 23 Elizabeth St N Mississauga, ONTARIO PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	DUP
COC ID#		MECP			CA14202-	CA14202-	CA14202-	CA14202-	CA14202-
COC ID#					JUN20	JUN20	JUN20	JUN20	JUN20
Date	Units	Table 3	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20
Depth of Sample (m)		2011 Criteria CT			20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	20.1-23.2
Elev of Sample (masl)		C1			61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	61.0-58.0
Parameter									
F1 (C6 to C10)	ug/L	750	25	< 25	<25	<25	<25	<25	<25
F1-BTEX (C6-C10)	ug/L	750	25	< 25	<25	<25	<25	<25	<25
F2 (C10 to C16)	ug/L	150	100	< 100	<100	<100	<100	<100	<100
F2-Naphthalene (C10-C16)	ug/L	150	100						
F3 (C16 to C34)	ug/L	500	200	< 200	<200	<200	<200	<200	<200
F3-PAHs (C16 to C34)	ug/L	500	200						
F4 (C34 to C50)	ug/L	500	200	< 200	<200	<200	<200	<200	<200
Reached Baseline at C50	Y/N			-	YES	YES	YES	YES	YES

#### Comments:

Results compared to MECP 2011 Table 3 Site Condition Standards for All Property Use in a Coarse Textured Soil Condition

RDL - Reported Detection Limit; G / S - Guideline / Standard

Detection limit exceeded Standard

Sample result exceeded Standard

The C6-C10 fraction is calculated using Toluene response factor.

The C10 - C16, C16 - C34, and C34 - C50 fractions are calculated using the average response factor for n-C10, n-C16, and nC34.

Gravimetric Heavy Hydrocarbons are not included in the Total C16 - C50 and are only determined if the chromatogram of the C34 - C50 Hydrocarbons indicated that hydrocarbons >C50 are present.

Total C6-C50 results are corrected for BTEX and PAH contributions.

This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.

nC6 and nC10 response factors are within 30% of Toluene response factor.

nC10, nC16 and nC34 response factors are within 10% of their average.

C50 response factor is within 70% of nC10 + nC16 nC34 average.

Linearity is within 15%.

Extraction and holding times were met for this sample.

+ - Insufficient water for sampling

TABLE 21 GROUND WATER QUALITY ANALYSIS BENZENE, TOLUENE, ETHYL BENZENE AND XYLENE SITE 23 Elizabeth St N Mississauga, ONTARIO PROJECT #20-088

Sample Name					BH1	BH2	BH3	BH4	Trip Blank	DUP
COC ID #		MECP			CA14202-	CA14202-	CA14202-	CA14202-	CA14202-	CA14202-
CCC 1D #		Table 3			JUN20	JUN20	JUN20	JUN20	JUN20	JUN20
Date	Units	2011 Criteria	RDL	Maximum	12-Jun-20	12-Jun-20	10-Jun-20	10-Jun-20	12-Jun-20	12-Jun-20
Depth of Sample (m)		CT			20.1-23.2	5.5-8.5	5.6-8.7	5.6-8.7	N/A	20.1-23.2
Elev of Sample (masl)		C1			61.0-58.0	75.9-72.9	77.8-74.8	77.7-74.7	N/A	61.0-58.0
Parameter										
Benzene	μg/L	44	0.5	1	1	<0.5	<0.5	<0.5	<0.5	1
Ethylbenzene	μg/L	2300	0.5	< 0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Toluene	μg/L	18000	0.5	< 0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Xylene Mixture	μg/L	4200	0.5	< 0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5


150 Sample result exceeded Standard


Extraction and holding times were met for this sample.

NV-No Value

# **FIGURES**











1 Banigan Drive, Toronto, Ont., M4H1G3 www.groundedeng.ca

## LEGEND

PROPERTY BOUNDARY



GROUNDED BOREHOLE WITH



O/H OVERHEAD HYDRO





CATCH BASIN

SANITARY SEWER



CONVEYANCE LAND

Survey Drawing No. 3296-0T.DWG Project No. 3296-0 Certificate date: July 23, 2019. Prepared by

R. Avis Surveying Inc. Received on July 3, 2020 as part of the ROWE package prepared by IBI Group Architects

## PHASE TWO **ENVIRONMENTAL SITE ASSESSMENT**

23 ELIZABETH ST. N., 42, 44, 46 PARK ST. E., MISSISSAUGA ONTARIO, L5G 2Z4

## **BOREHOLE AND** MONITORING WELL **LOCATIONS**




JULY 2020

1:200

20-088

FIGURE 3





1 Banigan Drive, Toronto, Ont., M4H1G3 www.groundedeng.ca

## LEGEND

PROPERTY BOUNDARY



GROUNDED BOREHOLE WITH



O/H OVERHEAD HYDRO



CATCH BASIN







GROUNDWATER ELEVATION JUNE 18, 2020 80.3



GROUNDWATER FLOW DIRECTION

Note

## Reference

Survey Drawing No. 3296-0T.DWG Project No. 3296-0 Certificate date: July 23, 2019. Prepared by

R. Avis Surveying Inc. Received on July 3, 2020 as part of the ROWE package prepared by IBI Group Architects

### Project PHASE TWO **ENVIRONMENTAL SITE ASSESSMENT**

23 ELIZABETH ST. N., 42, 44, 46 PARK ST. E., MISSISSAUGA ONTARIO, L5G 2Z4

## **GROUNDWATER ELEVATION AND CONTOURS**



Date

JULY 2020

Scale


1:200

Job No

20-088

Figure No

FIGURE 4





1 Banigan Drive, Toronto, Ont., M4H1G3 www.groundedeng.ca

## LEGEND

PROPERTY BOUNDARY



GROUNDED BOREHOLE WITH

—— GAS — GAS

O/H OVERHEAD HYDRO



CATCH BASIN



SANITARY SEWER



CONVEYANCE LAND

### Reference

Survey Drawing No. 3296-0T.DWG Project No. 3296-0 Certificate date: July 23, 2019. Prepared by

R. Avis Surveying Inc. Received on July 3, 2020 as part of the ROWE package prepared by IBI Group Architects

## PHASE TWO **ENVIRONMENTAL SITE ASSESSMENT**

23 ELIZABETH ST. N., 42, 44, 46 PARK ST. E., MISSISSAUGA ONTARIO, L5G 2Z4

Figure Title

## **CROSS - SECTION** LOCATIONS



JULY 2020

Scale


1:200


Job No


20-088


Figure No

FIGURE 5









# **APPENDIX**



# **APPENDIX A**





File No. 20-088-201 May 8, 2020

## **Phase One Environmental Conceptual Site Model**

## 23 Elizabeth St. N., 42, 44 & 46 Park St. E., Mississauga, Ontario

Phase One ESA including Figures of the Phase One Study Area, which identify the following:	Phase One ESA Information:			
Existing buildings and structures	Four (4), 2-storey bricks and wood panels residential buildings were observed on the Property. The Phase One Property is presented in Figure 2.			
Water bodies located in whole or in part on the Phase One Study Area	No water bodies were observed on the Phase One Property and Phase One Study Area as shown on Figure 3.			
Areas of Natural Significance located in whole or in part on the Phase One Study Area	No Areas of Natural Significance were in whole or in part on the Phase One Study Area.			
Roads (including names) within the Phase One Study Area	All roads within the Phase One Study Area are shown on Figure 3.			
Use of properties adjacent to the Phase One Property	The land use of properties adjacent to the Phase One Property is shown on Figure 3.			
Location of drinking water wells on the Phase One Property	No drinking water wells were observed on the Phase One Property.			
Areas where any PCA has occurred, and locations of tanks in the Phase One Study Area	The location of PCAs is shown on Figure 4.			
APECs on the Phase One Property	No APECs were identified on the Phase One Property.			
Narrative Description and Assessments				
Any areas where Potentially Contaminating Activity (PCAs) on, or potentially affecting, the Phase One Property have occurred	No PCAs were observed on the Property. Based on the review of PCAs within the Study Area, no APECs were identified on the Property.			
Any Potential Contaminants of Concerns (PCoCs)	No PCoCs were identified on the Property.			
The potential of underground utilities (if any present) to affect contaminant distribution and transport	Buried watermain enters the Property via Elizabeth Street to the south and via Park Street East to the east; however, no PCoCs were identified on the Property thus underground utilities had no effect on contaminant distribution and transport.			



Available regional or site specific geological and hydrogeological information	<ul> <li>The approximate elevation of the Property is approximately 80 masl and is relatively flat with a slight slope to the southeast.</li> <li>The nearest water body - Mary Fix Creek, approximately 150 m to the west of the Property.</li> <li>Locally the ground water is expected to flow south towards Credit River and regionally the ground water is expected to flow southeast towards Lake Ontario.</li> <li>The overburden is consisting of half coarse-textured glaciolacustrine deposits comprise of sand, gravel, minor silt and clay and half modern alluvial deposits comprise of clay, silt, sand, gravel and organic remains.</li> <li>The bedrock at the Property is of the Georgian Bay Formation, which is comprised of shale, limestone, dolostone and siltstone.</li> <li>According to published well record database, the depth to bedrock in the vicinity of the Property is approximately 6 m.</li> </ul>
Any uncertainty or absence of information obtained in the Phase One ESA that could affect the validity of the CSM	No uncertainty or absence of information obtained in the Phase One ESA is identified to influence the validity of the CSM.


Figure 1 – Site Location Plan


Figure 2 - Phase One Property


Figure 3 – Phase One Study Area


Figure 4 - PCA Locations


Figure 5 – APEC Locations











## **APPENDIX B**





## Appendix B: Sampling and Analysis Plan

Areas of Potential Environmental Concern (APECs)	Location of APECs on Phase One Property	Potentially Contaminating Activities (PCAs)	Potential Contaminants of Concern (PCoCs)	Media Potentially Impacted (Groundwater, soil and/or sediment)	Borehole or Monitoring Well Associated	Exceedances
No APECs	No APECs	Offsite	PHCs BTEX	Soil & Groundwater		None
			Metals As, Sb, Se CN- Hg Cr(VI) Low or high pH	Soil & Groundwater	BH1, BH2, BH3 & BH4	
			EC SAR B-HWS	Soil		
			CI Na	Groundwater		

# **APPENDIX C**





## SAMPLING/TESTING METHODS

SS: split spoon sample

AS: auger sample

GS: grab sample

FV: shear vane

DP: direct push

PMT: pressuremeter test

ST: shelby tube

CORE: soil coring RUN: rock coring

## **SYMBOLS & ABBREVIATIONS**

MC: moisture content

LL: liquid limit

PL: plastic limit

PI: plasticity index

y: soil unit weight (bulk)

G<sub>s</sub>: specific gravity

S<sub>u</sub>: undrained shear strength

∪ unstabilized water level

▼ 1st water level measurement

2nd water level measurement most recent

water level measurement

## **ENVIRONMENTAL SAMPLES**

M&I: metals and inorganic parameters

PAH: polycyclic aromatic hydrocarbon

PCB: polychlorinated biphenyl VOC: volatile organic compound

PHC: petroleum hydrocarbon
BTEX: benzene, toluene, ethylbenzene and xylene

PPM: parts per million

## FIELD MOISTURE (based on tactile inspection)

DRY: no observable pore water

MOIST: inferred pore water, not observable (i.e. grey, cool, etc.)

WET: visible pore water

------

MOICT.	:	 	4	_	- /: -	

COMPOSITION	
Term	% by weight
trace silt	<10
some silt	10 - 20
silt <b>y</b>	20 - 35
sand <i>and</i> silt	>35

COHESIONLESS				
Relative Density	N-Value			
Very Loose	<4			
Loose	4 - 10			
Compact	10 - 30			
Dense	30 - 50			

>50

Very Dense

COHESIVE		
Consistency	N-Value	Su (kPa)
Very Soft	<2	<12
Soft	2 - 4	12 - 25
Firm	4 - 8	25 - 50
Stiff	8 - 15	50 - 100
Very Stiff	15 - 30	100 - 200
Hard	>30	>200
Very Soft Soft Firm Stiff Very Stiff	<2 2 - 4 4 - 8 8 - 15 15 - 30	<12 12 - 25 25 - 50 50 - 100 100 - 200

## **ASTM STANDARDS**

## **ASTM D1586 Standard Penetration Test (SPT)**

Driving a 51 mm O.D. split-barrel sampler ("split spoon") into soil with a 63.5 kg weight free falling 760 mm. The blows required to drive the split spoon 300 mm ("bpf") after an initial penetration of 150 mm is referred to as the N-Value.

## ASTM D3441 Cone Penetration Test (CPT)

Pushing an internal still rod with a outer hollow rod ("sleeve") tipped with a cone with an apex angle of 60° and a cross-sectional area of 1000 mm² into soil. The resistance is measured in the sleeve and at the tip to determine the skin friction and the tip resistance.

## ASTM D2573 Field Vane Test (FVT)

Pushing a four blade vane into soil and rotating it from the surface to determine the torque required to shear a cylindrical surface with the vane. The torque is converted to the shear strength of the soil using a limit equilibrium analysis.


## **ASTM D1587 Shelby Tubes (ST)**

Pushing a thin-walled metal tube into the in-situ soil at the bottom of a borehole, removing the tube and sealing the ends to prevent soil movement or changes in moisture content for the purposes of extracting a relatively undisturbed sample.

## ASTM D4719 Pressuremeter Test (PMT)

Place an inflatable cylindrical probe into a pre-drilled hole and expanding it while measuring the change in volume and pressure in the probe. It is inflated under either equal pressure increments or equal volume increments. This provides the stress-strain response of the soil.

## **WELL LEGEND**



## **ROCK CORE TERMINOLOGY (MTO SHALE)**



TCR Total Core Recovery the total length of recovery (soil or rock) per run, as a percentage of the drilled length

SCR Solid Core Recovery the total length of sound full-diameter rock core pieces per run, as a percentage of the drilled length

**RQD** Rock Quality Designation the sum of all pieces of sound rock core in a run which are 10 cm or greater in length, as a percentage of the drilled length

Natural Fracture Frequency (typically per 0.3 m) The number of natural discontinuities (joints, faults, etc.) which are present per 0.3m. Ignores mechanical or drill-induced breaks, and closed discontinuities (e.g. bedding planes).

## LOGGING DISCONTINUITIES

## **Discontinuity Type**

BP bedding parting

**CL** cleavage

**CS** crushed seam **F7** fracture zone

FZ fracture zoneMB mechanical break

IS infilled seam

JT Joint

SS shear surface

**SZ** shear zone

VN vein

VO void

## Coating

CN CleanSN Stained


OX Oxidized VN Veneer

CT Coating (>1 mm)

## **Dip Inclination**

 $\begin{array}{lll} \textbf{H} & \text{horizontal/flat} & 0 - 20^{\circ} \\ \textbf{D} & \text{dipping} & 20 - 50^{\circ} \\ \textbf{SV} & \text{sub-vertical} & 50 - 90^{\circ} \\ \textbf{V} & \text{vertical} & 90\pm^{\circ} \\ \end{array}$ 

### Roughness (Barton et al.)



## **Spacing in Discontinuity Sets**

(ISRM 1981)

 VC
 very close
 < 60 mm</td>

 C
 close
 60 - 200 mm

 M
 mod. close
 0.2 to 0.6 m

 W
 wide
 0.6 to 2 m

 VW
 very wide
 > 2 m

## **Aperture Size**

 T
 closed / tight
 < 0.5 mm</td>

 GA
 gapped
 0.5 to 10 mm

 OP
 open
 > 10 mm

Bedding Thickness (Q. J. Eng. Geology,

Vol 3, 1970)

## **Planarity**

PR Planar
UN Undulating
ST Stepped
IR Irregular
DIS Discontinuous
CU Curved

## **GENERAL**

Degree of Weathering (after MTO, RR229 Evaluation of Shales for Construction Projects)

Zone	Degree	Description
Z1	unweathered	shale, regular jointing
Z2		angular blocks of unweathered shale, no matrix, with chemically weathered but intact shale
Z3	partially weathered	soil-like matrix with frequent angular shale fragments < 25mm diameter
Z4a		soil-like matrix with occasional shale fragments < 3mm diameter
Z4b	fully weathered	soil-like matrix only

## Strength classification (after Marinos and Hoek, 2001; ISRM 1981b)

Grade		(MPa)	Field Estimate (Description)	10.0,1770)	
R6	extremely strong	> 250	can only be chipped by geological hammer	Very thickly bedded	> 2 m
R5	very strong	100 - 250	requires many blows from geological hammer	Thickly bedded	0.6 – 2m
R4	strong	50 - 100	requires more than one blow from geological hammer	Medium bedded	200 – 600mm
R3	medium strong	25 - 50	can't be scraped, breaks under one blow from geological hammer	Thinly bedded  Very thinly bedded	60 – 200mm 20 – 60mm
R2	weak	5 - 25	can be peeled / scraped with knife with difficulty	Laminated	6 – 20mm
R1	very weak	1 - 5	easily scraped / peeled, crumbles under firm blow of geo. hammer	Thinly Laminated	< 6mm
R0	extremely weak	< 1	indented by thumbnail		



Date Started: Jun 2, 2020

Position: E: 614179, N: 4823383 (UTM 17T)

Elev. Datum : Geodetic

## **BOREHOLE LOG 1**

File No.: 20-088 Project: 23 Elizabeth Street North, Mississauga **Client:** Edenshaw Elizabeth Developments Limited stratigraphy samples undrained shear strength (kPa)
O unconfined + field vane headspace vapour (ppm)  $\widehat{\Xi}$ □ isobutylene Ξ details scale 80 120 100 200 300 comments SPT N-value elevation SPT N-values (bpf) moisture / plasticity description depth grain size distribution (%) (MIT) number type **GROUND SURFACE** GR SA SI CI 25mm ASPHALTIC CONCRETE -81 150mm AGGREGATE 1 SS 15 C FILL, silty sand, trace gravel, trace asphalt, compact, brown, moist SILT and SAND, trace gravel, loose to compact, orangey brown and grey, moist 7 0 SS2: M&I, BTEX, PHC ...at 1.5 m, moist to wet s wolloh 3 0 SS3: M&I 2 -...at 2.3 m, grey 4 SS 16 0 0 57 43 0 3 -SILTY CLAY, trace sand, trace gravel, very - 78 soft, grey, wet (GLACIAL TILL) 5 SS 0 SS5: BTEX, PHC SILTY SAND, some clay, some gravel, hard, grey, moist to wet (GLACIAL TILL) 6 35 0 17 36 32 15 5 -6 -7 34 SS 7.3m: Grinding 0 50 / INFERRED BEDROCK, shale and limestone 75mm fragments, grey 8 -9 -SS / 50 / 75mm 0 **GEORGIAN BAY FORMATION** 10.4m: Transition to sound bedrock (See rock core log for details) RUN RUN 2 12 -- 69 RUN 3 RUN 4 **Page** 1 of 2 Tech: JN | PM: JW | Rev: MD




Date Started: Jun 2, 2020

Position: E: 614179, N: 4823383 (UTM 17T)

Elev. Datum : Geodetic

## **BOREHOLE LOG 1**

Project: 23 Elizabeth Street North, Mississauga **Client:** Edenshaw Elizabeth Developments Limited



### **END OF BOREHOLE**

Filled with drill water upon completion of drilling.

50 mm dia. monitoring well installed.

## GROUNDWATER LEVELS ""-1--- Ponth (m) Elevation (m)

vate	water Depth (m)	Elevation (n
Jun 5, 2020	4.8	76.4
Jun 10, 2020	7.7	73.5
Jun 12, 2020	12.7	68.5
Jun 18, 2020	12.7	68.5
Jul 20, 2020	12.6	68.6



**Page** 1 of 2

(continued next page)

Date Started: Jun 2, 2020

Position: E: 614179, N: 4823383 (UTM 17T)

Elev. Datum: Geodetic

## **ROCK CORE LOG 1**

Tech: JN | PM: JW | Rev: MD

File No.: 20-088 Project: 23 Elizabeth Street North, Mississauga **Client:** Edenshaw Elizabeth Developments Limited Run UCS (MPa) natural fracture frequency shale weathering elevation (m) laboratory elev depth (m) graphic log notes and comments 25 50 100 250 depth (m) testing stratigraphy recovery zones estimated strength Rock coring started at 10.2m below grade 71 GEORGIAN BAY FORMATION Shale, grey, thinly bedded, weak; joints are horizontal, gapped to open; 10.4 / 70.8m: Transition to sound bedrock TCR = **58**% SCR = **42**% RQD = **11**% 10.7 / 70.5m: 15" lost core at the end of the interbedded with limestone, light grey, thinly bedded, medium strong Overall shale: 90%, limestone: 10% 70 70 12% limestone 88% shale 1 TCR = 95% SCR = 90% RQD = 80% 1 0 69 69 6% limestone 94% shale 2 1 68 TCR = 100% SCR = 92% RQD = 92% R3 1 1 5% limestone n 95% shale 67 1 0 TCR = 100% SCR = 95% R4 1 RQD = **92**% 66 1 7% limestone Run 4: 65.7 15.5 0 0 TCR = 100% SCR = 100% RQD = 100% 65 0 R5 1 Run 5: 11% limestone 0 89% shale 64 1 3 TCR = 100% SCR = 98% RQD = 93% 0 R6 0 63 63 0 19% limestone 81% shale n 0 62 TCR = 100% SCR = 100% RQD = 100% R7 0 0 10% limestone Run 7: 90% shale



Date Started: Jun 2, 2020


Position: E: 614179, N: 4823383 (UTM 17T)

Elev. Datum: Geodetic

23.2m

**ROCK CORE LOG 1** 

Project: 23 Elizabeth Street North, Mississauga **Client**: Edenshaw Elizabeth Developments Limited



**END OF COREHOLE** 



File No.: 20-088


Date Started: Jun 2, 2020

Position: E: 614147, N: 4823384 (UTM 17T)

Elev. Datum : Geodetic

## **BOREHOLE LOG 2**

Project: 23 Elizabeth Street North, Mississauga **Client:** Edenshaw Elizabeth Developments Limited



Auger refusal

Dry and open upon completion of drilling.

50 mm dia. monitoring well installed.

No. 10 screen

GR	OUNDWATER LEVE	_S
<u>Date</u>	Water Depth (m)	Elevation (m)
Jun 5, 2020	5.0	76.5
Jun 10, 2020	5.0	76.5
Jun 12, 2020	4.9	76.5
Jun 18, 2020	4.9	76.5
Jul 20, 2020	4.7	76.7




Date Started: May 25, 2020

Position: E: 614142, N: 4823408 (UTM 17T)

Elev. Datum: Geodetic

**BOREHOLE LOG 3** 

File No.: 20-088 Project: 23 Elizabeth Street North, Mississauga **Client:** Edenshaw Elizabeth Developments Limited stratigraphy samples undrained shear strength (kPa)
O unconfined + field vane headspace vapour (ppm) Œ pocket penetrometer Lab Vane ☐ isobutylene Ξ 80 120 160 100 200 300 comments






Date Started: May 25, 2020

Position: E: 614160, N: 4823412 (UTM 17T)

Elev. Datum: Geodetic

## **BOREHOLE LOG 4**

Project: 23 Elizabeth Street North, Mississauga **Client:** Edenshaw Elizabeth Developments Limited



Auger refusal

Unstabilized water level measured at 4.6 m below ground surface; caved to 8.7 m below ground surface upon completion of drilling.


50 mm dia. monitoring well installed. No. 10 screen

GROL	IND/	NATE	RIF	VFI S

<u>Date</u>	Water Depth (m)	Elevation (n
Jun 5, 2020	2.9	80.5
Jun 10, 2020	2.9	80.4
Jun 12, 2020	3.0	80.4
Jun 18, 2020	3.0	80.3
Jul 20, 2020	3.5	79.9

# **APPENDIX D**





#### MIT SYSTEM

	Borehole	Sample	Depth (m)	Elev. (m)	Gravel (%)	Sand (%)	Silt (%)	Clay (%)	
•	1	SS6	4.9	76.3	17	36	32	15	
	2	SS7	6.4	75.0	12	30	37	21	
<b>A</b>	4	SS8	7.8	75.5	15	36	33	16	




Title:

GRAIN SIZE DISTRIBUTION
SILT TILL

File No.:

20-088



M	יא ד	VQT	FM	1

	Borehole	Sample	Depth (m)	Elev. (m)	Gravel (%)	Sand (%)	Silt (%)	Clay (%)	
•	1	SS4	2.6	78.6	0	57	43	0	
	2	SS5	3.4	78.0	1	10	76	13	
<b>A</b>	3	SS5	3.2	80.2	0	57	43	0	
*	4	SS5	3.3	80.1	0	63	36	1	




Title:

GRAIN SIZE DISTRIBUTION SILT AND SAND

File No.:

20-088



	Borehole	Sample	Depth (m)	Elev. (m)	LL (%)	PL (%)	PI (%)	
•	1	SS6	4.9	76.3	26	14	12	
×	4	SS8	7.8	75.5	30	19	11	



Title:

ATTERBERG LIMITS CHART

File No.:

20-088

# **APPENDIX E**









CA14778-JUN20 R

20-088 23 Elizabeth St N Mississauga

Prepared for

**Grounded Engineering Inc.** 



#### First Page

CLIENT DETAILS	S	LABORATORY DETAIL	LS
Client	Grounded Engineering Inc.	Project Specialist	Brad Moore Hon. B.Sc
		Laboratory	SGS Canada Inc.
Address	12 Banigan Drive	Address	185 Concession St., Lakefield ON, K0L 2H0
	Toronto, Ontario		
	M4H1E9. Canada		
Contact	Jessie Wu	Telephone	705-652-2143
Telephone	647-264-7909	Facsimile	705-652-6365
Facsimile		Email	brad.moore@sgs.com
Email	jwu@groundedeng.ca	SGS Reference	CA14778-JUN20
Project	20-088 23 Elizabeth St N Mississauga	Received	06/03/2020
Order Number		Approved	06/09/2020
Samples	Soil (3)	Report Number	CA14778-JUN20 R
		Date Reported	06/09/2020

#### COMMENTS

CCME Method Compliance: Analyses were conducted using analytical procedures that comply with the Reference Method for the CWS for Petroleum Hydrocarbons in Soil and have been validated for use at the SGS laboratory, Lakefield, ON site.

Quality Compliance: Instrument performance / calibration quality criteria were met and extraction and analysis limits for holding times were met.

nC6 and nC10 response factors within 30% of response factor for toluene: YES

nC10, nC16 and nC34 response factors within 10% of the average response for the three compounds: YES

C50 response factors within 70% of nC10 + nC16 + nC34 average: YES

Linearity is within 15%: YES

F4G - gravimetric heavy hydrocarbons cannot be added to the C6 to C50 hydrocarbons.

The results for F4 and F4G are both reported and the greater of the two values is to be used in application to the CWS PHC.

Hydrocarbon results are expressed on a dry weight basis.

Temperature of Sample upon Receipt: 7 degrees C

Cooling Agent Present:Yes Custody Seal Present:Yes

Chain of Custody Number:012656

SIGNATORIES

Brad Moore Hon. B.Sc Brad Mo

1/17

SGS Canada Inc. 185 Concession St., Lakefield ON, K0L 2H0 t 705-652-2143 f 705-652-6365

www.sgs.com

Member of the SGS Group (SGS SA)



### **TABLE OF CONTENTS**

First Page	1
Index	2
Results	
Exceedance Summary	
Holding Time Summary	8-9
QC Summary	
Legend	16
Δηγονος	17



CKAGE: <b>REG153 - BTEX</b> (SO	OIL)		Sample Number	8	10	
			Sample Name	BH1-SS2	BH1-SS5	
REG153 / SOIL / COARSE - TABLE 3 - Reside	ential/Parkland - UNDEFINED		Sample Matrix	Soil	Soil	
			Sample Date	02/06/2020	02/06/2020	
Parameter	Units	RL	L1	Result	Result	
EX						
Benzene	μg/g	0.02	0.21	< 0.02	< 0.02	
Ethylbenzene	μg/g	0.05	2	< 0.05	< 0.05	
Toluene	μg/g	0.05	2.3	< 0.05	< 0.05	
Xylene (total)	μg/g	0.05	3.1	< 0.05	< 0.05	
m/p-xylene	μg/g	0.05		< 0.05	< 0.05	
o-xylene	μg/g	0.05		< 0.05	< 0.05	
o-xylene	μg/g	0.05				
o-xylene CKAGE: <b>REG153 - Hydrides</b> (		0.05	Sample Number	< 0.05	< 0.05 9	
·		0.05	Sample Number Sample Name			
·	SOIL)	0.05	·	8	9	
.CKAGE: <b>REG153 - Hydrides</b> (	SOIL)	0.05	Sample Name	8 BH1-SS2	9 BH1-SS3	
.CKAGE: <b>REG153 - Hydrides</b> (	SOIL)	0.05	Sample Name Sample Matrix	8 BH1-SS2 Soil	9 BH1-SS3 Soil	
CKAGE: <b>REG153 - Hydrides</b> (	SOIL) ential/Parkland - UNDEFINED		Sample Name Sample Matrix Sample Date	8 BH1-SS2 Soil 02/06/2020	9 BH1-SS3 Soil 02/06/2020	
CKAGE: REG153 - Hydrides ( REG153 / SOIL / COARSE - TABLE 3 - Reside	SOIL) ential/Parkland - UNDEFINED		Sample Name Sample Matrix Sample Date	8 BH1-SS2 Soil 02/06/2020	9 BH1-SS3 Soil 02/06/2020	
CKAGE: REG153 - Hydrides ( REG153 / SOIL / COARSE - TABLE 3 - Reside  Parameter  drides	SOIL) ential/Parkland - UNDEFINED Units	RL	Sample Name Sample Matrix Sample Date	8 BH1-SS2 Soil 02/06/2020 <b>Result</b>	9 BH1-SS3 Soil 02/06/2020 <b>Result</b>	



CKAGE: <b>REG153 - Metals and</b>	Inorganics (SOIL)		Sample Number	8	9	10	
			Sample Name	BH1-SS2	BH1-SS3	BH1-SS5	
REG153 / SOIL / COARSE - TABLE 3 - Resident	tial/Parkland - UNDEFINED		Sample Matrix	Soil	Soil	Soil	
			Sample Date	02/06/2020	02/06/2020	02/06/2020	
Parameter	Units	RL	L1	Result	Result	Result	
tals and Inorganics							
Moisture Content	%	-		15.6	15.6	21.6	
Barium	μg/g	0.1	390	43	35		
Beryllium	μg/g	0.02	4	0.33	0.27		
Boron	μg/g	1	120	3	2		
Cadmium	μg/g	0.02	1.2	0.07	0.05		
Chromium	μg/g	0.5	160	13	12		
Cobalt	μg/g	0.01	22	7.7	5.9		
Copper	μg/g	0.1	140	18	15		
Lead	μg/g	0.1	120	6.2	4.8		
Molybdenum	μg/g	0.1	6.9	0.2	0.3		
Nickel	μg/g	0.5	100	16	12		
Silver	μg/g	0.05	20	< 0.05	< 0.05		
Thallium	μg/g	0.02	1	0.09	0.08		
Uranium	μg/g	0.002	23	0.38	0.35		
Vanadium	μg/g	3	86	22	19		
Zinc	μg/g	0.7	340	35	26		
Water Soluble Boron	μg/g	0.5	1.5	< 0.5	< 0.5		



ACKAGE: <b>REG153 - Other (ORP)</b> (SC	OIL)		Sample Nui	mber	8	9
			Sample N	lame	BH1-SS2	BH1-SS3
REG153 / SOIL / COARSE - TABLE 3 - Residential/Park	land - UNDEFINED		Sample M	latrix	Soil	Soil
			Sample	Date	02/06/2020	02/06/2020
Parameter	Units	RL	L1		Result	Result
her (ORP)						
Mercury	μg/g	0.05	0.27		< 0.05	< 0.05
Sodium Adsorption Ratio		0.2	5		3.2	3.5
SAR Calcium	mg/L	0.09			19.8	23.4
SAR Magnesium	mg/L	0.02			2.6	3.3
SAR Sodium	mg/L	0.15			48.5	66.2
Conductivity	mS/cm	0.002	0.7		0.46	0.51
рН	pH Units	0.05			7.84	7.79
Chromium VI	μg/g	0.2	8		< 0.2	< 0.2
Free Cyanide	μg/g	0.05	0.051		< 0.05	< 0.05



ACKAGE: <b>REG153 - PHCs</b> (SOIL)			Sample Number	8	10
			Sample Name	BH1-SS2	BH1-SS5
= REG153 / SOIL / COARSE - TABLE 3 - Residential/Parkland -	UNDEFINED		Sample Matrix	Soil	Soil
			Sample Date	02/06/2020	02/06/2020
Parameter	Units	RL	L1	Result	Result
HCs					
F1 (C6-C10)	μg/g	10	55	< 10	< 10
F1-BTEX (C6-C10)	μg/g	10		< 10	< 10
F2 (C10-C16)	μg/g	10	98	< 10	< 10
F3 (C16-C34)	μg/g	50	300	< 50	< 50
F4 (C34-C50)	μg/g	50	2800	< 50	< 50
Chromatogram returned to baseline at nC50	Yes / No	_		YES	YES

# SGS FINAL REPORT

#### **EXCEEDANCE SUMMARY**

No exceedances are present above the regulatory limit(s) indicated

20200609 7 / 17





Conductivity								
Aethod: EDA 6010/SM 2510   Inter								
hetriod. El A 00 10/01vi 2010   linten	nal ref.: ME-CA-[ENV]	EWL-LAK-	-AN-006					
BH1-SS2	EWL0099-JUN20	8	06/02/2020	06/03/2020	06/04/2020	06/05/2020	06/30/2020	06/08/2020
BH1-SS3	EWL0099-JUN20	9	06/02/2020	06/03/2020	06/04/2020	06/05/2020	06/30/2020	06/08/2020
Cyanide by SFA								
Method: SM 4500   Internal ref.: ME	-CA-[ENV]SFA-LAK-A	N-005						
BH1-SS2	SKA5025-JUN20	8	06/02/2020	06/03/2020	06/04/2020	06/05/2020	06/16/2020	06/05/202
BH1-SS3	SKA5025-JUN20	9	06/02/2020	06/03/2020	06/04/2020	06/05/2020	06/16/2020	06/05/202
Hexavalent Chromium by SFA								
Method: EPA218.6/EPA3060A   Inte	ernal ref.: ME-CA-IEN\	∕ISKA-LAI	K-AN-012					
BH1-SS2	SKA5021-JUN20	8	06/02/2020	06/03/2020	06/05/2020	06/05/2020	07/02/2020	06/05/202
BH1-SS3	SKA5021-JUN20	9	06/02/2020	06/03/2020	06/05/2020	06/05/2020	07/02/2020	06/05/202
							*****	
Mercury by CVAAS								
Method: EPA 7471A/EPA 245   Inte	rnal ref.: ME-CA-[ENV	]SPE-LAK	-AN-004					
BH1-SS2	EMS0022-JUN20	8	06/02/2020	06/03/2020	06/04/2020	06/04/2020	06/30/2020	06/04/202
BH1-SS3	EMS0022-JUN20	9	06/02/2020	06/03/2020	06/04/2020	06/04/2020	06/30/2020	06/04/202
Metals in aqueous samples - ICP-OI	ES							
Method: MOE 4696e01/EPA 6010	Internal ref.: ME-CA-[	ENV]SPE-	LAK-AN-003					
BH1-SS2	ESG0016-JUN20	8	06/02/2020	06/03/2020	06/04/2020	06/04/2020	11/29/2020	06/04/202
BH1-SS3	ESG0016-JUN20	9	06/02/2020	06/03/2020	06/04/2020	06/04/2020	11/29/2020	06/04/202
Metals in Soil - Aqua-regia/ICP-MS								
Method: EPA 3050/EPA 200.8   Inte	ernal ref.: ME-CA-[EN\	/]SPE-LAŀ	<b>K-AN-005</b>					
BH1-SS2	EMS0022-JUN20	8	06/02/2020	06/03/2020	06/04/2020	06/04/2020	11/29/2020	06/04/202
BH1-SS3	EMS0022-JUN20	9	06/02/2020	06/03/2020	06/04/2020	06/04/2020	11/29/2020	06/04/202
Moisture								
Method: CCME Tier 1   Internal ref.:	: ME-CA-IENVIGC-LAI	K-AN-010						
BH1-SS2	GCM0087-JUN20	8	06/02/2020	06/03/2020	06/04/2020	06/04/2020	08/01/2020	06/05/202
BH1-SS3	GCM0087-JUN20	9	06/02/2020	06/03/2020	06/04/2020	06/04/2020	08/01/2020	06/05/202
BH1-SS5	GCM0087-JUN20	10	06/02/2020	06/03/2020	06/04/2020	06/04/2020	08/01/2020	06/05/202
····	253007 001420		00.02.2020	33,33,2020		33,3 .,2020	33,3.72020	33,00,202
National Professional Control								
Petroleum Hydrocarbons (F1)	.ME OA FENDESON :	Z ANI 040						
Petroleum Hydrocarbons (F1) Method: CCME Tier 1   Internal ref.:	ME-CA-[ENV]GC-LA	K-AN-010						

06/02/2020

06/03/2020

06/04/2020

06/04/2020

07/12/2020

06/05/2020

20200609 8 / 17

GCM0073-JUN20

Method: CCME Tier 1 | Internal ref.: ME-CA-[ENV]GC-LAK-AN-010

Petroleum Hydrocarbons (F2-F4)

BH1-SS2



#### HOLDING TIME SUMMARY

Sample Name	QC Batch Reference	Sample Number	Sampled	Received	Extracted/ Prepared	Analysed	Holding Time	Approved
Petroleum Hydrocarbons (F2-F4) (cc	ontinued)							
Method: CCME Tier 1   Internal ref.:	ME-CA-[ENV]GC-LA	<b>&lt;-AN-</b> 010						
BH1-SS5	GCM0073-JUN20	10	06/02/2020	06/03/2020	06/04/2020	06/04/2020	07/12/2020	06/05/2020
рН								
Method: SM 4500   Internal ref.: ME	-CA-[ENV]EWL-LAK-/	N-001						
BH1-SS2	ARD0024-JUN20	8	06/02/2020	06/03/2020	06/04/2020	06/04/2020	07/02/2020	06/04/2020
BH1-SS3	ARD0024-JUN20	9	06/02/2020	06/03/2020	06/04/2020	06/04/2020	07/02/2020	06/04/202
Method: MOE 4696e01/EPA 6010   BH1-SS2	ESG0016-JUN20	8	06/02/2020	06/03/2020	06/04/2020	06/04/2020	11/29/2020	06/04/202
BH1-SS3	ESG0016-JUN20	9	06/02/2020	06/03/2020	06/04/2020	06/04/2020	11/29/2020	06/04/2020
Volatile Organics Method: EPA 5035A/5030B/8260C	Internal ref.: ME-CA-	[ENV]GC-	LAK-AN-004					
Method: EPA 5035A/5030B/8260C	Internal ref.: ME-CA-	[ENV]GC-	LAK-AN-004 06/02/2020	06/03/2020	06/05/2020	06/05/2020	06/16/2020	06/09/2020
Method: EPA 5035A/5030B/8260C   BH1-SS2		• •		06/03/2020 06/03/2020	06/05/2020 06/05/2020	06/05/2020 06/05/2020	06/16/2020 06/16/2020	06/09/2020
Method: EPA 5035A/5030B/8260C   BH1-SS2 BH1-SS5	GCM0109-JUN20	8	06/02/2020					
Method: EPA 5035A/5030B/8260C   BH1-SS2 BH1-SS5 Water Soluble Boron	GCM0109-JUN20 GCM0109-JUN20	8 10	06/02/2020 06/02/2020					
	GCM0109-JUN20 GCM0109-JUN20	8 10	06/02/2020 06/02/2020					

20200609 9 / 17



#### QC SUMMARY

## Conductivity

Method: EPA 6010/SM 2510 | Internal ref.: ME-CA-[ENV]EWL-LAK-AN-006

Parameter	QC batch U	Units RL	Method	Dup	licate	LCS/Spike B		
	Reference			Blank	RPD	AC	Spike	F
						(%)	Recovery (%)	Lo
Conductivity	EWL0099-JUN20	mS/cm	0.002	<0.002	0	10	99	90

## Cyanide by SFA

Method: SM 4500 | Internal ref.: ME-CA-IENVISFA-LAK-AN-005

Parameter	QC batch	Units	RL	Method	Duj	plicate	LCS/Spik	
	Reference			Blank	RPD	AC (%)	Spike Recovery (%)	Lov
Free Cyanide	SKA5025-JUN20	μg/g	0.05	<0.05	ND	20	105	80

## **Hexavalent Chromium by SFA**

Method: EPA218.6/EPA3060A | Internal ref.: ME-CA-IENVISKA-LAK-AN-012

Parameter	QC batch	Units RL	RL		Duplicate		LCS/Spike I	
	Reference			Blank	RPD	AC (%)	Spike Recovery (%)	Lov
Chromium VI	SKA5021-JUN20	ug/g	0.2	<0.2	ND	20	89	80



#### QC SUMMARY

Mercury by CVAAS

Method: EPA 7471A/EPA 245 | Internal ref.: ME-CA-IENVISPE-LAK-AN-004

Parameter	QC batch	Units	RL	Method	Duplicate		LCS/Spike E	
	Reference			Blank	RPD	AC (%)	Spike	F
						(%)	Recovery (%)	Lo
Mercury	EMS0022-JUN20	μg/g	0.05	<0.05	5	20	101	80

## Metals in aqueous samples - ICP-OES

Method: MOE 4696e01/EPA 6010 | Internal ref.: ME-CA-IENVISPE-LAK-AN-003

Parameter	QC batch	Units	RL	Method	Dup	olicate	LCS/Spike E		
	Reference			Blank	RPD	AC	Spike	F	
						(%)	Recovery (%)	Lo	
SAR Calcium	ESG0016-JUN20	mg/L	0.09	<0.09	6	20	98	80	
SAR Magnesium	ESG0016-JUN20	mg/L	0.02	<0.02	9	20	98	80	
SAR Sodium	ESG0016-JUN20	mg/L	0.15	<0.15	5	20	97	80	



#### **QC SUMMARY**

Metals in Soil - Aqua-regia/ICP-MS

Method: EPA 3050/EPA 200.8 | Internal ref.: ME-CA-IENVISPE-LAK-AN-005

Parameter	QC batch	Units	RL	Method	Dup	licate	LCS/Spike E	
	Reference			Blank	RPD	AC (%)	Spike Recovery (%)	Lo
Silver	EMS0022-JUN20	ug/g	0.05	<0.05	ND	20	94	7
Arsenic	EMS0022-JUN20	μg/g	0.5	<0.5	8	20	102	7
Barium	EMS0022-JUN20	ug/g	0.1	<0.1	4	20	107	7
Beryllium	EMS0022-JUN20	μg/g	0.02	<0.02	5	20	98	7
Boron	EMS0022-JUN20	μg/g	1	<1	9	20	102	7
Cadmium	EMS0022-JUN20	μg/g	0.02	<0.02	11	20	100	7
Cobalt	EMS0022-JUN20	μg/g	0.01	<0.01	6	20	100	7
Chromium	EMS0022-JUN20	μg/g	0.5	<0.5	3	20	102	7
Copper	EMS0022-JUN20	μg/g	0.1	<0.1	7	20	101	7
Molybdenum	EMS0022-JUN20	μg/g	0.1	<0.1	1	20	95	7
Nickel	EMS0022-JUN20	ug/g	0.5	<0.5	6	20	101	7
Lead	EMS0022-JUN20	μg/g	0.1	<0.1	1	20	102	7
Antimony	EMS0022-JUN20	μg/g	0.8	<0.8	ND	20	92	7
Selenium	EMS0022-JUN20	μg/g	0.7	<0.7	ND	20	103	7
Thallium	EMS0022-JUN20	μg/g	0.02	<0.02	3	20	105	7
Uranium	EMS0022-JUN20	μg/g	0.002	<0.002	5	20	100	7
Vanadium	EMS0022-JUN20	μg/g	3	<3	5	20	101	7
Zinc	EMS0022-JUN20	μg/g	0.7	<0.7	6	20	101	7



#### QC SUMMARY

Petroleum Hydrocarbons (F1)

Method: CCME Tier 1 | Internal ref.: ME-CA-IENVIGC-LAK-AN-010

Parameter	QC batch	Units	RL	Method	Duplicate		LCS/Spike E	
	Reference			Blank	RPD	AC	Spike Recovery	F
						(%)	(%)	Lo
F1 (C6-C10)	GCM0109-JUN20	μg/g	10	<10	ND	30	107	80

## Petroleum Hydrocarbons (F2-F4)

Method: CCME Tier 1 | Internal ref.: ME-CA-IENVIGC-LAK-AN-010

		••						
Parameter	QC batch	Units	RL	Method	Dup	olicate	LCS/Spike E	
	Reference			Blank	RPD	AC	Spike Recovery	F
						(%)	(%)	Lo
F2 (C10-C16)	GCM0073-JUN20	μg/g	10	<10	ND	30	109	80
F3 (C16-C34)	GCM0073-JUN20	μg/g	50	<50	ND	30	109	80
F4 (C34-C50)	GCM0073-JUN20	μg/g	50	<50	ND	30	109	80



#### QC SUMMARY

pН

Method: SM 4500 | Internal ref.: ME-CA-[ENVIEWL-LAK-AN-001

Parameter	QC batch	Units	RL	Method	Dup	olicate	LC	S/Spike E
	Reference			Blank	RPD	AC	Spike Recovery	F
						(%)	(%)	Lo
рН	ARD0024-JUN20	pH Units	0.05		0	20	100	80

## **Volatile Organics**

Method: EPA 5035A/5030B/8260C | Internal ref.: ME-CA-IENVIGC-LAK-AN-004

Parameter	QC batch	Units	RL	Method	Dup	olicate	LC	S/Spike E
	Reference			Blank	RPD	AC (%)	Spike Recovery (%)	Lov
Benzene	GCM0109-JUN20	μg/g	0.02	<0.02	ND	50	97	60
Ethylbenzene	GCM0109-JUN20	μg/g	0.05	<0.05	ND	50	96	60
m/p-xylene	GCM0109-JUN20	μg/g	0.05	<0.05	ND	50	100	60
o-xylene	GCM0109-JUN20	μg/g	0.05	<0.05	ND	50	96	60
Toluene	GCM0109-JUN20	μg/g	0.05	<0.05	ND	50	95	60



#### **QC SUMMARY**

#### **Water Soluble Boron**

Method: O.Reg. 153/04 | Internal ref.: ME-CA-[ENV] SPE-LAK-AN-003

Parameter	QC batch	Units	RL	Method	Dup	olicate	LC	CS/Spike E
	Reference			Blank	RPD	AC	Spike	F
						(%)	Recovery (%)	Lo
Water Soluble Boron	ESG0014-JUN20	μg/g	0.5	<0.5	ND	20	102	80

Method Blank: a blank matrix that is carried through the entire analytical procedure. Used to assess laboratory contamination.

Duplicate: Paired analysis of a separate portion of the same sample that is carried through the entire analytical procedure. Used to evaluate measurement precision.

LCS/Spike Blank: Laboratory control sample or spike blank refer to a blank matrix to which a known amount of analyte has been added. Used to evaluate analyte recovery and laboratory accuracy Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate laboratory accuracy with sample matrix effects.

Reference Material: a material or substance matrix matched to the samples that contains a known amount of the analyte of interest. A reference material may be used in place of a matrix spike.

RL: Reporting limit

RPD: Relative percent difference

AC: Acceptance criteria

**Multielement Scan Qualifier**: as the number of analytes in a scan increases, so does the chance of a limit exceedance by random chance as opposed to a real method problem. Thus, in multielem analytes may exceed the quoted limits by up to 10% absolute and the spike is considered acceptable.

**Duplicate Qualifier**: for duplicates as the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the **Matrix Spike Qualifier**: for matrix spikes, as the concentration of the native analyte increases, the uncertainty of the matrix spike recovery increases. Thus, the matrix spike acceptance limits apply equal to the concentration of the native analyte.



#### **LEGEND**

#### **FOOTNOTES**

NSS Insufficient sample for analysis.

RL Reporting Limit.

- † Reporting limit raised.
- ↓ Reporting limit lowered.
- NA The sample was not analysed for this analyte
- ND Non Detect

Samples analysed as received. Solid samples expressed on a dry weight basis. "Temperature Upon Receipt" is representative of the whole shipment and may not reflect the temperature of individual samples.

Analysis conducted on samples submitted pursuant to or as part of Reg. 153/04, are in accordance to the Protocol for Analytical Methods Used in the Assessment of Properties under Part XV.1 of the Environmental Protection Act" published by the Ministry and dated March 9, 2004 as amended.

SGS provides criteria information (such as regulatory or guideline limits and summary of limit exceedances) as a service. Every attempt is made to ensure the criteria information in this report is accurate and current, however, it is not guaranteed. Comparison to the most current criteria is the responsibility of the client and SGS assumes no responsibility for the accuracy of the criteria levels indicated. This document is issued, on the Client's behalf, by the Company under its General Conditions of Service available on request and accessible at http://www.sgs.com/terms\_and\_conditions.htm. The Client's attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any other holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

This report must not be reproduced, except in full. This report supersedes all previous versions.

-- End of Analytical Report --

20200609 16 / 17

Request for Laboratory Services and CHAIN OF CUSTODY

Environment, Health & Safety - Lakefield: 185 Concession St., Lakefield, ON KOL 2H0 Phone: 705-652-2000 Fax: 705-652-6365 Web: www.sgs.com/environment

No: 012656

Note: Submission of samples to SGS is acrowledgement that you have been provided direction on sample collection/handling and transportation of samples to SGS is considered autorization for completion of work. Signatures may appear on this form or be retained on file in the confract, or in an alternative format (e.g. shipping documents). (3) Results may be sent by email to an unlimited number of addresses for no additional cost. Fax is available upon request. This document is issued by the Company under its General Conditions of Service accessible at	may appear on thi	rk. Signatures	mpletion of wo	ation for co	ed authoriz documen	considere est. This	SGS is	amples to	ssion of s	(2) Subm onal cost	samples.	rtation of fresses fo	nd transponder of add	Mandling a	ple collection mail to an ur	rection on sam ay be sent by	en provided d (3) Results m	you have be documents).	owledgement that nat (e.g. shipping	SGS is adm	ion of samples to ntract, or in an al	Note: Submiss the co	Sept. 2019	Revision #: 1.2 Date of Issue: 09 Sept, 2019	He
Yellow & White Copy - SGS		(mm/dd/yy)	20	2	2	atte.	Da						1	N	'		Signature:			Naio	1807	L.	Relinquished by (NAME):	elinquish	R
Pink Copy - Client		(mm/dd/yy)	20	2	3	Date:	Da				1		1	1	1	1	Signature:				Nao	Susus	Sampled By (NAME):	ampled B	S
									1	1	\	1	1	\	1						tions	Observations/Comments/Special Instructions	ns/Comments	bservation	0
																								N	12
																								-	=
																								0	10
																									9
10000000000000000000000000000000000000																									00
																									7
			9																					0,	6
																								- Ci	O
																									4
									X							<	W	~	<			555	10	-	ω
														X		_	_	-				5 3	5	1.1	N
									X					X		5	7	Mah	Wo	Se2		552	1	MA	-
	Water Charact General	Sewer Use: Specify pkg:			Organochlorine or specif	BTEX only Pesticides	VOCs all incl BTEX	F1-F4 only	F1-F4 + BTEX	PCBs Total	PAHs only SVOCs	ICP Metals onl Sb,As,Ba,Be,B,Cd,Cr,Co,C Se,Ag,TI,U,V,Zn	Full Metals Su ICP metals plus B(HWS-su	Metals & Inorginal CrVI, CN,Hg pH,(B(HV (CI, Na-water)	Field Filtered (	ES MATRIX	# OF BOTTLES	TIME	DATE	g <sub>0</sub>	NOIT	SAMPLE IDENTIFICATION	SAMPLE		Selection of the select
COMMENTS:	Exter				y other					Arc		y cu,Pb,M	oil only)		Y/N)			NO	YES   N	X	NDITION (R	RECORD OF SITE CONDITION (RSC)	RECORE		1000
	nded									oclor 🗌		o,Ni,		CS SAR-soil)		Sanitary Storm Municipality:		3 Day min 1 MMER Other:	Reg 347/558 (3 Day min TAT) PWQO MMER CCME Other:	0000	Soil Texture:  **Coarse**    Medium    Fine	Res/Park Ind/Com Agri/Other	° ° °	Table 1  Table 2  Table 3  Table 3	DADE
	TCLP	e specify)	Other (please specify)	0	Pest	Pe	VOC	PHC		PCB	SVOC			×	W:	Sewer By-Law:	Se	S:	Other Regulations:	Othe			n 153/0	egulation	7.77
				D	ESTED	IUQ	SRE	<b>NALYSIS REQUES</b>	ANA										ONS	REGULATIONS	2	_	,		199
NOTE: DRINKING (POTABLE) WATER SAMPLES FOR HUMAN CONSUMPTION MUST BE SUBMITTED WITH SGS DRINKING WATER CHAIN OF CUSTODY	N CONSUMPTION OF CUSTODY	FOR HUMAI	R SAMPLES DRINKING W.	E) WATE	POTABL	NKING (	E: DRII	NOT					Date:_	Specify Due Date:	Spe				7	Email:	ded co	mir eg rondedag ca	Boom	Email:	m
		ays )N	RUSH TAT (Additional Charges May Apply): ☐ 1 Day ☐ 2 Days ☐ 3 Days ☐ 4 Days PLEASE CONFIRM RUSH FEASIBILITY WITH SGS REPRESENTATIVE PRIOR TO SUBMISSION	OR TO	2 Days	ENTAT	1 Day	GS RE	NITH S	lay Ap	FEASIE	nal Ch	(Additio	RUSH TAT (Additional Charges May Apply): PLEASE CONFIRM RUSH FEASIBILITY WITH	PLE				e:	Phone:	-	100	-	Fax:	TIT
TAT's are quoted in business days (exclude statutory holidays & weekends).  Samples received after 6pm or on weekends: TAT begins next business day	MISS is a GC siness days (exclude statutory 6pm or on weekends: TAT be	siness days (	TURNAROUND TIME (TAT) REQUIRED  TAT's are quoted in bus Samples received after	TAT's are Samples	TIME (T	GNUO	RNAR	TI.			lays)	AT (5-7)	Regular TAT (5-7days)	<sup>™</sup> N					act: ess:	Contact:	WHH 189	NAMY AND ROWING	10 TO PO	Address:	
St. N.	Elizabeth		Site Location/ID:23	Site Lo							M.	180	20-	Project #:	Pro				Company:	_	3 (	8	Jess	Contact:	C
		- 88		P.O. #:										Quotation #:	Quo	2	Report Information)	ort Inform	(same as Report Information)	- 10	En inecris	1 20	Company: Grounded	ompany	0
way at the	LAB LIMS #3 AT 1911 D	LABLI					I	1	1	br (-c)	on Hece	remperature upon Receipt ("C)	remper			T T REGIL	di midet.	Cusiony Sear Illiact.	IMI		TON (III.)	BEDORT INCORMATION	BEDOB	DOGGE	
1	5				10	1cc	Type:	1	18,	i ve	esent:	Cooling Agent Present:	Cooling		Påč	N N N N N N N N N N N N N N N N N N N	Received By (signature) Custody Seal Present: Custody Seal Intact:	Received By (signature Custody Seal Present:		(mm/dd/yy)	20 (mm	2000	Sept.	Received By: Received Date:	ת עע
									only	b use	on - La	Section	mation	y Infor	Laboratory Information Section - Lab use only	\_		900		,	11.1	1	3		
Page of								31	672-036	ax: 519	8-8060 F	: 877-84	Toll Free	672-4500	hone: 519-	657 Consortium Court, London, ON, N6E 2S8 Phone: 519-672-4500 Toll Free: 877-848-8060 Fax: 519-672-0361	, London, O	rtium Court	Jon: 657 Consc	- Lone			The state of		







CA14830-JUN20 R

20-088 25 Elizabeth St, N, Mississauga

Prepared for

**Grounded Engineering Inc.** 



#### First Page

CLIENT DETAIL:	S	LABORATORY DETAIL	ILS
Client	Grounded Engineering Inc.	Project Specialist	Brad Moore Hon. B.Sc
		Laboratory	SGS Canada Inc.
Address	12 Banigan Drive	Address	185 Concession St., Lakefield ON, K0L 2H0
	Toronto, Ontario		
	M4H1E9. Canada		
Contact	Jessie Wu	Telephone	705-652-2143
Telephone	647-264-7909	Facsimile	705-652-6365
Facsimile		Email	brad.moore@sgs.com
Email	jwu@groundedeng.ca	SGS Reference	CA14830-JUN20
Project	20-088 25 Elizabeth St, N, Mississauga	Received	06/04/2020
Order Number		Approved	06/10/2020
Samples	Soil (2)	Report Number	CA14830-JUN20 R
		Date Reported	06/10/2020

#### COMMENTS

CCME Method Compliance: Analyses were conducted using analytical procedures that comply with the Reference Method for the CWS for Petroleum Hydrocarbons in Soil and have been validated for use at the SGS laboratory, Lakefield, ON site.

Quality Compliance: Instrument performance / calibration quality criteria were met and extraction and analysis limits for holding times were met.

nC6 and nC10 response factors within 30% of response factor for toluene: YES

nC10, nC16 and nC34 response factors within 10% of the average response for the three compounds: YES

C50 response factors within 70% of nC10 + nC16 + nC34 average: YES

Linearity is within 15%: YES

F4G - gravimetric heavy hydrocarbons cannot be added to the C6 to C50 hydrocarbons.

The results for F4 and F4G are both reported and the greater of the two values is to be used in application to the CWS PHC.

Hydrocarbon results are expressed on a dry weight basis.

Temperature of Sample upon Receipt: 10 degrees C

Cooling Agent Present:Yes Custody Seal Present:Yes

Chain of Custody Number:013369

#### SIGNATORIES

Brad Moore Hon. B.Sc Brad Mo

1 / 17

SGS Canada Inc. 185 Concession St., Lakefield ON, K0L 2H0 t 705-652-2143 f 705-652-6365

Member of the SGS Group (SGS SA)

www.sgs.com



#### **TABLE OF CONTENTS**

First Page	1
Index	2
Results	3-6
Exceedance Summary	
Holding Time Summary	8-9
QC Summary	
Legend	16
Δηπογος	17



#### CA14830-JUN20 R

Client: Grounded Engineering Inc.

Project: 20-088 25 Elizabeth St, N, Mississauga

Project Manager: Jessie Wu

Samplers: Rehan Fawan/Jessie Wu

PACKAGE: <b>REG153 - BTEX</b> (SOIL)			Sample Number	8	9
			Sample Name	BH2 SS2	BH2 SS4
I = REG153 / SOIL / COARSE - TABLE 3 - Residential/Par	ırkland - UNDEFINED		Sample Matrix	Soil	Soil
			Sample Date	02/06/2020	02/06/2020
Parameter	Units	RL	L1	Result	Result
BTEX					
Benzene	μg/g	0.02	0.21	< 0.02	< 0.02
Ethylbenzene	μg/g	0.05	2	< 0.05	< 0.05
Toluene	μg/g	0.05	2.3	< 0.05	< 0.05
Xylene (total)	μg/g	0.05	3.1	< 0.05	< 0.05
m/p-xylene	μg/g	0.05		< 0.05	< 0.05
o-xylene	μg/g	0.05		< 0.05	< 0.05
ACKAGE: <b>REG153 - Hydrides</b> (SOIL)	)		Sample Number	8	9
(0.0.1.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0	,		Sample Name	BH2 SS2	BH2 SS4
1 = REG153 / SOIL / COARSE - TABLE 3 - Residential/Par	ırkland - UNDEFINED		Sample Matrix	Soil	Soil
			Sample Date	02/06/2020	02/06/2020
Parameter	Units	RL	L1	Result	Result
Hydrides					
Antimony	μg/g	0.8	7.5	< 0.8	< 0.8
Arsenic	μg/g	0.5	18	2.8	2.0
Selenium	μg/g	0.7	2.4	< 0.7	< 0.7
·					



#### CA14830-JUN20 R

**Client:** Grounded Engineering Inc.

Project: 20-088 25 Elizabeth St, N, Mississauga

Project Manager: Jessie Wu

Samplers: Rehan Fawan/Jessie Wu

ACKAGE: REG153 - Metals and Inorganic	cs (SOIL)		Sample Number	8	9
			Sample Name	BH2 SS2	BH2 SS4
= REG153 / SOIL / COARSE - TABLE 3 - Residential/Parkland -	UNDEFINED		Sample Matrix	Soil	Soil
			Sample Date	02/06/2020	02/06/2020
Parameter	Units	RL	L1	Result	Result
letals and Inorganics					
Moisture Content	%	-		14.3	8.4
Barium	μg/g	0.1	390	50	55
Beryllium	μg/g	0.02	4	0.36	0.33
Boron	μg/g	1	120	4	6
Cadmium	μg/g	0.02	1.2	0.10	0.07
Chromium	μg/g	0.5	160	16	16
Cobalt	μg/g	0.01	22	7.9	7.4
Copper	μg/g	0.1	140	19	18
Lead	μg/g	0.1	120	11	5.6
Molybdenum	μg/g	0.1	6.9	0.4	0.2
Nickel	μg/g	0.5	100	16	15
Silver	μg/g	0.05	20	< 0.05	< 0.05
Thallium	μg/g	0.02	1	0.09	0.09
Uranium	μg/g	0.002	23	0.38	0.41
Vanadium	μg/g	3	86	27	24
Zinc	μg/g	0.7	340	47	33
Water Soluble Boron	μg/g	0.5	1.5	< 0.5	< 0.5



#### CA14830-JUN20 R

Client: Grounded Engineering Inc.

Project: 20-088 25 Elizabeth St, N, Mississauga

Project Manager: Jessie Wu

Samplers: Rehan Fawan/Jessie Wu

ACKAGE: REG153 - Other (ORP)	(SOIL)		Sa	ample Number	8	9
			8	Sample Name	BH2 SS2	BH2 SS4
= REG153 / SOIL / COARSE - TABLE 3 - Residentia	al/Parkland - UNDEFINED		8	Sample Matrix	Soil	Soil
				Sample Date	02/06/2020	02/06/2020
Parameter	Units	RL	L1		Result	Result
other (ORP)						
Mercury	μg/g	0.05	0.27		< 0.05	< 0.05
Sodium Adsorption Ratio		0.2	5		< 0.2	0.6
SAR Calcium	mg/L	0.09			23.9	16.7
SAR Magnesium	mg/L	0.02			1.8	2.9
SAR Sodium	mg/L	0.15			3.2	10.0
Conductivity	mS/cm	0.002	0.7		0.15	0.16
рН	pH Units	0.05			7.85	7.83
Chromium VI	μg/g	0.2	8		< 0.2	< 0.2
Free Cyanide	μg/g	0.05	0.051		< 0.05	< 0.05



#### CA14830-JUN20 R

**Client:** Grounded Engineering Inc.

Project: 20-088 25 Elizabeth St, N, Mississauga

Project Manager: Jessie Wu

Samplers: Rehan Fawan/Jessie Wu

PACKAGE: <b>REG153 - PHCs</b> (SOIL)			Sample Number	8	9
			Sample Name	BH2 SS2	BH2 SS4
1 = REG153 / SOIL / COARSE - TABLE 3 - Residential/Parklan	id - UNDEFINED		Sample Matrix	Soil	Soil
			Sample Date	02/06/2020	02/06/2020
Parameter	Units	RL	L1	Result	Result
PHCs					
F1 (C6-C10)	μg/g	10	55	< 10	< 10
F1-BTEX (C6-C10)	μg/g	10		< 10	< 10
F2 (C10-C16)	μg/g	10	98	< 10	< 10
F3 (C16-C34)	μg/g	50	300	< 50	< 50
F4 (C34-C50)	μg/g	50	2800	< 50	< 50
Chromatogram returned to baseline at nC50	Yes / No	-		YES	YES

# SGS FINAL REPORT

#### **EXCEEDANCE SUMMARY**

No exceedances are present above the regulatory limit(s) indicated

20200610 7 / 17





Sample Name	QC Batch Reference	Sample Number	Sampled	Received	Extracted/ Prepared	Analysed	Holding Time	Approved
Conductivity								
Method: EPA 6010/SM 2510	0   Internal ref.: ME-CA-[ENV]I	EWL-LAK-	AN-006					
BH2 SS2	EWL0145-JUN20	8	06/02/2020	06/04/2020	06/05/2020	06/08/2020	06/30/2020	06/08/202
BH2 SS4	EWL0145-JUN20	9	06/02/2020	06/04/2020	06/05/2020	06/08/2020	06/30/2020	06/08/202
Cyanide by SFA								
Method: SM 4500   Internal	ref.: ME-CA-[ENV]SFA-LAK-A	N-005						
BH2 SS2	SKA5025-JUN20	8	06/02/2020	06/04/2020	06/04/2020	06/05/2020	06/16/2020	06/10/202
BH2 SS4	SKA5025-JUN20	9	06/02/2020	06/04/2020	06/04/2020	06/05/2020	06/16/2020	06/10/202
Hexavalent Chromium by SI	FA							
Method: EPA218.6/EPA306	0A   Internal ref.: ME-CA-[EN\	/JSKA-LAI	K-AN-012					
BH2 SS2	SKA5033-JUN20	8	06/02/2020	06/04/2020	06/08/2020	06/09/2020	07/02/2020	06/10/202
BH2 SS4	SKA5033-JUN20	9	06/02/2020	06/04/2020	06/08/2020	06/09/2020	07/02/2020	06/10/202
Mercury by CVAAS								
	45   Internal ref.: ME-CA-[ENV	]SPE-LAK	(-AN-004					
BH2 SS2	EMS0028-JUN20	8	06/02/2020	06/04/2020	06/04/2020	06/08/2020	06/30/2020	06/09/202
BH2 SS4	EMS0028-JUN20	9	06/02/2020	06/04/2020	06/04/2020	06/08/2020	06/30/2020	06/09/202
Matala in announce accordes	IOD OEG							
		ENVISPE-	-LAK-AN-003					
	A 6010   Internal ref.: ME-CA-[			06/04/2020	06/05/2020	06/05/2020	11/20/2020	06/08/202
Method: MOE 4696e01/EPA BH2 SS2	A 6010   Internal ref.: ME-CA-[ ESG0022-JUN20	8	06/02/2020	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4	ESG0022-JUN20 ESG0022-JUN20			06/04/2020 06/04/2020	06/05/2020 06/05/2020	06/05/2020 06/05/2020	11/29/2020	
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4 Metals in Soil - Aqua-regia/l	ESG0022-JUN20 ESG0022-JUN20 CP-MS	8 9	06/02/2020 06/02/2020					06/08/202 06/08/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/l Method: EPA 3050/EPA 200	ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENV	8 9 /]SPE-LAK	06/02/2020 06/02/2020 <b>C-AN-005</b>	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/202
Method: MOE 4696e01/EPA  BH2 SS2  BH2 SS4  Metals in Soil - Aqua-regia/l  Method: EPA 3050/EPA 200  BH2 SS2	ESG0022-JUN20 ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENV	8 9 <b>/]SPE-LAH</b> 8	06/02/2020 06/02/2020 <b>C-AN-005</b> 06/02/2020	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/l Method: EPA 3050/EPA 200	ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENV	8 9 /]SPE-LAK	06/02/2020 06/02/2020 <b>C-AN-005</b>	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/l Method: EPA 3050/EPA 200 BH2 SS2 BH2 SS4  Moisture	ESG0022-JUN20 ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENVEX EMS0028-JUN20 EMS0028-JUN20	8 9 <b>/]SPE-LA</b> k 8 9	06/02/2020 06/02/2020 <b>C-AN-005</b> 06/02/2020	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/l Method: EPA 3050/EPA 200 BH2 SS2 BH2 SS4  Moisture	ESG0022-JUN20 ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENV	8 9 <b>/]SPE-LA</b> k 8 9	06/02/2020 06/02/2020 <b>C-AN-005</b> 06/02/2020	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/l Method: EPA 3050/EPA 200 BH2 SS2 BH2 SS4  Moisture	ESG0022-JUN20 ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENVEX EMS0028-JUN20 EMS0028-JUN20	8 9 <b>/]SPE-LA</b> k 8 9	06/02/2020 06/02/2020 <b>C-AN-005</b> 06/02/2020	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/09/202 06/09/202 06/09/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/li Method: EPA 3050/EPA 200 BH2 SS2 BH2 SS4  Moisture  Method: CCME Tier 1   Inte	ESG0022-JUN20 ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENV] EMS0028-JUN20 EMS0028-JUN20	8 9 /]SPE-LAH 8 9	06/02/2020 06/02/2020 <b>K-AN-005</b> 06/02/2020 06/02/2020	06/04/2020 06/04/2020 06/04/2020	06/05/2020 06/04/2020 06/04/2020	06/05/2020 06/08/2020 06/08/2020	11/29/2020 11/29/2020 11/29/2020	06/08/202 06/09/202 06/09/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/l Method: EPA 3050/EPA 200 BH2 SS2 BH2 SS4  Moisture  Method: CCME Tier 1   Interesting the state of the	ESG0022-JUN20 ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENV] EMS0028-JUN20 EMS0028-JUN20 emal ref.: ME-CA-[ENV]GC-LAI GCM0140-JUN20 GCM0140-JUN20	8 9 //SPE-LAH 8 9	06/02/2020 06/02/2020 <b>C-AN-005</b> 06/02/2020 06/02/2020	06/04/2020 06/04/2020 06/04/2020	06/05/2020 06/04/2020 06/04/2020	06/05/2020 06/08/2020 06/08/2020	11/29/2020 11/29/2020 11/29/2020 08/01/2020	06/09/202 06/09/202 06/09/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/l Method: EPA 3050/EPA 200 BH2 SS2 BH2 SS4  Moisture Method: CCME Tier 1   Inte BH2 SS2 BH2 SS4  Petroleum Hydrocarbons (F	ESG0022-JUN20 ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENV] EMS0028-JUN20 EMS0028-JUN20 emal ref.: ME-CA-[ENV]GC-LAI GCM0140-JUN20 GCM0140-JUN20	8 9 //SPE-LAK 8 9 <an-010 8</an-010 	06/02/2020 06/02/2020 <b>C-AN-005</b> 06/02/2020 06/02/2020	06/04/2020 06/04/2020 06/04/2020	06/05/2020 06/04/2020 06/04/2020	06/05/2020 06/08/2020 06/08/2020	11/29/2020 11/29/2020 11/29/2020 08/01/2020	06/09/202 06/09/202 06/09/202
Method: MOE 4696e01/EPA BH2 SS2 BH2 SS4  Metals in Soil - Aqua-regia/l Method: EPA 3050/EPA 200 BH2 SS2 BH2 SS4  Moisture Method: CCME Tier 1   Intel BH2 SS2 BH2 SS4  Petroleum Hydrocarbons (F	ESG0022-JUN20 ESG0022-JUN20 ESG0022-JUN20 CP-MS D.8   Internal ref.: ME-CA-[ENV EMS0028-JUN20 EMS0028-JUN20 emai ref.: ME-CA-[ENV]GC-LAI GCM0140-JUN20 GCM0140-JUN20	8 9 //SPE-LAK 8 9 <an-010 8</an-010 	06/02/2020 06/02/2020 <b>C-AN-005</b> 06/02/2020 06/02/2020	06/04/2020 06/04/2020 06/04/2020	06/05/2020 06/04/2020 06/04/2020	06/05/2020 06/08/2020 06/08/2020	11/29/2020 11/29/2020 11/29/2020 08/01/2020	06/09/202 06/09/202 06/09/202

20200610 8 / 17

GCM0096-JUN20

GCM0096-JUN20

8

06/02/2020

06/02/2020

06/04/2020

06/04/2020

06/05/2020

06/05/2020

06/05/2020

06/05/2020

07/12/2020

07/12/2020

06/09/2020

06/09/2020

Method: CCME Tier 1 | Internal ref.: ME-CA-[ENV]GC-LAK-AN-010

BH2 SS2

BH2 SS4



#### HOLDING TIME SUMMARY

BH2 SS4

HOLDING TIME SUMMART								
Sample Name	QC Batch Reference	Sample Number	Sampled	Received	Extracted/ Prepared	Analysed	Holding Time	Approved
pH								
Method: SM 4500   Internal ref	f.: ME-CA-[ENV]EWL-LAK-/	N-001						
BH2 SS2	ARD0032-JUN20	8	06/02/2020	06/04/2020	06/08/2020	06/08/2020	07/02/2020	06/08/202
BH2 SS4	ARD0032-JUN20	9	06/02/2020	06/04/2020	06/08/2020	06/08/2020	07/02/2020	06/08/2020
Sodium adsorption ratio (SAR)								
Method: MOE 4696e01/EPA 60	010   Internal ref.: ME-CA-[	ENV]ARD	-LAK-AN-021					
BH2 SS2	ESG0022-JUN20	8	06/02/2020	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/2020
BH2 SS4	ESG0022-JUN20	9	06/02/2020	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/2020
Volatile Organics								
Method: EPA 5035A/5030B/82	60C   Internal ref.: ME-CA-	[ENV]GC-	LAK-AN-004					
BH2 SS2	GCM0109-JUN20	8	06/02/2020	06/04/2020	06/05/2020	06/05/2020	06/16/2020	06/09/2020
BH2 SS4	GCM0109-JUN20	9	06/02/2020	06/04/2020	06/05/2020	06/05/2020	06/16/2020	06/09/2020
Water Soluble Boron								
Method: O.Reg. 153/04   Intern	nal ref.: ME-CA-[ENV] SPE-	LAK-AN-(	003					
BH2 SS2	ESG0020-JUN20	8	06/02/2020	06/04/2020	06/05/2020	06/05/2020	11/29/2020	06/08/2020

06/02/2020

06/04/2020

06/05/2020

06/05/2020

11/29/2020

06/08/2020

20200610 9 / 17

ESG0020-JUN20

9



#### QC SUMMARY

Conductivity

Method: EPA 6010/SM 2510 | Internal ref.: ME-CA-[ENV]EWL-LAK-AN-006

Parameter	QC batch	Units	RL	Method	Duj	olicate	LC	S/Spike Blank	S/Spike Blank		atrix Spike / Ref.	
	Reference			Blank	RPD	AC	Spike	Recovery Limits (%)		•		ry Limits
						(%)	Recovery (%)	Low	High	(%)	Low	High
Conductivity	EWL0145-JUN20	mS/cm	0.002	<0.002	0	10	99	90	110	NA		

#### Cyanide by SFA

Method: SM 4500 | Internal ref.: ME-CA-IENVISFA-LAK-AN-005

Parameter	QC batch	Units	RL	Method	Duj	olicate	LC	CS/Spike Blank  Recovery Limits  (%)		Matrix Spike /		/ Ref.	
	Reference			Blank	RPD	AC	Spike			Spike Recovery	Recover	ry Limits 6)	
						(%)	Recovery (%)	Low	High	(%)	Low	High	
Free Cyanide	SKA5025-JUN20	μg/g	0.05	<0.05	ND	20	105	80	120	100	75	125	

#### **Hexavalent Chromium by SFA**

Method: EPA218.6/EPA3060A | Internal ref.: ME-CA-[ENV]SKA-LAK-AN-012

Parameter	QC batch	Units	RL	Method	Duj	olicate	LC	S/Spike Blank  Recovery Limits  (%)		M	atrix Spike / Ref	
	Reference			Blank	RPD	AC	Spike			Spike Recovery	Recover	ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
Chromium VI	SKA5033-JUN20	ug/g	0.2	<0.2	ND	20	90	80	120	78	75	125

20200610 10 / 17



#### QC SUMMARY

Mercury by CVAAS

Method: EPA 7471A/EPA 245 | Internal ref.: ME-CA-[ENVISPE-LAK-AN-004

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank Recovery Limits (%)		M	latrix Spike / Ref	:
	Reference			Blank	RPD	AC	Spike			Spike Recovery	11000101	
						(%)	Recovery (%)	Low	High	(%)	Low	High
Mercury	EMS0028-JUN20	μg/g	0.05	<0.05	ND	20	98	80	120	97	70	130

#### Metals in aqueous samples - ICP-OES

Method: MOE 4696e01/EPA 6010 | Internal ref.: ME-CA-IENVISPE-LAK-AN-003

Parameter	QC batch	Units	RL	Method	Dup	licate LCS/Sp		S/Spike Blank		Matrix Spike / Ref.		
	Reference			Blank	RPD	AC (%)	Spike Recovery Limits (%)		Spike Recovery		ry Limits %)	
						(%)	(%)	Low	High	(%)	Low	High
SAR Calcium	ESG0022-JUN20	mg/L	0.09	<0.09	0	20	103	80	120	104	70	130
SAR Magnesium	ESG0022-JUN20	mg/L	0.02	<0.02	1	20	99	80	120	102	70	130
SAR Sodium	ESG0022-JUN20	mg/L	0.15	<0.15	0	20	98	80	120	106	70	130

20200610 11 / 17



#### QC SUMMARY

Metals in Soil - Aqua-regia/ICP-MS

Method: EPA 3050/EPA 200.8 | Internal ref.: ME-CA-[ENV]SPE-LAK-AN-005

Parameter	QC batch	Units	RL	Method	Dup	licate	LCS	S/Spike Blank		Ma	atrix Spike / Re	i.
	Reference			Blank	RPD	AC (%)	Spike Recovery	Recover	•	Spike Recovery		ry Limits %)
						(%)	(%)	Low	High	(%)	Low	High
Silver	EMS0028-JUN20	ug/g	0.05	<0.05	ND	20	103	70	130	107	70	130
Arsenic	EMS0028-JUN20	μg/g	0.5	<0.5	6	20	101	70	130	99	70	130
Barium	EMS0028-JUN20	ug/g	0.1	<0.1	6	20	101	70	130	108	70	130
Beryllium	EMS0028-JUN20	μg/g	0.02	<0.02	7	20	101	70	130	97	70	130
Boron	EMS0028-JUN20	μg/g	1	<1	6	20	107	70	130	107	70	130
Cadmium	EMS0028-JUN20	μg/g	0.02	<0.02	1	20	102	70	130	111	70	130
Cobalt	EMS0028-JUN20	μg/g	0.01	<0.01	5	20	104	70	130	117	70	130
Chromium	EMS0028-JUN20	μg/g	0.5	<0.5	5	20	105	70	130	119	70	130
Copper	EMS0028-JUN20	μg/g	0.1	<0.1	4	20	106	70	130	115	70	130
Molybdenum	EMS0028-JUN20	μg/g	0.1	<0.1	7	20	96	70	130	114	70	130
Nickel	EMS0028-JUN20	ug/g	0.5	<0.5	4	20	103	70	130	116	70	130
Lead	EMS0028-JUN20	μg/g	0.1	<0.1	5	20	102	70	130	103	70	130
Antimony	EMS0028-JUN20	μg/g	0.8	<0.8	ND	20	100	70	130	108	70	130
Selenium	EMS0028-JUN20	μg/g	0.7	<0.7	ND	20	107	70	130	108	70	130
Thallium	EMS0028-JUN20	μg/g	0.02	<0.02	9	20	105	70	130	105	70	130
Uranium	EMS0028-JUN20	µg/g	0.002	<0.002	3	20	100	70	130	97	70	130
Vanadium	EMS0028-JUN20	μg/g	3	<3	5	20	105	70	130	114	70	130
Zinc	EMS0028-JUN20	μg/g	0.7	<0.7	2	20	105	70	130	108	70	130

20200610 12 / 17



#### QC SUMMARY

Petroleum Hydrocarbons (F1)

Method: CCME Tier 1 | Internal ref.: ME-CA-[ENVIGC-LAK-AN-010

Parameter	QC batch	Units	RL	Method	Duj	olicate	LC	.CS/Spike Blank		M	Matrix Spike / Ref.	
	Reference			Blank	RPD	AC	Spike	(%)		Spike Recovery	Recove	-
						(%)	(%) Recovery (%)		High	(%)	Low	High
F1 (C6-C10)	GCM0109-JUN20	μg/g	10	<10	ND	30	107	80	120	95	60	140

#### Petroleum Hydrocarbons (F2-F4)

Method: CCME Tier 1 | Internal ref.: ME-CA-IENVIGC-LAK-AN-010

Parameter	QC batch	Units	RL		Duplicate		LC	S/Spike Blank		Matrix Spike / Ref.				
	Reference	Reference		ice Blank		Blank	RPD	AC	Spike	Recove	ry Limits %)	Spike Recovery		ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High		
F2 (C10-C16)	GCM0096-JUN20	μg/g	10	<10	ND	30	110	80	120	109	60	140		
F3 (C16-C34)	GCM0096-JUN20	μg/g	50	<50	ND	30	110	80	120	109	60	140		
F4 (C34-C50)	GCM0096-JUN20	μg/g	50	<50	ND	30	110	80	120	109	60	140		

20200610 13 / 17



#### QC SUMMARY

pН

Method: SM 4500 | Internal ref.: ME-CA-[ENV]EWL-LAK-AN-001

Parameter	QC batch	Units	RL	Method	Duj	olicate	LC	S/Spike Blank		Matrix Spike / Ref.		
	Reference			Blank	RPD	AC	Spike	Recovery Limits (%)				ry Limits
						(%)	Recovery (%)	Low	High	(%)	Low	High
рН	ARD0032-JUN20	pH Units	0.05		1	20	100	80	120			

#### **Volatile Organics**

Method: EPA 5035A/5030B/8260C | Internal ref.: ME-CA-IENVIGC-LAK-AN-004

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		Ma	atrix Spike / Ref	
	Reference			Blank	RPD	AC	Spike	Recover	•	Spike Recovery		ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
Benzene	GCM0109-JUN20	μg/g	0.02	<0.02	ND	50	97	60	130	83	50	140
Ethylbenzene	GCM0109-JUN20	μg/g	0.05	<0.05	ND	50	96	60	130	89	50	140
m/p-xylene	GCM0109-JUN20	μg/g	0.05	<0.05	ND	50	100	60	130	92	50	140
o-xylene	GCM0109-JUN20	μg/g	0.05	<0.05	ND	50	96	60	130	92	50	140
Toluene	GCM0109-JUN20	μg/g	0.05	<0.05	ND	50	95	60	130	87	50	140

20200610 14 / 17

CA14830-JUN20 R



#### **QC SUMMARY**

#### Water Soluble Boron

Method: O.Reg. 153/04 | Internal ref.: ME-CA-IENVI SPE-LAK-AN-003

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank		M	latrix Spike / Ref	f.
	Reference			Blank	RPD	AC	Spike		ery Limits %)	Spike Recovery		ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
Water Soluble Boron	ESG0020-JUN20	μg/g	0.5	<0.5	ND	20	100	80	120	116	70	130

Method Blank: a blank matrix that is carried through the entire analytical procedure. Used to assess laboratory contamination.

Duplicate: Paired analysis of a separate portion of the same sample that is carried through the entire analytical procedure. Used to evaluate measurement precision.

LCS/Spike Blank: Laboratory control sample or spike blank refer to a blank matrix to which a known amount of analyte has been added. Used to evaluate analyte recovery and laboratory accuracy without sample matrix effects.

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate laboratory accuracy with sample matrix effects.

Reference Material: a material or substance matrix matched to the samples that contains a known amount of the analyte of interest. A reference material may be used in place of a matrix spike.

RL: Reporting limit

RPD: Relative percent difference

AC: Acceptance criteria

Multielement Scan Qualifier: as the number of analytes in a scan increases, so does the chance of a limit exceedance by random chance as opposed to a real method problem. Thus, in multielement scans, for the LCS and matrix spike, up to 10% of the analytes may exceed the quoted limits by up to 10% absolute and the spike is considered acceptable.

**Duplicate Qualifier**: for duplicates as the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the average of the two duplicates is greater than five times the RL. **Matrix Spike Qualifier**: for matrix spikes, as the concentration of the native analyte increases, the uncertainty of the matrix spike recovery increases. Thus, the matrix spike acceptance limits apply only when the concentration of the matrix spike is greater than or equal to the concentration of the native analyte.

20200610 15 / 17



#### **LEGEND**

#### **FOOTNOTES**

NSS Insufficient sample for analysis.

RL Reporting Limit.

- † Reporting limit raised.
- ↓ Reporting limit lowered.
- NA The sample was not analysed for this analyte
- ND Non Detect

Samples analysed as received. Solid samples expressed on a dry weight basis. "Temperature Upon Receipt" is representative of the whole shipment and may not reflect the temperature of individual samples.

Analysis conducted on samples submitted pursuant to or as part of Reg. 153/04, are in accordance to the Protocol for Analytical Methods Used in the Assessment of Properties under Part XV.1 of the Environmental Protection Act" published by the Ministry and dated March 9, 2004 as amended.

SGS provides criteria information (such as regulatory or guideline limits and summary of limit exceedances) as a service. Every attempt is made to ensure the criteria information in this report is accurate and current, however, it is not guaranteed. Comparison to the most current criteria is the responsibility of the client and SGS assumes no responsibility for the accuracy of the criteria levels indicated. This document is issued, on the Client's behalf, by the Company under its General Conditions of Service available on request and accessible at http://www.sgs.com/terms\_and\_conditions.htm. The Client's attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any other holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

This report must not be reproduced, except in full. This report supersedes all previous versions.

-- End of Analytical Report --

20200610 16 / 17



# Request for Laboratory Services and CHAIN OF CUSTODY

Environment, Health & Safety - Lakefield: 185 Concession St., Lakefield, ON K0L 2H0 Phone: 705-652-2000 Fax: 705-652-6365 Web: www.sgs.com/environment - London: 657 Consortium Court, London, ON, N6E 2S8 Phone: 519-672-4500 Toll Free: 877-848-8060 Fax: 519-672-0361

Pink Copy - Client Yellow & White Copy - SGS Is form or be retained on file in	REMAIN Faw Zan Joso WM Signature:    Date: June 2 / 20 (mm/dd/yy) Pink Copy - Client	2 / 20 2 / 20 ation for completion of wo	dun!	Date:	D D					atom of g		dimend	My,	John .	Signature: Signature:	S Page Page	an / Lesgi IVM	NAM FaWzan  Tess) e W	ampled By (NAME): elinquished by (NAME):	ampled elinquis
								A STATE OF THE STA										al Instructions	1 2 2 bservations/Comments/Special Instructions	rvati
											No.									
202.																				
received by							×					>		6		4	,	÷	BH 2 >>4	
Samples							X					< ×		1.8	4	Zpm	JUNE 2,20		1 2	
	Sewer Use: Specify pkg: Water Charac General		Organochlorine or spec	BTEX only Pesticides	VOCs all incl BTEX	F1-F4 only	F1-F4 + BTEX	PCBs Total	SVOCs all incl PAHs, ABNs, CPs	Sb,As,Ba,Be,B,Cd,Cr,Co, Se,Ag,TI,U,V,Zn	ICP Metals on Sb,As,Ba,Be,B,Cd,Cr,Co,	Metals & Inor incl CrVI, CN,Hg pH,(B(H (CI, Na-water)	Field Filtered	MATRIX	# OF BOTTLES	TIME	DATE	TIFICATION	SAMPLE IDENTIFICATION	
COMMENTS:	Exte		ify other				(			Cu,Pb,N	soil only)	0165				No	DYES ON	ITE CONDITION (RSC)	RECORD OF SITE	
	ation Pkg ation TCLP specify							oclor 🗌		lo,NI,		SAR-soil)		алу	Munic	(3 Day min TAT) MIMER Other:	☐ Reg 347/558 (3 Day min ☐ PWQO ☐ MMER ☐ CCME ☐ Other: ☐ MISA	ark Soil Texture:  m	le 1 Res/Park le 2 Ind/Com le 3 Agri/Other	Table 1 Table 2 Table 3 Table
	(please specify) TCLP	Other	PHC VOC Pest	CP	VOC	PHC	_ 4	PCI	SVOC	(0)		N Qo		Sewer By-Law:	Sewer	S:	Other Regulations:		Regulation 153/04:	gula
MUST BE SUBMITTED	NOTE: DHINKING (POTABLE) WATER SAMPLES FOR HUMAN CONSUMPTION MUST BE SUBMITTED WITH SGS DRINKING WATER CHAIN OF CUSTODY	H SGS DRINKING W.	(POTABLE	NKING	O E	YO NO	200				ate:	Specify Due Date	Specify	"			A Email:	groundleders. Ca	Jan Brand	Email:
	ays N	☐ 1 Day ☐ 2 Days ☐ 3 Days ☐ 4 Days SGS REPRESENTATIVE PRIOR TO SUBMISSION	2 Days	ay [	□ 1 D	GS RE		ay App	rges M EASIB	al Cha	dition	RUSH TAT (Additional Charges May Apply): PLEASE CONFIRM RUSH FEASIBILITY WITH	RUSH				Phone:	100g	Phone: 647 264	hone:
ins next business day	TAT's are quoted in business days (exclude statutory holidays & weekends).  Samples received after 6pm or on weekends: TAT begins next business day	TAT's are quoted in but Samples received after	S I IME (1	COUNT	MNAN				ays)	Regular TAT (5-7days)	lar TA		A				Contact: Address:	M 4H 1E9	No	3 res
	23 Elizabeth St.					4				280	20-	*	Quotation Project #:		ion)	port Informat	☐ (same as Report Information) Company:	Wu beginson	19/58 Syle(	Company:
															RMATION	INVOICE INFORMATION	INI		REPORT INFORMATION	
A14830-JUNZO	LAB LIMS #: (A) 4		(1)	1	Type:	F 9	No		0.	Cooling Agent Present: Temperature Upon Rec	poling A	100		8 8	signature): /// Present: Yes \( \) Intact: Yes \( \)	Received By (signature): Custody Seal Present: Custody Seal Intact:		(hr:min)	Received By: Think R Received Time: 10 :5	eivec
							only	b use	n-La	Section	ation	Inform	tory	Laboratory Information Section - Lab use only				PS INT	اما	







CA14915-MAY20 R

20-088, 25 Elizabeth St. N, Mississauga

Prepared for

**Grounded Engineering Inc.** 



#### First Page

CLIENT DETAILS	S	LABORATORY DETAI	ILS
Client	Grounded Engineering Inc.	Project Specialist	Brad Moore Hon. B.Sc
		Laboratory	SGS Canada Inc.
Address	12 Banigan Drive	Address	185 Concession St., Lakefield ON, K0L 2H0
	Toronto, Ontario		
	M4H1E9. Canada		
Contact	Jessie Wu	Telephone	705-652-2143
Telephone	647-264-7909	Facsimile	705-652-6365
Facsimile		Email	brad.moore@sgs.com
Email	jwu@groundedeng.ca	SGS Reference	CA14915-MAY20
Project	20-088, 25 Elizabeth St. N, Mississauga	Received	05/26/2020
Order Number		Approved	06/01/2020
Samples	Soil (5)	Report Number	CA14915-MAY20 R
		Date Reported	06/01/2020

#### COMMENTS

CCME Method Compliance: Analyses were conducted using analytical procedures that comply with the Reference Method for the CWS for Petroleum Hydrocarbons in Soil and have been validated for use at the SGS laboratory, Lakefield, ON site.

Quality Compliance: Instrument performance / calibration quality criteria were met and extraction and analysis limits for holding times were met.

nC6 and nC10 response factors within 30% of response factor for toluene: YES

nC10, nC16 and nC34 response factors within 10% of the average response for the three compounds: YES

C50 response factors within 70% of nC10 + nC16 + nC34 average: YES

Linearity is within 15%: YES

F4G - gravimetric heavy hydrocarbons cannot be added to the C6 to C50 hydrocarbons.

The results for F4 and F4G are both reported and the greater of the two values is to be used in application to the CWS PHC.

Hydrocarbon results are expressed on a dry weight basis.

Temperature of Sample upon Receipt: 5 degrees C

Cooling Agent Present:Yes

Custody Seal Present:Yes

Chain of Custody Number:013729

SIGNATORIES

Brad Moore Hon. B.Sc Brad Mo

SGS Canada Inc. 185 Concession St., Lakefield ON, K0L 2H0 t 705-652-2143 f 705-652-6365

> Member of the SGS Group (SGS SA) 1/18

www.sgs.com



#### **TABLE OF CONTENTS**

First Page	1
Index	2
Results	3-6
Exceedance Summary	7
Holding Time Summary	8-10
QC Summary	11-16
Legend	17
Annexes	18



#### CA14915-MAY20 R

**Client:** Grounded Engineering Inc.

Project: 20-088, 25 Elizabeth St. N, Mississauga

Project Manager: Jessie Wu Samplers: Jason Ngo

PACKAGE: <b>REG153 - BTEX</b> (SOIL)			Sample Number	8	9	10	11	12
			Sample Name	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP
1 = REG153 / SOIL / COARSE - TABLE 3 - Residential/Pa	arkland - UNDEFINED		Sample Matrix	Soil	Soil	Soil	Soil	Soil
			Sample Date	25/05/2020	25/05/2020	25/05/2020	25/05/2020	25/05/2020
Parameter	Units	RL	L1	Result	Result	Result	Result	Result
STEX								
Benzene	μg/g	0.02	0.21	< 0.02	< 0.02	< 0.02	< 0.02	< 0.02
Ethylbenzene	μg/g	0.05	2	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Toluene	μg/g	0.05	2.3	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Xylene (total)	μg/g	0.05	3.1	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
m/p-xylene	μg/g	0.05		< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
o-xylene	μg/g	0.05		< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
	,		Sample Number	8	9	10	11	12
PACKAGE: <b>REG153 - Hydrides</b> (SOIL	_)		Sample Number	0	9	10		
			Sample Name	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP
1 = REG153 / SOIL / COARSE - TABLE 3 - Residential/Pa	arkland - UNDEFINED		Sample Matrix	Soil	Soil	Soil	Soil	Soil
			Sample Date	25/05/2020	25/05/2020	25/05/2020	25/05/2020	25/05/2020
Parameter	Units	RL	L1	Result	Result	Result	Result	Result
lydrides								
Antimony	µg/g	0.8	7.5	< 0.8	< 0.8	< 0.8	< 0.8	< 0.8
Arsenic	μg/g	0.5	18	2.2	1.1	1.1	4.6	1.2
Selenium	μg/g	0.7	2.4	< 0.7	< 0.7	< 0.7	< 0.7	< 0.7



#### CA14915-MAY20 R

**Client:** Grounded Engineering Inc.

Project: 20-088, 25 Elizabeth St. N, Mississauga

**Project Manager:** Jessie Wu **Samplers:** Jason Ngo

ACKAGE: <b>REG153 - Metals and Ino</b> r	rganics (SOIL)		Sample Number	8	9	10	11	12
			Sample Name	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP
= REG153 / SOIL / COARSE - TABLE 3 - Residential/Pa	arkland - UNDEFINED		Sample Matrix	Soil	Soil	Soil	Soil	Soil
			Sample Date	25/05/2020	25/05/2020	25/05/2020	25/05/2020	25/05/2020
Parameter	Units	RL	L1	Result	Result	Result	Result	Result
etals and Inorganics								
Moisture Content	%	-		13.1	15.6	17.3	9.9	16.7
Barium	μg/g	0.1	390	25	12	13	60	13
Beryllium	μg/g	0.02	4	0.15	0.12	0.13	0.62	0.15
Boron	μg/g	1	120	3	2	3	12	3
Cadmium	μg/g	0.02	1.2	0.03	0.04	0.04	0.12	0.03
Chromium	μg/g	0.5	160	6.8	5.8	5.4	22	6.5
Cobalt	μg/g	0.01	22	3.7	2.7	3.4	14	4.1
Copper	μg/g	0.1	140	8.6	8.8	8.6	29	9.3
Lead	μg/g	0.1	120	3.3	2.5	2.6	7.3	3.2
Molybdenum	μg/g	0.1	6.9	0.1	0.1	0.1	0.3	0.2
Nickel	μg/g	0.5	100	7.4	5.2	6.1	31	7.2
Silver	μg/g	0.05	20	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Thallium	µg/g	0.02	1	0.04	0.03	0.03	0.14	0.04
Uranium	μg/g	0.002	23	0.46	0.36	0.31	0.66	0.31
Vanadium	μg/g	3	86	12	12	11	27	12
Zinc	μg/g	0.7	340	15	11	14	67	16
Water Soluble Boron	μg/g	0.5	1.5	< 0.5	< 0.5	< 0.5	0.8	< 0.5



#### CA14915-MAY20 R

**Client:** Grounded Engineering Inc.

Project: 20-088, 25 Elizabeth St. N, Mississauga

Project Manager: Jessie Wu
Samplers: Jason Ngo

PACKAGE: <b>REG153 - Other (ORP)</b> (S	SOIL)		Sample Number	8	9	10	11	12
			Sample Name	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP
= REG153 / SOIL / COARSE - TABLE 3 - Residential/Pa	arkland - UNDEFINED		Sample Matrix	Soil	Soil	Soil	Soil	Soil
			Sample Date	25/05/2020	25/05/2020	25/05/2020	25/05/2020	25/05/2020
Parameter	Units	RL	L1	Result	Result	Result	Result	Result
ther (ORP)								
Mercury	µg/g	0.05	0.27	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Sodium Adsorption Ratio		0.2	5	0.4	0.3	0.3	1.1	0.4
SAR Calcium	mg/L	0.09		17.6	15.7	27.9	11.1	35.0
SAR Magnesium	mg/L	0.02		1.9	2.6	1.8	6.9	3.6
SAR Sodium	mg/L	0.15		6.5	4.9	5.3	19.0	8.6
Conductivity	mS/cm	0.002	0.7	0.16	0.14	0.15	0.22	0.22
рН	pH Units	0.05		8.06	8.14	7.86	8.22	8.06
Chromium VI	μg/g	0.2	8	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2
Free Cyanide	μg/g	0.05	0.051	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05



#### CA14915-MAY20 R

Client: Grounded Engineering Inc.

Project: 20-088, 25 Elizabeth St. N, Mississauga

Project Manager: Jessie Wu

Samplers: Jason Ngo

ACKAGE: <b>REG153 - PHCs</b> (SOIL)			Sample Number	8	9	10	11	12
			Sample Name	BH3-SS4	BH3-SS6	BH4-SS5	BH4-SS8	DUP
= REG153 / SOIL / COARSE - TABLE 3 - Residential/Parkland	d - UNDEFINED		Sample Matrix	Soil	Soil	Soil	Soil	Soil
			Sample Date	25/05/2020	25/05/2020	25/05/2020	25/05/2020	25/05/2020
Parameter	Units	RL	L1	Result	Result	Result	Result	Result
HCs								
F1 (C6-C10)	μg/g	10	55	< 10	< 10	< 10	< 10	< 10
F1-BTEX (C6-C10)	μg/g	10		< 10	< 10	< 10	< 10	< 10
F2 (C10-C16)	μg/g	10	98	< 10	< 10	< 10	22	< 10
F3 (C16-C34)	μg/g	50	300	< 50	< 50	< 50	57	< 50
F4 (C34-C50)	μg/g	50	2800	< 50	< 50	< 50	< 50	< 50
Chromatogram returned to baseline at nC50	Yes / No	-		YES	YES	YES	YES	YES



#### **EXCEEDANCE SUMMARY**

No exceedances are present above the regulatory limit(s) indicated

20200601 7 / 18



#### HOLDING TIME SUMMARY

Sample Name	QC Batch Reference	Sample Number	Sampled	Received	Extracted/ Prepared	Analysed	Holding Time	Approved
Conductivity								
Method: FPA 6010/SM 2510   Internal ref.:	MF-CA-IFNVIE	WI -I AK-A	N-006					

BH3-SS4	EWL0447-MAY20	8	05/25/2020	05/26/2020	05/28/2020	05/28/2020	06/22/2020	05/29/2020
BH3-SS6	EWL0447-MAY20	9	05/25/2020	05/26/2020	05/28/2020	05/28/2020	06/22/2020	05/29/2020
BH4-SS5	EWL0447-MAY20	10	05/25/2020	05/26/2020	05/28/2020	05/28/2020	06/22/2020	05/29/2020
BH4-SS8	EWL0447-MAY20	11	05/25/2020	05/26/2020	05/28/2020	05/28/2020	06/22/2020	05/29/2020
DUP	EWL0447-MAY20	12	05/25/2020	05/26/2020	05/28/2020	05/28/2020	06/22/2020	05/29/2020

#### Cyanide by SFA

#### Method: SM 4500 | Internal ref.: ME-CA-[ENV]SFA-LAK-AN-005

BH3-SS4	SKA5129-MAY20	8	05/25/2020	05/26/2020	05/27/2020	05/28/2020	06/08/2020	05/28/2020
BH3-SS6	SKA5129-MAY20	9	05/25/2020	05/26/2020	05/27/2020	05/28/2020	06/08/2020	05/28/2020
BH4-SS5	SKA5129-MAY20	10	05/25/2020	05/26/2020	05/27/2020	05/28/2020	06/08/2020	05/28/2020
BH4-SS8	SKA5129-MAY20	11	05/25/2020	05/26/2020	05/27/2020	05/28/2020	06/08/2020	05/28/2020
DUP	SKA5129-MAY20	12	05/25/2020	05/26/2020	05/27/2020	05/28/2020	06/08/2020	05/28/2020

#### **Hexavalent Chromium by SFA**

#### Method: EPA218.6/EPA3060A | Internal ref.: ME-CA-[ENV]SKA-LAK-AN-012

BH3-SS4	SKA5138-MAY20	8	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/24/2020	05/30/2020
BH3-SS6	SKA5138-MAY20	9	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/24/2020	05/30/2020
BH4-SS5	SKA5138-MAY20	10	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/24/2020	05/30/2020
BH4-SS8	SKA5138-MAY20	11	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/24/2020	05/30/2020
DUP	SKA5138-MAY20	12	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/24/2020	05/30/2020

#### **Mercury by CVAAS**

# Method: EPA 7471A/EPA 245 | Internal ref.: ME-CA-[ENV]SPE-LAK-AN-004

BH3-SS4	EMS0125-MAY20	8	05/25/2020	05/26/2020	05/26/2020	05/28/2020	06/22/2020	05/28/2020
BH3-SS6	EMS0125-MAY20	9	05/25/2020	05/26/2020	05/26/2020	05/28/2020	06/22/2020	05/28/2020
BH4-SS5	EMS0125-MAY20	10	05/25/2020	05/26/2020	05/26/2020	05/28/2020	06/22/2020	05/28/2020
BH4-SS8	EMS0125-MAY20	11	05/25/2020	05/26/2020	05/26/2020	05/28/2020	06/22/2020	05/28/2020
DUP	EMS0125-MAY20	12	05/25/2020	05/26/2020	05/26/2020	05/28/2020	06/22/2020	05/28/2020

#### Metals in aqueous samples - ICP-OES

#### Method: MOE 4696e01/EPA 6010 | Internal ref.: ME-CA-[ENV]SPE-LAK-AN-003

BH3-SS4	ESG0071-MAY20	8	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020
BH3-SS6	ESG0071-MAY20	9	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020
BH4-SS5	ESG0071-MAY20	10	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020
BH4-SS8	ESG0071-MAY20	11	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020
DUP	ESG0071-MAY20	12	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020

#### Metals in Soil - Aqua-regia/ICP-MS

## Method: EPA 3050/EPA 200.8 | Internal ref.: ME-CA-[ENV]SPE-LAK-AN-005

BH3-SS4	EMS0125-MAY20	8	05/25/2020	05/26/2020	05/26/2020	05/28/2020	11/21/2020	05/28/2020
20200604			0 / 10					

20200601



#### HOLDING TIME SUMMARY

Sample Name	QC Batch Reference	Sample Number	Sampled	Received	Extracted/ Prepared	Analysed	Holding Time	Approved
Metals in Soil - Aqua-regia/IC	P-MS (continued)							
Method: EPA 3050/EPA 200.	8   Internal ref.: ME-CA-[ENV	/JSPE-LAK	<b>K-AN-005</b>					
BH3-SS6	EMS0125-MAY20	9	05/25/2020	05/26/2020	05/26/2020	05/28/2020	11/21/2020	05/28/2020
BH4-SS5	EMS0125-MAY20	10	05/25/2020	05/26/2020	05/26/2020	05/28/2020	11/21/2020	05/28/2020
BH4-SS8	EMS0125-MAY20	11	05/25/2020	05/26/2020	05/26/2020	05/28/2020	11/21/2020	05/28/2020
DUP	EMS0125-MAY20	12	05/25/2020	05/26/2020	05/26/2020	05/28/2020	11/21/2020	05/28/2020

#### Moisture

#### Method: CCME Tier 1 | Internal ref.: ME-CA-[ENV]GC-LAK-AN-010

BH3-SS4	GCM0362-MAY20	8	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/24/2020	05/28/2020
BH3-SS6	GCM0362-MAY20	9	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/24/2020	05/28/2020
BH4-SS5	GCM0362-MAY20	10	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/24/2020	05/28/2020
BH4-SS8	GCM0362-MAY20	11	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/24/2020	05/28/2020
DUP	GCM0362-MAY20	12	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/24/2020	05/28/2020

#### Petroleum Hydrocarbons (F1)

#### Method: CCME Tier 1 | Internal ref.: ME-CA-[ENV]GC-LAK-AN-010

BH3-SS4	GCM0397-MAY20	8	05/25/2020	05/26/2020	05/28/2020	05/29/2020	06/08/2020	06/01/2020
BH3-SS6	GCM0397-MAY20	9	05/25/2020	05/26/2020	05/28/2020	05/29/2020	06/08/2020	06/01/2020
BH4-SS5	GCM0397-MAY20	10	05/25/2020	05/26/2020	05/28/2020	05/29/2020	06/08/2020	06/01/2020
BH4-SS8	GCM0397-MAY20	11	05/25/2020	05/26/2020	05/28/2020	05/29/2020	06/08/2020	06/01/2020
DUP	GCM0397-MAY20	12	05/25/2020	05/26/2020	05/28/2020	05/29/2020	06/08/2020	06/01/2020

#### Petroleum Hydrocarbons (F2-F4)

#### Method: CCME Tier 1 | Internal ref.: ME-CA-[ENV]GC-LAK-AN-010

BH3-SS4	GCM0376-MAY20	8	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/04/2020	05/29/2020
BH3-SS6	GCM0376-MAY20	9	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/04/2020	05/29/2020
BH4-SS5	GCM0376-MAY20	10	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/04/2020	05/29/2020
BH4-SS8	GCM0376-MAY20	11	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/04/2020	05/29/2020
DUP	GCM0376-MAY20	12	05/25/2020	05/26/2020	05/28/2020	05/29/2020	07/04/2020	05/29/2020

#### pΗ

#### Method: SM 4500 | Internal ref.: ME-CA-[ENV]EWL-LAK-AN-001

BH3-SS4	ARD0077-MAY20	8	05/25/2020	05/26/2020	05/27/2020	05/27/2020	06/24/2020	05/28/2020
BH3-SS6	ARD0077-MAY20	9	05/25/2020	05/26/2020	05/27/2020	05/27/2020	06/24/2020	05/28/2020
BH4-SS5	ARD0077-MAY20	10	05/25/2020	05/26/2020	05/27/2020	05/27/2020	06/24/2020	05/28/2020
BH4-SS8	ARD0077-MAY20	11	05/25/2020	05/26/2020	05/27/2020	05/27/2020	06/24/2020	05/28/2020
DUP	ARD0077-MAY20	12	05/25/2020	05/26/2020	05/27/2020	05/27/2020	06/24/2020	05/28/2020

#### Sodium adsorption ratio (SAR)

### Method: MOE 4696e01/EPA 6010 | Internal ref.: ME-CA-[ENV]ARD-LAK-AN-021

BH3-SS4	ESG0071-MAY20	8	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020
BH3-SS6	ESG0071-MAY20	9	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020

20200601 9 / 18



#### HOLDING TIME SUMMARY

Sample Name	QC Batch Reference	Sample Number	Sampled	Received	Extracted/ Prepared	Analysed	Holding Time	Approved
Sodium adsorption ratio (SA	AR) (continued)							
Method: MOE 4696e01/EPA	A 6010   Internal ref.: ME-CA-[	ENV]ARD-	LAK-AN-021					
BH4-SS5	ESG0071-MAY20	10	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020
BH4-SS8	ESG0071-MAY20	11	05/25/2020	05/26/2020	05/28/2020	05/28/2020	11/21/2020	05/28/2020

05/25/2020

12

05/26/2020

05/28/2020

05/28/2020

11/21/2020

05/28/2020

#### **Volatile Organics**

DUP

#### Method: EPA 5035A/5030B/8260C | Internal ref.: ME-CA-[ENV]GC-LAK-AN-004

ESG0071-MAY20

BH3-SS4	GCM0397-MAY20	8	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/08/2020	06/01/2020
BH3-SS6	GCM0397-MAY20	9	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/08/2020	06/01/2020
BH4-SS5	GCM0397-MAY20	10	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/08/2020	06/01/2020
BH4-SS8	GCM0397-MAY20	11	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/08/2020	06/01/2020
DUP	GCM0397-MAY20	12	05/25/2020	05/26/2020	05/29/2020	05/29/2020	06/08/2020	06/01/2020

#### Water Soluble Boron

#### Method: O.Reg. 153/04 | Internal ref.: ME-CA-[ENV] SPE-LAK-AN-003

BH3-SS4	ESG0068-MAY20	8	05/25/2020	05/26/2020	05/27/2020	05/28/2020	11/21/2020	05/28/2020
BH3-SS6	ESG0068-MAY20	9	05/25/2020	05/26/2020	05/27/2020	05/28/2020	11/21/2020	05/28/2020
BH4-SS5	ESG0068-MAY20	10	05/25/2020	05/26/2020	05/27/2020	05/28/2020	11/21/2020	05/28/2020
BH4-SS8	ESG0068-MAY20	11	05/25/2020	05/26/2020	05/27/2020	05/28/2020	11/21/2020	05/28/2020
DUP	ESG0068-MAY20	12	05/25/2020	05/26/2020	05/27/2020	05/28/2020	11/21/2020	05/28/2020

20200601 10 / 18



#### QC SUMMARY

#### Conductivity

Method: EPA 6010/SM 2510 | Internal ref.: ME-CA-[ENV]EWL-LAK-AN-006

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank		M	atrix Spike / Ref	:
	Reference			Blank	Blank  RPD AC Spike  (%) Recovery				ery Limits %)	Spike Recovery	Recover	-
						(%)	Recovery (%)	Low	High	(%)	Low	High
Conductivity	EWL0447-MAY20	mS/cm	0.002	<0.002	0	10	99	90	110	NA		

#### Cyanide by SFA

Method: SM 4500 | Internal ref.: ME-CA-IENVISFA-LAK-AN-005

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank		M	atrix Spike / Ref	
	Reference			Blank RPD AC (%)	Spike		ry Limits %)	Spike Recovery	Recover	-		
				(%)	Recovery (%)	Low	High	(%)	Low	High		
Free Cyanide	SKA5129-MAY20	μg/g	0.05	<0.05	ND	20	94	80	120	85	75	125

#### **Hexavalent Chromium by SFA**

Method: FPA218 6/FPA3060A | Internal ref: MF-CA-IFNVISKA-I AK-AN-012

Parameter	QC batch	Units	DI	Mathad	D	-lianta	1.0	C/Cnilca Dianic			atrix Calles / Def	
T didniero	Reference	Units	RL	Method Blank	RPD	AC	Spike	S/Spike Blank Recover	•	Spike Recovery	atrix Spike / Ref Recovel	ry Limits
						(%)	Recovery (%)	Low	High	(%)	Low	High
Chromium VI	SKA5138-MAY20	ug/g	0.2	<0.2	ND	20	97	80	120	88	75	125

20200601 11 / 18



#### QC SUMMARY

Mercury by CVAAS

Method: EPA 7471A/EPA 245 | Internal ref.: ME-CA-[ENVISPE-LAK-AN-004

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank		M	atrix Spike / Ref	
	Reference			Blank RPD AC (%)	Spike		ery Limits %)	Spike Recovery	Recover	ry Limits %)		
				(%)	Recovery (%)	Low	High	(%)	Low	High		
Mercury	EMS0125-MAY20	μg/g	0.05	<0.05	ND	20	103	80	120	91	70	130

#### Metals in aqueous samples - ICP-OES

Method: MOE 4696e01/EPA 6010 | Internal ref.: ME-CA-IENVISPE-LAK-AN-003

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		М	atrix Spike / Ref	<u>.</u>
	Reference			Blank	Blank RPD	AC	Spike	Recove	•	Spike Recovery		ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
SAR Calcium	ESG0071-MAY20	mg/L	0.09	<0.09	1	20	101	80	120	95	70	130
SAR Magnesium	ESG0071-MAY20	mg/L	0.02	<0.02	2	20	99	80	120	97	70	130
SAR Sodium	ESG0071-MAY20	mg/L	0.15	<0.15	6	20	99	80	120	99	70	130

20200601 12 / 18



#### QC SUMMARY

Metals in Soil - Aqua-regia/ICP-MS

Method: EPA 3050/EPA 200.8 | Internal ref.: ME-CA-[ENV]SPE-LAK-AN-005

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		Ma	atrix Spike / Re	f.
	Reference			Blank	RPD	AC (%)	Spike Recovery		ry Limits %)	Spike Recovery		ery Limits %)
						(70)	(%)	Low	High	(%)	Low	High
Silver	EMS0125-MAY20	ug/g	0.05	<0.05	ND	20	102	70	130	108	70	130
Arsenic	EMS0125-MAY20	μg/g	0.5	<0.5	7	20	96	70	130	91	70	130
Barium	EMS0125-MAY20	ug/g	0.1	<0.1	4	20	107	70	130	96	70	130
Beryllium	EMS0125-MAY20	μg/g	0.02	<0.02	2	20	93	70	130	84	70	130
Boron	EMS0125-MAY20	μg/g	1	<1	0	20	105	70	130	92	70	130
Cadmium	EMS0125-MAY20	μg/g	0.02	<0.02	2	20	102	70	130	110	70	130
Cobalt	EMS0125-MAY20	μg/g	0.01	<0.01	3	20	101	70	130	112	70	130
Chromium	EMS0125-MAY20	μg/g	0.5	<0.5	1	20	102	70	130	115	70	130
Copper	EMS0125-MAY20	μg/g	0.1	<0.1	1	20	105	70	130	114	70	130
Molybdenum	EMS0125-MAY20	μg/g	0.1	<0.1	6	20	95	70	130	107	70	130
Nickel	EMS0125-MAY20	ug/g	0.5	<0.5	0	20	102	70	130	115	70	130
Lead	EMS0125-MAY20	μg/g	0.1	<0.1	1	20	101	70	130	97	70	130
Antimony	EMS0125-MAY20	μg/g	0.8	<0.8	ND	20	92	70	130	111	70	130
Selenium	EMS0125-MAY20	μg/g	0.7	<0.7	ND	20	100	70	130	104	70	130
Thallium	EMS0125-MAY20	μg/g	0.02	<0.02	11	20	102	70	130	99	70	130
Uranium	EMS0125-MAY20	μg/g	0.002	<0.002	6	20	98	70	130	90	70	130
Vanadium	EMS0125-MAY20	μg/g	3	<3	2	20	101	70	130	106	70	130
Zinc	EMS0125-MAY20	μg/g	0.7	<0.7	0	20	99	70	130	104	70	130

20200601 13 / 18



#### QC SUMMARY

Petroleum Hydrocarbons (F1)

Method: CCME Tier 1 | Internal ref.: ME-CA-[ENVIGC-LAK-AN-010

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank		M	atrix Spike / Ref	
	Reference			Blank	RPD	AC	Spike		ry Limits %)	Spike Recovery	Recover	ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
F1 (C6-C10)	GCM0397-MAY20	μg/g	10	<10	ND	30	94	80	120	101	60	140

#### Petroleum Hydrocarbons (F2-F4)

Method: CCME Tier 1 | Internal ref.: ME-CA-IENVIGC-LAK-AN-010

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		M	atrix Spike / Ref	
	Reference			Blank	RPD	AC	Spike	Recove	•	Spike Recovery		ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
F2 (C10-C16)	GCM0376-MAY20	μg/g	10	<10	ND	30	117	80	120	126	60	140
F3 (C16-C34)	GCM0376-MAY20	μg/g	50	<50	ND	30	117	80	120	126	60	140
F4 (C34-C50)	GCM0376-MAY20	μg/g	50	<50	ND	30	117	80	120	126	60	140

20200601 14 / 18



#### QC SUMMARY

pН

Method: SM 4500 | Internal ref.: ME-CA-[ENV]EWL-LAK-AN-001

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank		М	atrix Spike / Ref	
	Reference			Blank	RPD	RPD AC (%)	Spike		ry Limits %)	Spike Recovery	Recover	•
						(%)	Recovery (%)	Low	High	(%)	Low	High
рН	ARD0077-MAY20	pH Units	0.05		0	20	100	80	120			

#### **Volatile Organics**

Method: EPA 5035A/5030B/8260C | Internal ref.: ME-CA-IENVIGC-LAK-AN-004

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		Ma	atrix Spike / Ref	
	Reference			Blank	RPD AC (%)	Spike	Recover	•	Spike Recovery		ry Limits %)	
							Recovery (%)	Low	High	(%)	Low	High
Benzene	GCM0397-MAY20	μg/g	0.02	<0.02	ND	50	90	60	130	94	50	140
Ethylbenzene	GCM0397-MAY20	μg/g	0.05	<0.05	ND	50	87	60	130	95	50	140
m/p-xylene	GCM0397-MAY20	μg/g	0.05	<0.05	ND	50	88	60	130	97	50	140
o-xylene	GCM0397-MAY20	μg/g	0.05	<0.05	ND	50	86	60	130	96	50	140
Toluene	GCM0397-MAY20	μg/g	0.05	<0.05	ND	50	86	60	130	94	50	140

20200601 15 / 18



#### **QC SUMMARY**

Water Soluble Boron

Method: O.Reg. 153/04 | Internal ref.: ME-CA-IENVI SPE-LAK-AN-003

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank		M	latrix Spike / Ref	
	Reference	Blank	RPD	AC	Spike		ry Limits %)	Spike Recovery	Recover	ry Limits %)		
						(%)	Recovery (%)	Low	High	(%)	Low	High
Water Soluble Boron	ESG0068-MAY20	μg/g	0.5	<0.5	ND	20	103	80	120	112	70	130

Method Blank: a blank matrix that is carried through the entire analytical procedure. Used to assess laboratory contamination.

Duplicate: Paired analysis of a separate portion of the same sample that is carried through the entire analytical procedure. Used to evaluate measurement precision.

LCS/Spike Blank: Laboratory control sample or spike blank refer to a blank matrix to which a known amount of analyte has been added. Used to evaluate analyte recovery and laboratory accuracy without sample matrix effects.

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate laboratory accuracy with sample matrix effects.

Reference Material: a material or substance matrix matched to the samples that contains a known amount of the analyte of interest. A reference material may be used in place of a matrix spike.

RL: Reporting limit

RPD: Relative percent difference

AC: Acceptance criteria

Multielement Scan Qualifier: as the number of analytes in a scan increases, so does the chance of a limit exceedance by random chance as opposed to a real method problem. Thus, in multielement scans, for the LCS and matrix spike, up to 10% of the analytes may exceed the quoted limits by up to 10% absolute and the spike is considered acceptable.

**Duplicate Qualifier**: for duplicates as the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the average of the two duplicates is greater than five times the RL. **Matrix Spike Qualifier**: for matrix spikes, as the concentration of the native analyte increases, the uncertainty of the matrix spike recovery increases. Thus, the matrix spike acceptance limits apply only when the concentration of the matrix spike is greater than or equal to the concentration of the native analyte.

20200601 16 / 18



#### **LEGEND**

#### **FOOTNOTES**

NSS Insufficient sample for analysis.

RL Reporting Limit.

- † Reporting limit raised.
- ↓ Reporting limit lowered.
- NA The sample was not analysed for this analyte
- ND Non Detect

Samples analysed as received. Solid samples expressed on a dry weight basis. "Temperature Upon Receipt" is representative of the whole shipment and may not reflect the temperature of individual samples.

Analysis conducted on samples submitted pursuant to or as part of Reg. 153/04, are in accordance to the Protocol for Analytical Methods Used in the Assessment of Properties under Part XV.1 of the Environmental Protection Act" published by the Ministry and dated March 9, 2004 as amended.

SGS provides criteria information (such as regulatory or guideline limits and summary of limit exceedances) as a service. Every attempt is made to ensure the criteria information in this report is accurate and current, however, it is not guaranteed. Comparison to the most current criteria is the responsibility of the client and SGS assumes no responsibility for the accuracy of the criteria levels indicated. This document is issued, on the Client's behalf, by the Company under its General Conditions of Service available on request and accessible at http://www.sgs.com/terms\_and\_conditions.htm. The Client's attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any other holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

This report must not be reproduced, except in full. This report supersedes all previous versions.

-- End of Analytical Report --

20200601 17 / 18

# Request for Laboratory Services and CHAIN OF CUSTODY

Request for Laboratory Services and CHAIN OF CUST(
Environment, Health & Safety - Lakefield: 185 Concession St., Lakefield, ON KOL 2H0 Phone: 705-652-2000 Fax: 705-652-6365 Web: www.sgs.com/environment

3

	- Edildoir oor conso	ומעווו כסטון, בטוו	don, ON, Not	200 FRORE.	FIIOHE, 519-6/2-4500 TOIL FREE: 6//-648-8060 Fax: 519-6/2-0361	11-848-8060 F	-8x: 519-0	12-0301								Page of
Backwad By N. MUMICYK		Received By (signature)	natura):	Tabor.	aboratory Information Section - Lab use only	ection - La	b use o	nly			2			0	A-14	A. HANK MAPEO
Received Date: 05 /26 /20 (mm/dd/yy) Received Time: 14 : CO (hr : min)		Custody Seal Present: Custody Seal Intact:	act: Yes	2 8	Cooling Ag	Cooling Agent Present: Yes		Nº S	J\vec{y}	Se ICENAC	N. V.	7		LAB LIMS #:	#	**
REPORT INFORMATION	NN	INVOICE INFORMATION	MATION													
company Grounded Eng	X (same as Report Information)	ort Informatio	n)		Quotation #:							P.O.	#		-	
Contact: Jessic WU	Company:				20-	880						Site	Site Location/ID:25	25 Elizab	petr	St. N. Missie
Address: 12 Veriger Ur.	Contact:								TURN	AROUN	DTIME	(TAT) R	TURNAROUND TIME (TAT) REQUIRED			
Torono, UN MAH 1E9	Address:				Regular TAT (5-7days)	(5-7days)						TAT's a	re quoted in	business days (exc	lude statutor	TAT's are quoted in business days (exclude statutory holidays & weekends).
7-264-FO	Addieso.			3		Charges N	fav Appl			Dav	202	oampie	1 Day 2 Days 3 Days 4 Days	Dave	cends: IAI o	Samples received after opin or on weekends. (A) begins next business day
	Phone:				PLEASE CONFIRM RUSH FEASIBILITY WITH SGS REPRESENTATIVE PRIOR TO SUBMISSION	USH FEASIE	BILITY W	TH SGS	REPR	ESENT.	ATIVE F	PRIOR TO	SUBMIS	SION		
Email Lung on of ord odog committee	Email:				Specify Due Date:				NOTE:	DRINKIN	G (POTA	BLE) WAT	ER SAMPLI	WITH SGS DRINKING WATER CHAIN OF CUSTODY	ONSUMPTIC	NOTE: DRINKING (POTABLE) WATER SAMPLES FOR HUMAN CONSUMPTION MUST BE SUBMITTED WITH SGS DRINKING WATER CHAIN OF CHISTODY
4	REGULATIONS						<b>A</b>	NAI YSIS REQUESTED	212	200	123	CB.				
		The second second		-		COURS	3.0	200					Common and	On the last of the	1	TOTAL DESCRIPTION OF THE PERSON OF THE PERSO
n 153/04:	Other Regulations:	S:	Sewer By-Law:	y-Law:	M&I	SVOC	PCB	PHC		VOC	Pest	-	Other (pl	(please specify)	TCLP	
Table 2 Ind/Com Coarse	□ Pwqo □	PWGO MMER	Storm	orm										Pkg	Specify	
		Other:	Municipality:	īţ:	lg, CrVI	, NI,	clor [								-	
RECORD OF SITE CONDITION (RSC)	XYES   NO	0			gani /s),EC. lite	U,P'0,W	Are				y other				Exte	COMMENTS:
SAMPLE IDENTIFICATION	DATE	TIME SAMPLED B	#OF	MATRIX	Field Filtered ( Metals & Inor incl. CrVI, CN, Hg pH, (B(H (CI, Na-water))  Full Metals S ICP metals plus B(HWS-6 ICP Metals on SS,As,Ba,Bo,B,Cd,Cr,Co, Se,Ag,Ti,U,Y,Zn	PAHs only SVOCs	PCBs Total	F1-F4 + BTEX	F1-F4 only no BTEX VOCS all incl BTEX	BTEX only	Pesticides Organochlorine or spec			Sewer Use: Specify pkg: Water Charac	General Decarding Decardin	
1 BH3-884	May 25,20	nak	7	n	X			MODESCON, N								
2 11 556				_						18						
S 55 - HMA &																
8 55 11	~	<	~		_											
5 000	6	<	<	<	<			<								
6			15													
7																
00																
9	and the second															
10										4						
11			N. Same D.										7.			
12										15						
Observations/Comments/Special Instructions	N. N.	All Indian	Market St.	1												
Sampled By (NAME): SCHO!		Si	Signature:	1	1					Date:	N.	8	w	(mm/dd/yy)		Pink Copy - Client
Relinquished by (NAME):	ON	Si	Signature:		1					Date:	1-19 N	25	20	(mm/dd/yy)	-	Yellow & White Copy - SGS

Date of Issue: 09 Sept, 2019 ion #: 1.2

Note: Submission of samples to SGS is acknowledgement that you have been provided direction on sample collection/handling and transportation of samples to SGS is considered authorization for completion of work. Signatures may appear on this form or be retained on file in the contract, or in an alternative format (e.g. shipping documents). (3) Results may be sent by email to an unlimited number of addresses for no additional cost. Fax is available upon request. This document is issued by the Company under its General Conditions of Service accessible at http://www.sgs.com/terms\_and\_conditions.htm. (Printed copies are available upon request.) Attention is drawn to the limitation of liability, indernification and jurisdiction issues defined therein.







CA14917-MAY20 R

20-088-101 Mississagua

Prepared for

**Grounded Engineering Inc.** 



#### First Page

CLIENT DETAIL	S	LABORATORY DETAIL	LS
Client	Grounded Engineering Inc.	Project Specialist	Brad Moore Hon. B.Sc
		Laboratory	SGS Canada Inc.
Address	12 Banigan Drive, Toronto	Address	185 Concession St., Lakefield ON, K0L 2H0
	Canada, M4H1E9		
	Phone: 647-264-7909. Fax:		
Contact	Jessie Wu	Telephone	705-652-2143
Telephone	647-264-7909	Facsimile	705-652-6365
Facsimile		Email	brad.moore@sgs.com
Email	jwu@groundedeng.ca	SGS Reference	CA14917-MAY20
Project	20-088-101 Mississagua	Received	05/26/2020
Order Number		Approved	06/01/2020
Samples	Leachate (1)	Report Number	CA14917-MAY20 R
		Date Reported	06/01/2020

#### COMMENTS

Temperature of Sample upon Receipt: 5 degrees C

Cooling Agent Present:Yes Custody Seal Present:Yes

Chain of Custody Number:012652

TCLP metals reported at 10x DL

Raise RL for NO2/NO3 due to matrix interference

#### SIGNATORIES

Brad Moore Hon. B.Sc Brad Mod

SGS Canada Inc. 185 Concession St., Lakefield ON, K0L 2H0 t 705-652-2143 f 705-652-6365

> Member of the SGS Group (SGS SA) 1 / 15

www.sgs.com



#### **TABLE OF CONTENTS**

First Page	1
Index	
Results	
Exceedance Summary	
QC Summary	
Legend	14
Annexes	15



L1 = REG558 / LEACHATE / - - SCHEDULE 4 - -

L1 = REG558 / LEACHATE / - - SCHEDULE 4 - -

# **FINAL REPORT**

#### CA14917-MAY20 R

Client: Grounded Engineering Inc.

Project: 20-088-101 Mississagua

Project Manager: Jessie Wu

Samplers: Jason Ngo

PACKAGE: REG558 - Acid rock Drainage

Sample Number

6

(LEACHATE)

Parameter

Sample Name

Sample Matrix

TCLP Leachate

Sample Date

L1

25/05/2020

Result

**Acid rock Drainage** 

Final pH 0.01 no unit

Units

RL

PACKAGE: REG558 - Metals and Inorganics

(LEACHATE)

Sample Number

TCLP

6.08

6

Sample Name

Sample Matrix

Leachate

Sample Date

25/05/2020

RL L1 Units Parameter Result

Metals and Inorganics

motalo ana morganico					
Sample weight	g	0.001		100	
Ext Fluid	#1 or #2	0.01		2	
^ Ext Volume	mL	0.01		2000	
Nitrite (as N)	as N mg/L	0.03		< 0.3↑	
Nitrate (as N)	as N mg/L	0.06		< 0.6↑	
Nitrate + Nitrite (as N)	as N mg/L	0.06	1000	< 0.6↑	
Fluoride	mg/L	0.06	150	0.26	
Cyanide (total)	mg/L	0.01	20	< 0.01	
Arsenic	mg/L	0.0002	2.5	0.0027	
Silver	mg/L	0.00005	5	< 0.00005	
Barium	mg/L	0.00002	100	0.425	
Boron	mg/L	0.002	500	0.077	



#### CA14917-MAY20 R

**Client:** Grounded Engineering Inc.

Project: 20-088-101 Mississagua

Project Manager: Jessie Wu

Samplers: Jason Ngo

PACKAGE: <b>REG558 - Metals and Inorganic</b>	e		Sample Number	6
PACKAGE: <b>REG556 - Metals and Inorganic</b> (LEACHATE)	3		campio i alliboi	Č
LEAGRATE)			Sample Name	TCLP
			Sample Matrix	Leachate
_1 = REG558 / LEACHATE / SCHEDULE 4			Sample Matrix	25/05/2020
Description	11-4-			
Parameter	Units	RL	L1	Result
Metals and Inorganics (continued)		ı		
Cadmium	mg/L	0.00000	0.5	0.000630
		3		
Chromium	mg/L	0.00008	5	0.00175
Lead	mg/L	0.00001	5	0.00236
Selenium	mg/L	0.00004	1	0.00022
Uranium	mg/L	0.00000	10	0.00345
		2		
			Sample Number	6
PACKAGE: <b>REG558 - Other (ORP)</b> (LEACH	IAIE)		Sample Number	O
			Sample Name	TCLP
.1 = REG558 / LEACHATE / SCHEDULE 4			Sample Matrix	Leachate
.1 = REG558 / LEACHATE / SCHEDULE 4			Sample Matrix Sample Date	
.1 = REG558 / LEACHATE / SCHEDULE 4 Parameter	Units	RL	Sample Matrix	Leachate
Parameter Other (ORP)	Units	RL	Sample Matrix Sample Date	Leachate 25/05/2020
Parameter	<b>Units</b>	<b>RL</b> 0.00001	Sample Matrix Sample Date	Leachate 25/05/2020
Parameter Other (ORP)			Sample Matrix Sample Date L1 0.1	Leachate 25/05/2020  Result < 0.00001
Parameter Other (ORP)  Mercury			Sample Matrix Sample Date	Leachate 25/05/2020 Result
Parameter Other (ORP)  Mercury			Sample Matrix Sample Date L1 0.1	Leachate 25/05/2020  Result < 0.00001
Parameter Other (ORP)  Mercury  PACKAGE: REG558 - PCBs (LEACHATE)			Sample Matrix Sample Date L1  0.1  Sample Number	Leachate 25/05/2020  Result < 0.00001
Parameter Other (ORP)			Sample Matrix Sample Date L1  0.1  Sample Number Sample Name	Leachate 25/05/2020  Result   < 0.00001  6  TCLP
Parameter Other (ORP)  Mercury  PACKAGE: REG558 - PCBs (LEACHATE)			Sample Matrix Sample Date L1  0.1  Sample Number Sample Name Sample Matrix	Leachate 25/05/2020  Result  < 0.00001  6  TCLP  Leachate
Parameter Other (ORP)  Mercury  PACKAGE: REG558 - PCBs (LEACHATE)  1 = REG558 / LEACHATE / SCHEDULE 4	mg/L	0.00001	Sample Matrix Sample Date L1  0.1  Sample Number Sample Name Sample Matrix Sample Date	Leachate 25/05/2020  Result  < 0.00001  6  TCLP  Leachate 25/05/2020
Parameter Other (ORP) Mercury PACKAGE: REG558 - PCBs (LEACHATE)  1 = REG558 / LEACHATE / SCHEDULE 4 Parameter	mg/L	0.00001	Sample Matrix Sample Date L1  0.1  Sample Number Sample Name Sample Matrix Sample Date	Leachate 25/05/2020  Result  < 0.00001  6  TCLP  Leachate 25/05/2020



#### CA14917-MAY20 R

Client: Grounded Engineering Inc.

Project: 20-088-101 Mississagua

Project Manager: Jessie Wu

Samplers: Jason Ngo

CHATE)		Sample Number	6
		Sample Name	TCLP
		Sample Matrix	Leachate
		Sample Date	25/05/2020
Units	RL	L1	Result
mg/L	0.001	0.001	< 0.001
		Sample Number	6
		Sample Name	TCLP
		Sample Matrix	Leachate
		Sample Date	25/05/2020
Units	RL	L1	Result
ma/l	0.8	200	< 0.8
			< 0.008
			< 0.02
			< 0.02
			< 0.02
		5	
			< 0.02
mg/L			< 0.02
mg/L	0.008	0.5	< 0.008
mg/L	0.02	20	< 0.02
mg/L	0.02	0.5	< 0.02
			< 0.02
mg/L	0.02	0.5	<b>~</b> 0.02
	Units  mg/L   Units         RL           mg/L         0.001           Units         RL           mg/L         0.8           mg/L         0.02           mg/L         0.008           mg/L         0.002	Sample Name   Sample Matrix   Sample Date	



Benzene

# **FINAL REPORT**

#### CA14917-MAY20 R

**Client:** Grounded Engineering Inc.

Project: 20-088-101 Mississagua

Project Manager: Jessie Wu

Samplers: Jason Ngo

PACKAGE: <b>REG558 - VOCs - BTEX</b> (	(LEACHATE)		Sample Number	6		
			Sample Name	TCLP		
L1 = REG558 / LEACHATE / SCHEDULE 4			Sample Matrix	Leachate		
			Sample Date	25/05/2020		
Parameter	Units	RL	L1	Result		
VOCs - BTEX						

< 0.02

0.02

mg/L

0.5



#### **EXCEEDANCE SUMMARY**

No exceedances are present above the regulatory limit(s) indicated

20200601 7 / 15



#### QC SUMMARY

Anions by IC

Method: EPA300/MA300-lons1.3 | Internal ref.: ME-CA-[ENV]IC-LAK-AN-001

Parameter	QC batch	Units	RL	Method	Duj	olicate	LC	S/Spike Blank		м	atrix Spike / Ref	
	Reference			Blank	RPD	AC	Spike	Recove	ry Limits %)	Spike Recovery		ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
Nitrate + Nitrite (as N)	DIO0496-MAY20	mg/L	0.06	<0.06	NA		NA			NA		
Nitrite (as N)	DIO0496-MAY20	mg/L	0.03	<0.03	ND	20	95	80	120	98	75	125
Nitrate (as N)	DIO0496-MAY20	mg/L	0.06	<0.06	0	20	100	80	120	104	75	125

#### Cyanide by SFA

Method: SM 4500 | Internal ref.: ME-CA-IENVISFA-LAK-AN-005

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		М	atrix Spike / Ref	
	Reference			Blank	RPD	AC	Spike Recovery		ry Limits %)	Spike Recovery	Recove	ry Limits 6)
						(%)	(%)	Low	High	(%)	Low	High
Cyanide (total)	SKA0238-MAY20	mg/L	0.01	<0.01	ND	10	99	90	110	88	75	125

20200601 8 / 15



#### QC SUMMARY

Fluoride by Specific Ion Electrode

Method: SM 4500 | Internal ref.: ME-CA-[ENV]EWL-LAK-AN-014

Parameter	QC batch	Units	RL	Method	Duj	plicate	LC	S/Spike Blank		M	atrix Spike / Ref	·
	Reference			Blank	RPD	AC	Spike		ery Limits %)	Spike Recovery	Recover	ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
Fluoride	EWL0444-MAY20	mg/L	0.06	<0.06	ND	10	103	90	110	102	75	125

#### Inorganics-General

Method: EPA 7471A/SM 3112B | Internal ref.: ME-CA-[ENV]SPE-LAK-AN-004

Parameter	QC batch	Units	RL	Method	Dup	olicate	LC	S/Spike Blank		М	atrix Spike / Re	f.
	Reference			Blank	RPD	AC (W)	Spike		ry Limits %)	Spike Recovery		ry Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
Mercury	EHG0026-MAY20	mg/L	0.00001	< 0.00001	ND	20	119	80	120	116	70	130

20200601 9 / 15



#### QC SUMMARY

Metals in aqueous samples - ICP-MS

Method: SM 3030/EPA 200.8 | Internal ref.: ME-CA-[ENVISPE-LAK-AN-006

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		Ma	atrix Spike / Re	i.
	Reference			Blank	RPD	AC	Spike	Recover	•	Spike Recovery		ory Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
Silver	EMS0137-MAY20	mg/L	0.00005	<0.00005	ND	20	99	90	110	98	70	130
Arsenic	EMS0137-MAY20	mg/L	0.0002	<0.0002	4	20	99	90	110	107	70	130
Barium	EMS0137-MAY20	mg/L	0.00002	<0.00002	2	20	103	90	110	NV	70	130
Boron	EMS0137-MAY20	mg/L	0.002	<0.002	5	20	99	90	110	99	70	130
Cadmium	EMS0137-MAY20	mg/L	0.000003	<0.000003	ND	20	99	90	110	96	70	130
Chromium	EMS0137-MAY20	mg/L	0.00008	<0.00008	18	20	99	90	110	112	70	130
Lead	EMS0137-MAY20	mg/L	0.00001	<0.00001	7	20	102	90	110	110	70	130
Selenium	EMS0137-MAY20	mg/L	0.00004	<0.00004	ND	20	101	90	110	110	70	130
Uranium	EMS0137-MAY20	mg/L	0.000002	<0.000002	0	20	102	90	110	116	70	130

#### **Polychlorinated Biphenyls**

Method: MOE E3400/EPA 8082A | Internal ref.: ME-CA-IENVIGC-LAK-AN-001

Parameter	QC batch	Units	RL	Method	Du	plicate	LC	S/Spike Blank		м	atrix Spike / Re	ī.
	Reference			Blank	RPD	AC	Spike	Recove	•	Spike Recovery		ery Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
Polychlorinated Biphenyls (PCBs) -	GCM0390-MAY20	mg/L	0.001	< 0.001	ND	30	96	60	140	109	60	140
Total												

20200601 10 / 15



#### QC SUMMARY

Semi-Volatile Organics

Method: EPA 3510C/8270D | Internal ref.: ME-CA-IENVIGC-LAK-AN-005

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		М	atrix Spike / Ref	
	Reference			Blank	RPD	AC (V)	Spike	Recove	•	Spike Recovery	Recover	•
						(%)	Recovery (%)	Low	High	(%)	Low	High
Benzo(a)pyrene	GCM0381-MAY20	mg/L	0.001	< 0.001	NSS	30	89	50	140	NSS	50	140

20200601 11 / 15



#### QC SUMMARY

#### Volatile Organics

Method: EPA 5030B/8260C | Internal ref.: ME-CA-[ENV]GC-LAK-AN-004

Parameter	QC batch	Units	RL	Method	Dup	licate	LC	S/Spike Blank		Ma	atrix Spike / Re	f.
	Reference			Blank	RPD	AC	Spike	Recover	•	Spike Recovery		ory Limits %)
						(%)	Recovery (%)	Low	High	(%)	Low	High
1,1-Dichloroethylene	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	99	60	130	96	50	140
1,2-Dichlorobenzene	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	105	60	130	106	50	140
1,2-Dichloroethane	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	97	60	130	100	50	140
1,4-Dichlorobenzene	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	105	60	130	104	50	140
Benzene	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	101	60	130	100	50	140
Carbon tetrachloride	GCM0411-MAY20	mg/L	0.008	<0.008	ND	30	102	60	130	98	50	140
Chloroform	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	102	60	130	101	50	140
Dichloromethane	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	98	60	130	99	50	140
Methyl ethyl ketone	GCM0411-MAY20	mg/L	0.8	<0.8	ND	30	100	50	140	110	50	140
Monochlorobenzene	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	105	60	130	103	50	140
Tetrachloroethene	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	105	60	130	102	50	140
Trichloroethylene	GCM0411-MAY20	mg/L	0.02	<0.02	ND	30	103	60	130	101	50	140
Vinyl Chloride	GCM0411-MAY20	mg/L	0.008	<0.008	ND	30	93	50	140	90	50	140

20200601 12 / 15



#### **QC SUMMARY**

Method Blank: a blank matrix that is carried through the entire analytical procedure. Used to assess laboratory contamination.

Duplicate: Paired analysis of a separate portion of the same sample that is carried through the entire analytical procedure. Used to evaluate measurement precision.

LCS/Spike Blank: Laboratory control sample or spike blank refer to a blank matrix to which a known amount of analyte has been added. Used to evaluate analyte recovery and laboratory accuracy without sample matrix effects.

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate laboratory accuracy with sample matrix effects.

Reference Material: a material or substance matrix matched to the samples that contains a known amount of the analyte of interest. A reference material may be used in place of a matrix spike.

RL: Reporting limit

RPD: Relative percent difference

AC: Acceptance criteria

Multielement Scan Qualifier: as the number of analytes in a scan increases, so does the chance of a limit exceedance by random chance as opposed to a real method problem. Thus, in multielement scans, for the LCS and matrix spike, up to 10% of the analytes may exceed the quoted limits by up to 10% absolute and the spike is considered acceptable.

**Duplicate Qualifier**: for duplicates as the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the average of the two duplicates is greater than five times the RL. **Matrix Spike Qualifier**: for matrix spikes, as the concentration of the native analyte increases, the uncertainty of the matrix spike recovery increases. Thus, the matrix spike acceptance limits apply only when the concentration of the matrix spike is greater than or equal to the concentration of the native analyte.

20200601 13 / 15



#### **LEGEND**

#### **FOOTNOTES**

NSS Insufficient sample for analysis.

RL Reporting Limit.

- † Reporting limit raised.
- ↓ Reporting limit lowered.
- NA The sample was not analysed for this analyte
- ND Non Detect

Samples analysed as received. Solid samples expressed on a dry weight basis. "Temperature Upon Receipt" is representative of the whole shipment and may not reflect the temperature of individual samples.

Analysis conducted on samples submitted pursuant to or as part of Reg. 153/04, are in accordance to the Protocol for Analytical Methods Used in the Assessment of Properties under Part XV.1 of the Environmental Protection Act" published by the Ministry and dated March 9, 2004 as amended.

SGS provides criteria information (such as regulatory or guideline limits and summary of limit exceedances) as a service. Every attempt is made to ensure the criteria information in this report is accurate and current, however, it is not guaranteed. Comparison to the most current criteria is the responsibility of the client and SGS assumes no responsibility for the accuracy of the criteria levels indicated. This document is issued, on the Client's behalf, by the Company under its General Conditions of Service available on request and accessible at http://www.sgs.com/terms\_and\_conditions.htm. The Client's attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any other holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

This report must not be reproduced, except in full. This report supersedes all previous versions.

-- End of Analytical Report --

20200601 14 / 15



# Request for Laboratory Services and CHAIN OF CUSTODY

Page\_ No: 012652

of

Environment, Health & Safety - Lakefield: 185 Concession St., Lakefield, ON K0L 2H0 Phone: 705-652-2000 Fax: 705-652-6365 Web: www.sgs.com/environment - London: 657 Consortium Court, London, ON, N6E 2S8 Phone: 519-672-4500 Toll Free: 877-848-8060 Fax: 519-672-0361

Date: 26 (mm/dd/yy) Yellow & White Copy - SGS of samples to SGS is considered by place of the in-	Yello ar on this form	(yy) res may appe	(mm/dd	De Police	or complete	3	20 S	ate:	D SGS is	samples t	ssion of s	2) Submi	amples. (	tation of s	transpor	andling an	llection/h	organization on sample collection/handling and transportation	provided direct	you have been	cnowledgement that	bignature of samples to SGS is acknowledgement that you have been provided dispetion on sample collection/handling and transportation of the contract, or in an alternative format (a.g. shipoing documents). (3.l. Beauting Systems are the contract or in an alternative format (a.g. shipoing documents).	ote: S	Revision #: 1.2 Date of Issue: 09 Sept, 2019	Revis Date o
Pink Copy - Client	Pink	(46)	(mm/dd/yy)		120	25	200	Date:	D					1		1	1	1	orginature.			J. P. A.	AME: COC-	Relinquished by (NAME):	Re
						1	0		-	1					1	1			Cianatana			750	2000	Sampled By (NAME):	San
			-	-			-	-			-	ľ										155	Observations/Comments/Special Instructions	ervations/Comm	Obs
																									12
						-												Line And Service				2 1 1 1 2	W. To B.		11
																							Sakas A Sakas		10
																									9
						18																			00
The following																1						10 To	Was beautiful		7
															-			18.0				87		1 mg/m	6
			+																						Oi
																34		N.							4
THE PERSON NAMED IN									5																ω
																					0		200	The division of	N
	4	1				^	7	100										S	2)		SPENSENCE	0	P	100	
	Opcs Observed Opcs Observed Opcs		Sewer Use:	S. 17.	17-17-1	TCLP	Pesticides Organochlorine or specify	BTEX only	VOCs all incl BTEX	F1-F4 only	F1-F4 + BTEX	PCBs Total	PAHs only SVOCs	ICP Metals only Sb,As,Ba,Be,B,Cd,Cr,Co,Cl Se,Ag,Tl,U,V,Zn	Full Metals Su ICP metals plus B(HWS-so ICP Metals control	Metals & Inorginal CrVI, CN, Hg pH, (B(HW) (CI, Na-water)	Field Filtered (	MATRIX	# OF BOTTLES	TIME	DATE	N N	SAMPLE IDENTIFICATION	SAME	
COMMENTS.		Exten					other					Arc		J,Pb,M	il only)	gani S),EC,	(/N)			NO	YES   N	DITION (RSC)	RECORD OF SITE CONDITION (RSC)	RECO	
	Specify TCLP tests	tion Pkg		235								clor		o,Ni,		CS SAR-soll)		Sanitary Storm Municipality:	11.1	(3 Day min TA MMER Other:	Reg 347/558 (3 Day min TAT)  PWQO MMER  CCME Other:	Soil Texture:	☐ Res/Park So☐ Ind/Com☐ Agri/Other	Table 1 Table 2 Table 3 Table	0000
	TCLP		se specify)	Other (please	Othe	1	Pest	VOC	٧٥	PHC		PCB	SVOC		- 80	×		Sewer By-Law:	Sew	S:	Other Regulations:	Ot		Regulation 153/04:	R
						TED	NALYSIS REQUESTED	EQI	IS R	LYS	ANA										TIONS	REGULATIONS			100
NOTE: DRINKING (POTABLE) WATER SAMPLES FOR HUMAN CONSUMPTION MUST BE SUBMITTED WITH SGS DRINKING WATER CHAIN OF CUSTODY	STODY N	BLE) WATER SAMPLES FOR HUMAN CONSUMPTION WITH SGS DRINKING WATER CHAIN OF CUSTODY	FOR HIL ATER C	KING W	GS DRIN	ABLE) W	G (POT/	RINKING	TE: DF	NO					Date:	Specify Due Date	Spec				Email:	e	onaparde de la	Email: Juvul	m
			DN	MISSIG	PLEASE CONFIRM RUSH FEASIBILITY WITH SGS REPRESENTATIVE PRIOR TO SUBMISSION	PRIOR	ATIVE	SENT/	EPRESENT	SGS R	WITH :	BILITY	FEASI	RUSH	NFIRM	PLEASE CONFIRM RUSH FEASIBILITY WITH	PLE				Phone:	Ph			Fax:
TAT's are quoted in business days (exclude statutory holidays & weekends). Samples received after 6pm or on weekends: TAT begins next business day	statutory hos: TAT begin	ays (exclude on weekend	r 6pm or	ted in bu	s are quo ples recei	Sam							days)	Regular TAT (5-7days)	gular T	TAT Re	0				Address:	909	264 7	Phone: 647	무ㅣ
				RED	TURNAROUND TIME (TAT) REQUIRED	E (TAT)	DTIM	ROUN	URNA	1											Contact:	5	BONISAND	Address: 1	A
E	155 gw	Niss.	-	on/ID:	Site Location/ID:	Si					-	0)-1	280	0-0	2	Project #:	Proj				Company:	000	NM 21S	Contact: Jes	Q
		TOTAL STREET	-	The second	, O	0	-	-	-	2000000	-	- Common	00000000	-	-	Quotation #:	Quo	-	ation)	port Informa	(same as Report Information)	meeling	Granded Engl	Company: Or	0
		CINIO T.							1										ORMATION	INVOICE INFORMATION	N	N	REPORT INFORMATION	REI	888
tertibhi-t	A-1	ABING *				160ACK	10	TE	V. JABO	1		Yes Y	resent:	Cooling Agent Present: Yes C	Cooling		7	N	9	Received By (signature) Custody Seal Present: Custody Seal Intact:	1	(hr:min)	1 36 8	Received Date: Received Time:	R R R
											only	rap use	ection - L	Dac I	Handi	A HILLOI	Dilaro	July				~	MINA	7	

# **APPENDIX F**





# PHASE TWO CONCEPTUAL SITE MODEL

#### PREPARED FOR:

Edenshaw Elizabeth Developments Limited 129 Lakeshore Rd. E., Suite 201, 2nd Floor Mississauga, ON L5G 1E5

#### **ATTENTION:**

Mr. Steven Soldano

23 Elizabeth St. N., 42, 44 & 46 Park St. E. | Mississauga, Ontario

**Grounded Engineering Inc.** 

**File No.** 20-088 (Rev.1)

**Issued** July 31, 2020



# **TABLE OF CONTENTS**

		ODUCTION	1
	1.1	SITE DESCRIPTION	1
	1.2	PROPERTY OWNERSHIP	1
	1.3	SUMMARY OF PREVIOUS INVESTIGATIONS	2
2	INFC	RMATION FROM THE PHASE ONE ENVIRONMENTAL SITE ASSESSMENT	2
	2.1	AREAS WHERE POTENTIAL CONTAMINATING ACTIVITY HAS OCCURRED	2
	2.2	AREAS OF POTENTIAL ENVIRONMENTAL CONCERN	
	2.3	SUBSURFACE STRUCTURES AND UTILITIES	
3	PHY	SICAL SETTING OF THE PHASE TWO PROPERTY	6
	3.1	STRATIGRAPHY	6
		3.1.1 Geological Unit Thickness	6
		3.1.2 Elevations of Geological Units	
		3.1.3 Material in Geological Units	
	3.2	APPROXIMATE DEPTH TO WATER TABLE	
	3.3	SITE HYDROGEOLOGICAL CHARACTERISTICS	
	3.4	APPROXIMATE DEPTH TO BEDROCK	
	3.5	SECTION 41 OR 43.1	
	3.6	Soils Placed On, In or Under the Phase Two Property	9
	3.7	PROPOSED BUILDINGS	9
4	CON	TAMINATION IN OR UNDER THE PHASE TWO PROPERTY	
	4.1	APPLICABLE SITE CONDITION STANDARD	9
	4.2	MEDIA INVESTIGATED	10
	4.3	SAMPLING RATIONALE AND AREAS WHERE CONTAMINANTS ARE PRESENT	10
		4.3.1 Location and Depth of Soil Samples	11
		4.3.2 Location and Depth of Ground Water Samples	
	4.4	EXEMPTION OF SALT-RELATED EXCEEDANCES (O.REG. 49.1 (1))	
	4.5	CONTAMINANTS ASSOCIATED WITH EACH AREA	40
	4.6	MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED	
	4.6 4.7		12
		MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED	12 12
	4.7	MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED	12 12 12
	4.7 4.8	MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED	12 12 12 12
	4.7 4.8 4.9	MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED  INFORMATION KNOWN ABOUT EACH CONTAMINATED AREA  DISTRIBUTION OF CONTAMINANT  REASONS FOR DISCHARGE OF CONTAMINANT	12 12 12 12
	4.7 4.8 4.9 4.10	MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED  INFORMATION KNOWN ABOUT EACH CONTAMINATED AREA  DISTRIBUTION OF CONTAMINANT  REASONS FOR DISCHARGE OF CONTAMINANT  MIGRATION OF CONTAMINANT	12 12 12 12
	4.7 4.8 4.9 4.10 4.11	MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED INFORMATION KNOWN ABOUT EACH CONTAMINATED AREA DISTRIBUTION OF CONTAMINANT REASONS FOR DISCHARGE OF CONTAMINANT MIGRATION OF CONTAMINANT CLIMATIC OR METEOROLOGICAL INFLUENCES ON MIGRATION	12 12 12 13
	4.7 4.8 4.9 4.10 4.11 4.12	MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED INFORMATION KNOWN ABOUT EACH CONTAMINATED AREA DISTRIBUTION OF CONTAMINANT REASONS FOR DISCHARGE OF CONTAMINANT MIGRATION OF CONTAMINANT CLIMATIC OR METEOROLOGICAL INFLUENCES ON MIGRATION SOIL VAPOUR INTRUSION INTO BUILDINGS	12 12 12 13 13
	4.7 4.8 4.9 4.10 4.11 4.12 4.13	MEDIUM IN WHICH CONTAMINANTS ARE ASSOCIATED INFORMATION KNOWN ABOUT EACH CONTAMINATED AREA DISTRIBUTION OF CONTAMINANT REASONS FOR DISCHARGE OF CONTAMINANT MIGRATION OF CONTAMINANT CLIMATIC OR METEOROLOGICAL INFLUENCES ON MIGRATION SOIL VAPOUR INTRUSION INTO BUILDINGS RELEVANT CONSTRUCTION FEATURES OF BUILDINGS	12 12 12 13 13



5.1	DESCRIPTION OF ALL COMPONENTS	15
5.2	RECEPTOR HUMAN HEALTH	16
5.3	RECEPTOR TERRESTRIAL ENVIRONMENT	16
5.4	RECEPTOR AQUATIC ENVIRONMENT	17
5.5	SUMMARY OF POTENTIAL RECEPTOR RISKS	17

# **TABLES**

Table 1 - Water Levels

# **FIGURES**

- Figure 1 Site Location
- Figure 2 PCA and APEC Locations
- Figure 3 Borehole and Monitoring Well Locations
- Figure 4 Groundwater Elevations and Contours
- Figure 5 Cross Section Locations
- Figure 6 Cross Section A-A'
- Figure 7 Cross Section B-B'
- Figure 8 Human Health Conceptual Site Model
- Figure 9 Ecological Conceptual Site Model



# 1 Introduction

# 1.1 Site Description

Edenshaw Elizabeth Developments Limited retained Grounded Engineering Inc. to complete a Phase Two Environmental Site Assessment (ESA) of the property located northwest of the intersection of Elizabeth St. N., and Park St. E., Mississauga, Ontario (Property). The Phase Two ESA has been prepared for purpose of due diligence/financing and for filing a Record of Site Condition (RSC). The site location is presented in Figure 1.

The Property is rectangular in shape, with a total area of 0.18 ha. The Property is bounded by Elizabeth St. N. to the northwest and Park St. E. to the southeast. The Property is currently developed with four (4) residential dwellings each with a basement. The Property is considered to be residential land use by the Ontario Ministry of the Environment, Conservation, and Parks (MECP). The Phase Two ESA has been prepared for purpose of due diligence/financing and for filing a Record of Site Condition (RSC). The Phase Two ESA is prepared in accordance with Ontario Regulation 153/04 (O.Reg. 153/04).

# 1.2 Property Ownership

The Property information is provided below:

Municipal Address	<ul> <li>23 Elizabeth Street North Mississauga</li> <li>42 Park Street East Mississauga</li> <li>44 Park Street East Mississauga</li> <li>46 Park Street East Mississauga</li> </ul>
Legal Description	Plan 300-E Pt Lot 8 Plan 300-E Pt Lot 8 RP 43R2685 Part 1,2,3 and 4
PIN(s)	<ul> <li>13463-0092 (LT)</li> <li>13463-0001(LT)</li> <li>13463-0002(LT)</li> <li>13463-0003(LT)</li> </ul>
Current Land Use Residential	
Property Owner Information	<ul> <li>Leslie Calhoun</li> <li>Tara Prouty and Patrick Alleguede</li> <li>Margaret-Anne Murphy</li> <li>Edenshaw Elizabeth Developments Limited</li> </ul>



Person who has engaged the Qualified Person to conduct the Phase One ESA Edenshaw Elizabeth Developments Limited 129 Lakeshore Rd. E., Suite 201, 2nd Floor Mississauga, ON L5G 1E5

# 1.3 Summary of Previous Investigations

The following environmental report was provided for review for the Property. The findings of the report are summarized below:

#### Report 1

Title and File No.	Phase One Environmental Site Assessment, 23 Elizabeth St. N., 44, 42 & 46 Park St. E., Mississauga, Ontario. File No. 20-088	
Report Date	May 8, 2020	
Prepared By	Grounded Engineering Inc.	
Prepared for	Edenshaw Elizabeth Developments Limited	
Description of Data,	•	
Analysis or	- Mary Fix Creek located approximately 150 m to the west of the Property.	
Findings	<ul> <li>Potentially contaminating activities (PCAs) were found on sites located with the Study Area but not on the Phase One Property.</li> </ul>	
	- No Area of Potential Environmental Concern (APEC) were identified on the Property.	
	- A Phase Two ESA will not be required prior to the submission of a Record of Site	
	Condition (RSC). An RSC can be submitted based on the Phase One ESA alone.	

The PCAs and APEC locations are provided in Figure 2.

# 2 Information from the Phase One Environmental Site Assessment

# 2.1 Areas Where Potential Contaminating Activity Has Occurred

Potential Contaminating Activity (PCAs) were identified in the Phase One ESA for the Property. No on-site PCAs were identified by the Phase One ESA. The information regarding whether the PCAs have the potential to cause Areas of Potential Environmental Concerns (APECs) is provided below.



Location of PCA	PCA	APEC (Yes/No)	Rationalization
28 Elizabeth St. N. 20 m South	#01 - Ontario Spill	No	The CoC associated with the spill is minimal in quantity. The PCA is also located downgradient to the Property. The QP does not think this PCA will cause an APEC on the Property
28 Helene St. N. 45 m Northeast	#02 – O.Reg. 347 Waste Generator	No	The waste generator onsite is likely for small scale usage. The QP does not think this PCA will cause an APEC on the Property.
80 m Northwest	#46 – Rail Yards, Tracks and Spurs	No	The CoCs associated with the railway spurs are soil related and are unlikely to migrate into and through the groundwater table. The QP does not think this PCA will cause an APEC on the Property.
30 Queen St. E. 95 m North	#03 – Coal Storage	No	The CoCs associated with the coal storage are soil related and are unlikely to migrate into and through the groundwater table. The QP does not think this PCA will cause an APEC on the Property.
12 Park St. E. 130 m Southwest	#18 – Electricity Generation, Transformation and Power Stations	No	Downgradient PCA. Due to the distance and gradient from the Property, groundwater impacts, if present, are unlikely to cause contamination on the Property. The QP does not think this PCA will cause an APEC on the Property.
26 Stavebank Rd. 180 m South	#18 – Electricity Generation, Transformation and Power Stations	No	Downgradient PCA. Due to the distance and gradient from the Property, groundwater impacts, if present, are unlikely to cause contamination on the Property. The QP does not think this PCA will cause an APEC on the Property.
15 Stavebank Rd. 190 m Southeast	#18 – Electricity Generation, Transformation and Power Stations	No	Downgradient PCA. Due to the distance and gradient from the Property, groundwater impacts, if present, are unlikely to cause contamination on the Property. The QP does not think this PCA will cause an APEC on the Property.
Hurontario St. and Queen St. E. 200 m Northeast	#59 – Wood Treating and Preservative Facility and Bulk Storage of Treated and Preserved Wood Products	No	Due to the distance from the Property, groundwater impacts, if present, are unlikely to cause contamination on the Property. The QP does not think this PCA will cause an APEC on the Property.
10 Ann St. 215 m East	#10- Commercial Autobody Shops	No	Due to the distance from the Property, groundwater impacts, if present, are unlikely to cause contamination on the Property. The QP does not think this PCA will cause an APEC on the Property.



Location of PCA	PCA	APEC (Yes/No)	Rationalization
40 Stavebank Rd. 230 m Southwest	#02 – O.Reg. 347 Waste Generator	No	Downgradient PCA. Due to the distance and gradient from the Property, groundwater impacts, if present, are unlikely to cause contamination on the Property. The QP does not think this PCA will cause an APEC on the Property.
30 Stavebank Rd. 240 m Southeast	#18 – Electricity Generation, Transformation and Power Stations	No	Downgradient PCA. Due to the distance and gradient from the Property, groundwater impacts, if present, are unlikely to cause contamination on the Property. The QP does not think this PCA will cause an APEC on the Property.
88 High St. E. 250 m Northeast	#28 – Gasoline and Associated Products Storage in Fixed Tanks	No	Downgradient PCA. Due to the distance and gradient from the Property, groundwater impacts, if present, are unlikely to cause contamination on the Property. The QP does not think this PCA will cause an APEC on the Property.

The locations of the PCAs and APECs are shown on Figure 2. No APECs were identified for the Property.



#### 2.2 Areas of Potential Environmental Concern

No APECs resulting from PCAs were identified for the Property. The results are shown on Figure 2.

#### 2.3 Subsurface Structures and Utilities

The site inspection of the Property and utility locates conducted as part of the Phase One ESA found the following information regarding utilities and services at the Property:

- Underground water service enters the Property via Elizabeth Street North to the south and Park Street East to the east
- Underground gas utility enters the Property via Elizabeth Street North to the south and Park Street East to the east
- Hydro lines are overhead

It is possible that the bedding materials for the underground utilities could serve as preferential pathways for the migration of PCoCs. The subsurface utilities may contribute to migration of contaminants, if detected on site.



# 3 Physical Setting of the Phase Two Property

# 3.1 Stratigraphy

Detailed geological information for the Property is presented on the geologic cross sections shown in Figures 6 and 7. The geology at the Property is summarized below.

#### 3.1.1 Geological Unit Thickness

Geological Unit Thickness (Estimate)		
Borehole	BH1 to BH4 Thickness Range (m)	
Earth Fill	0.8 to 1.5	
Silt and Sand	3.0 to 7.6	
Silty Clay (Glacial Till)	4.6 to 7.6	
Sandy Silt (Glacial Till)	7.6 to 10.4	
Bedrock	8.6 to at least 23.2	

#### 3.1.2 Elevations of Geological Units

Geological Unit Elevations			
Borehole	BH1 to BH4		
Boreliole	Elev. Top Range (masl)	Elev. Bottom Range (masl)	
Earth Fill	83.4	80.3	
Silt and Sand	82.7	75.9	
Silty Clay (Glacial Till)	78.2	75.3	
Sandy Silt (Glacial Till)	76.6	72.9	
Bedrock	74.2	58	



#### 3.1.3 Material in Geological Units

Geological Units	Description
Earth Fill	Underlying the surficial materials, the boreholes observed a layer of earth fill that extends to depths of 0.8 to 1.1 metres below grade (Elev. 82.7 to 80.3 metres). The earth fill varies in composition but generally consists of silty sand, with trace gravel and trace rootlets. The earth fill is typically dark brown to brown, and moist.
Silt and Sand	Native Silt and Sandwas encountered in all borehole locations underlying the Earth Fill. The Native Silty Sand unit extends down to depths of 3.0 to 7.6 m below grade (Elev. 75.9 to 78.2 m). The silty sand unit contains trace gravel and trace clay.
Glacial Till	Underlying the silt and sand unit, all the boreholes encountered an undisturbed native glacial till deposit. The upper portion of the till has a matrix of cohesive silty clay (encountered in all but Borehole 3). The till transitions to a cohesive sandy silt till. The till was encountered at 3.0 to 6.1 metres below grade (Elev. 76.8 to 78.2 m).  The upper cohesive till is generally grey, and moist to wet. The upper till contains trace to some gravel and trace sand. The lower cohesionless sandy silt till is generally grey, and moist to wet. This layer contains some clay and some gravel.
Bedrock	The top of inferred bedrock was encountered at depths ranging from 7.6 to 10.4 m in all boreholes across the site (Elev. 72.9 to 74.2± m). Boreholes 2 to 4 inferred the top of weathered bedrock through auger cuttings, split spoon samples, and auger grinding/resistance observations. Boreholes 2 to 4 were terminated due to auger and sampler refusal (at target investigation depth) at elevations ranging from Elev. 72.8 to 73.8 m. Borehole 1 recovered rock core from Elev. 71.0 to 58.0 m.  The bedrock beneath the site is the Georgian Bay Formation ("GBF"), which broadly comprises thin to medium bedded grey shale and limestone of Ordovician age. The shale is interbedded with calcareous shale, limestone, dolostone, and calcareous sandstone (conventionally grouped together as "limestone") which are typically laterally discontinuous.

# 3.2 Approximate Depth to Water Table

Five (5) ground water level measurements were conducted in June and July by Grounded Engineering Inc. in the newly installed monitoring wells using a Solinst interface probe on the following dates:

- June 5, 2020
- June 10, 2020
- June 12, 2020
- June 18, 2020
- July 20, 2020

A total of four (4) monitoring wells have been installed by Grounded Engineering Inc. The ground water levels are presented in Table 1 and Figure 4. The shallowest ground water depth was measured at 2.9 mbgs (80.5 masl) and was observed at Borehole 4 located at the north end of the site on June 5, 2020.

Based on the groundwater elevations measured on the Property, the groundwater was determined to flow locally to the south. Regional groundwater flow is expected to flow to the south towards



Credit River then east towards Lake Ontario. Groundwater elevations are provided on Table 1. The groundwater flow direction and contour are present in Figure 4.

To calculate the ground water elevation in the monitoring well, the following calculation was completed:

Geodetic Ground Elevation (masl) – Measured Depth to Water Table (m) + Stick up of Well (m) = Ground Water Elevation (masl)

Based on the current groundwater levels, the groundwater within the aquifer is encountered at an elevation of approximately 76.4 to 80.5 masl. Groundwater is also observed within the bedrock at 68.5 masl.

## 3.3 Site Hydrogeological Characteristics

Horizontal Hydraulic Gradients	The horizontal hydraulic gradient at the Property was determined to be approximately 0.1 m/m.		
Vertical Hydraulic	The vertical hydraulic gradient at the Property was determined to be approximately 0.3		
Gradients	m/m downwards.		
	■ Earth Fill 1 x 10 <sup>-6</sup> m/s		
Hydraulic	<ul> <li>Silty Sand 1 x 10<sup>-7</sup> m/s</li> </ul>		
Conductivity	<ul> <li>Silty Clay (Glacial Till) 3.1 x 10-8 m/s</li> </ul>		
	<ul> <li>Sandy Silt (Glacial Till) 9.39 x 10<sup>-8</sup> m/s</li> </ul>		

# 3.4 Approximate Depth to Bedrock

The bedrock at the Property is of the Georgian Bay Formation, which is comprised of shale, limestone, dolostone and siltstone. The top of inferred bedrock was encountered at depths ranging from 7.6 to 10.4 m in all boreholes across the site (Elev. 72.9 to 74.2± m). Boreholes 2 to 4 indirectly inferred the top of weathered bedrock through auger cuttings, split spoon samples, and auger grinding/resistance observations. Boreholes 2 to 4 were terminated due to auger and sampler refusal (at target investigation depth) at elevations ranging from Elev. 72.8 to 73.8 m. Borehole 1 recovered rock core from Elev. 71.0 to 58.0 m.

#### 3.5 Section 41 or 43.1

Section 41 of the Regulation does <u>not</u> apply to the Phase Two Property based on the following rationale:

- The Property is not located within an area of natural significance;
- The Property does not include or is not adjacent to an area of natural significance or part of such an area;
- The Property does not include land that is within 30 m of an area of natural significance or part of such an area;



- The surface soil at the Property has a pH value that is not less than 5 or greater than 9;
   and
- The sub-surface soil at the Property has a pH value that is not less than 5 or greater than 11.

Section 43.1 of the Regulation does <u>not</u> apply to the Phase Two Property based on the following rationale:

- The Property is not considered a shallow soil property; or
- The Property does not include all or part of a water body and is not adjacent to a water body and does not include land that is within 30 m of a water body.

#### 3.6 Soils Placed On, In or Under the Phase Two Property

No soils have been imported or place on, in or under the Phase Two Property since the site reconnaissance completed for the Phase One ESA in May 6, 2020.

## 3.7 Proposed Buildings

It is understood that the Phase Two Property will be developed with redeveloped with a 22-storey high rise residential building and a P6-underground parking. As part of the future development, a 13 m<sup>2</sup> triangular parcel along the intersection of Elizabeth Street North and Park Street East will be conveyed to the City of Mississauga as proposed road-widening

# 4 Contamination In or Under the Phase Two Property

# 4.1 Applicable Site Condition Standard

The applicable site condition standard for the Phase Two Property is determined to be Table 3 Site Condition Standard for Residential/Parkland/Institutional in non-potable groundwater condition for coarse textured soil due to the following reason:

Current Land Use	Residential Land Use
Future Land Use	Residential Land Use
Soil Texture	Coarse
Potable Water Source	Lake Ontario
Bedrock Depth	Bedrock is located at a depth of greater than 2 m.
Property located within 30 m of a surface water body (Yes/No)	No



Property located in or adjacent to a provincial park or an Area of Natural Significance (Yes/No)	No
---	----

Grounded Engineering Inc. notified the Peel Region Clerk of the intention to use non-potable groundwater standards. No objections have been received on July 17, 2020 to the use of non-potable groundwater standards.

# 4.2 Media Investigated

The scope of the Phase Two ESA is as follow:

Boreholes and Monitoring Wells	<ul> <li>Advancing of 4 boreholes to depths of 8.6 to 23.2 m below ground surface (mbgs)</li> <li>Installation of 4 of monitoring wells</li> </ul>		
Parameters Investigated for Soil	<ul> <li>Metals</li> <li>Hydride-forming Metals         <ul> <li>Antimony (Sb), Arsenic (As), Selenium (Se)</li> </ul> </li> <li>Selected Other Regulated Parameters (ORPs)         <ul> <li>Electrical Conductivity (EC), Sodium Adsorption Ratio (SAR), Boron-hot water soluble (B-HWS), Cyanide (CN-), Mercury (Hg), Hexavalent Chromium (Cr(VI)), low or high pH</li> </ul> </li> <li>Petroleum Hydrocarbons (PHCs)</li> <li>Volatile Organic Compounds II (BTEX)</li> </ul>		
Parameters Investigated for Groundwater	<ul> <li>Metals</li> <li>Hydride-forming Metals         <ul> <li>Antimony (Sb), Arsenic (As), Selenium (Se)</li> </ul> </li> <li>Selected Other Regulated Parameters (ORPs)         <ul> <li>Cyanide (CN-), Sodium (Na), Chloride (Cl), Mercury (Hg), Hexavalent Chromium (Cr(VI))</li> </ul> </li> <li>Petroleum Hydrocarbons (PHCs)</li> <li>Volatile Organic Compounds II (BTEX)</li> </ul>		

- 3 soil samples were submitted for grain size analysis and soil classification
- All boreholes and monitoring wells are surveyed to a geodetic benchmark
- All monitoring wells are developed and sampled
- Groundwater level measurements are conducted in all monitoring wells to determine groundwater elevation on the Property

# 4.3 Sampling Rationale and Areas Where Contaminants are Present

Based on the Phase One ESA, no APECs were identified on the Property. Soil and groundwater sampling were conducted for due diligence/refinancing purpose. No exceedances were identified in the soil and the groundwater on the Property.



#### 4.3.1 Location and Depth of Soil Samples

Sample	De	pth	Ctroto	Metals	U Motolo	ORPs	DUC <sub>O</sub> /DTEV
ID	mbgs	masl	Strata	Metals	H-Metals	URPS	PHCs/BTEX
BH1 SS2	0.8 - 1.4	80.4-79.8	Silty Sand	√	√	√	√
BH1 SS3	1.5 - 2.1	79.7-79.1	Silty Sand	√	√	√	
BH1 SS5	3.0 - 3.7	78.1-77.5	Glacial Till				√
BH2 SS2	0.8 - 1.2	80.6-80.2	Fill	√	√	√	√
BH2 SS4	2.3 - 2.9	79.1-78.5	Silty Sand	√	√	√	√
BH3 SS4	2.3 - 2.6	81.2-80.9	Silty Sand	√	√	√	√
BH3 SS6	4.6 - 4.8	78.9-78.7	Silty Sand	√	√	√	√
BH4 SS5	3.0 - 3.5	80.3-79.8	Silty Sand	√	√	√	√
BH4 SS8	7.6 - 8.1	75.7-75.3	Glacial Till	√	√	√	√

#### 4.3.2 Location and Depth of Ground Water Samples

Sample ID	Screen Depth		Screen Strata	Metals	H-Metals	ORPs	PHCs/BTEX	
Sample ID	mbgs	masl	Screen Strata	wetais	n-ivietais	UKPS	PHOS/DIEX	
BH1	20.1-23.2	61.0-58.0	Bedrock	√	√	√	√	
BH2	5.5-8.5	75.9-72.9	Glacial Till	√	√	√	√	
внз	5.6-8.7	77.8-74.8	Silty Sand to Glacial Till	√	√	√	√	
ВН4	5.6-8.7	77.7-74.7	Silty Sand to Glacial Till	√	√	√	√	

# 4.4 Exemption of Salt-Related Exceedances (O.Reg. 49.1 (1))

Chemical analysis of the groundwater indicates that there are exceedances of the MECP Table 3 Standards for Electrical Conductivity (salt related compound) within the upper soils.

The Property is located at the corner of two municipal roadways (Elizabeth Street North and Park Street East). The roadways have public sidewalks between the road and the Property boundary. The Property features a driveway and car parking. The roadways, sidewalks, driveway, and parking area are all salted during the winter months for safety purposes.

The Qualified Person has determined, based on the Phase One Environmental Site Assessment and the Phase Two Environmental Site Assessment, that a substance (salt) has been applied to surfaces of the roadway, sidewalks, driveway and parking area for the safety of vehicular and pedestrian traffic under conditions of snow or ice or both.



The applicable site condition standard is exceeded at the Property solely because of the reason as stated above (application of salt for safety purposes during winter months). As per O.Reg. 153/04 49.1 the applicable site condition standard is deemed not to be exceeded for the purpose of Part XV.1 of the Act.

#### 4.5 Contaminants Associated with Each Area

No Areas of Potential Concerns (APECs) were identified on the Property.

#### 4.6 Medium in Which Contaminants are Associated

Soil and groundwater were investigated as part of the Phase Two ESA investigation. No CoCs were identified in the following media for the contaminants listed.

Metals	H-Metals	ORPs	PHCs/BTEX
Soil – None	Soil – None	Soil – None	Soil – None
Groundwater - None	Groundwater - None	Groundwater - None	Groundwater - None

Based on the Phase Two investigation, there are no CoCs above the MECP Table 3 RPI Standards identified on the Property.

#### 4.7 Information Known about Each Contaminated Area

No contaminants were identified in the soil and groundwater on the Property. All the samples met the Table 3 RPI Standard.

#### 4.8 Distribution of Contaminant

No contaminants were identified in the soil and groundwater during the investigation. The cross sections of the Property are presented on Figures 6 and 7.

# 4.9 Reasons for Discharge of Contaminant

No contaminants were identified in the soil and ground water during the investigation. The cross sections of the Property are presented on Figure 6 and 7.

# 4.10 Migration of Contaminant

No contaminants were identified on the Property. As such, there is no migration associated with contaminant on the Property.



# 4.11 Climatic or Meteorological Influences on Migration

No contaminants were identified on the Property. As such, there is no climatic or meteorological influences on migration on the Property.

# 4.12 Soil Vapour Intrusion into Buildings

No contaminants were identified in the ground water during the investigation. As such there is no soil vapour intrusion into buildings.

# 4.13 Relevant Construction Features of Buildings

The Property is currently occupied by four (4) 2-storey residential buildings each with a basement and associated asphaltic surficial parking area/driveway. The buildings were built in 1928. Observations on the interior of the building were not available due to access restriction during the pandemic.

#	Address	Above Grade Levels	Below Grade Levels	Use	Entry/Exits
1	23 Elizabeth St. N.	2 level	1 basement level	Residential	Southside and eastside of the building
2	42 Park St. E.	2 level + Attic	1 basement level	Residential	Eastside and westside of the building
3	44 Park St. E.	2 level	1 basement level	Residential	Eastside and westside of the building
4	46 Park St. E.	2 level	1 basement level	Residential	Eastside, southside and westside of the building.

Walls	Interior not accessed for all buildings.
Floors	Interior not accessed for all buildings.
Ceilings	Interior not accessed for all buildings.



Lighting	Interior not accessed for all buildings.
Exterior	#1 – wood panels
	#2 & #3 - brick
	#4 – brick and wood panels
Roof (if accessed)	Shingles
Heating and Cooling System	Exterior floor mount/ wall mount AC units
Drains, Pits, Sumps Observed	Interior not accessed for all buildings.
Staining and Corrosion	N/A
Air Emissions	Chimneys observed at all buildings.

## 4.14 Building HVAC

Currently HVAC systems present in the building on the Property will not affect the distribution and transport of contaminants because no volatile CoCs were identified.

#### 4.15 Subsurface Structures and Utilities

The site inspection of the Property and utility locates conducted as part of the Phase One ESA found the following information regarding utilities and services at the Property:

- Underground water service enters the Property via Elizabeth Street North to the south and Park Street East to the east
- Underground gas utility enters the Property via Elizabeth Street North to the south and Park Street East to the east
- · Hydro lines are overhead

It is possible that the bedding materials for the underground utilities could serve as preferential pathways for the migration of PCoCs. The subsurface utilities may contribute to migration of contaminants, if detected on site.



# **5 Potential Exposures Pathways and Receptors**

# **5.1** Description of All Components

A list of all risk-based components of potential exposure pathways and receptors are presented below and presented on Figures 8 and 9.

Potential Pathway	Description
GW1	Ground water for drinking water purposes
GW2	Ground water for protection from movement to indoor air
GW3	Ground water for protection of aquatic life
S1	Soil for protection of a residential receptor from direct contact with surface soil
S2	Soil for protection from direct soil contact for a lower frequency and intensity exposure than residential surface soil, such as commercial or industrial scenarios
S3	Soil for direct soil contact for a low-frequency, high-intensity, human health exposure scenario without children present that is protective of a worker digging in the soil
S-IA	Soil for protection of movement to indoor air and human exposure
S-OA	Soil for protection of movement to outdoor air and human exposure
S-Odour	Soil for protection of movement to outdoor air and human exposure
S-GW1	Soil for protection from movement to ground water for drinking water purposes
S-GW3	Soil for protection from movement to ground water and then to aquatic life
Plants and Soil Organisms	Soil for protection against adverse effects to plants and soil dwelling organisms
Mammals and Birds	Soil for protection against adverse effects through direct soil and food ingestion to mammals and birds



# 5.2 Receptor Human Health

Potential		CoCs from Phase	Potential Risks (Yes/No)			
Pathway	Sources	Two ESA	Source	Pathway	Receptor	Risk
GW1	Contamination not present in ground water	None	No	Yes	Yes	No Risk
GW2	Contamination not present in ground water	None	No	Yes	Yes	No Risk
GW3	Contamination not present in ground water	None	No	Yes	No	No Risk
S1	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk
S2	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk
S3	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk
S-IA	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk
S-OA	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk
S-Odour	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk
S-GW1	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk
S-GW3	Contamination not present in fill material and native soils	None	No	Yes	No	No Risk

# 5.3 Receptor Terrestrial Environment

Potential	Caurage	CoCs from Phase	Potential Risks (Yes/No)				
Pathway	Sources	Two ESA	Source	Pathway	Receptor	Risk	
Plants and Soil Organisms	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk	
Mammals and Birds	Contamination not present in fill material and native soils	None	No	Yes	Yes	No Risk	



# **5.4** Receptor Aquatic Environment

Potential	Courses	CoCs from Phase	Potential Risks (Yes/No)				
Pathway	Sources	Two ESA	Source	Pathway	Receptor	Risk	
GW3	Contamination not present in fill material and native soils	None	No	Yes	No	No Risk	
S-GW3	Contamination not present in fill material and native soils	None	No	Yes	No	No Risk	

# 5.5 Summary of Potential Receptor Risks

No Contaminants of Concern were identified during the Phase Two ESA investigation. There is no potential risk associated with the Human Receptor, the Terrestrial or the Aquatic Environment.

# **TABLES**



Table 1: GROUNDWATER ELEVATION 23 Elizabeth St. N.


Consultant	Monitoring Well ID	05-Jun-20	10-Jun-20	12-Jun-20	18-Jun-20	20-Jul-20
Consultant		<b>GW Elevation (masl)</b>	<b>GW Elevation (masl)</b>	<b>GW Elevation (masl)</b>	<b>GW Elevation (masl)</b>	GW Elevation (masl)
	BH1	76.3	73.4	68.4	68.5	68.6
Grounded	BH2	76.4	76.4	76.5	76.5	76.7
Engineering	BH3	80.2	79.7	79.4	79.8	79.5
	BH4	80.5	80.4	80.4	80.3	79.9


NA – Monitoring wells could not be located or monitored

NM – Not Measured

# **FIGURES**











1 Banigan Drive, Toronto, Ont., M4H1G3 www.groundedeng.ca

#### LEGEND

PROPERTY BOUNDARY



GROUNDED BOREHOLE WITH



O/H OVERHEAD HYDRO





CATCH BASIN

SANITARY SEWER



CONVEYANCE LAND

Survey Drawing No. 3296-0T.DWG Project No. 3296-0 Certificate date: July 23, 2019. Prepared by

R. Avis Surveying Inc. Received on July 3, 2020 as part of the ROWE package prepared by IBI Group Architects

#### PHASE TWO **ENVIRONMENTAL SITE ASSESSMENT**

23 ELIZABETH ST. N., 42, 44, 46 PARK ST. E., MISSISSAUGA ONTARIO, L5G 2Z4

#### **BOREHOLE AND** MONITORING WELL **LOCATIONS**




JULY 2020

1:200

20-088

FIGURE 3





1 Banigan Drive, Toronto, Ont., M4H1G3 www.groundedeng.ca

#### LEGEND

PROPERTY BOUNDARY



GROUNDED BOREHOLE WITH



O/H OVERHEAD HYDRO



CATCH BASIN







GROUNDWATER ELEVATION JUNE 18, 2020 80.3



GROUNDWATER FLOW DIRECTION

Note

#### Reference

Survey Drawing No. 3296-0T.DWG Project No. 3296-0 Certificate date: July 23, 2019. Prepared by

R. Avis Surveying Inc. Received on July 3, 2020 as part of the ROWE package prepared by IBI Group Architects

#### Project PHASE TWO **ENVIRONMENTAL SITE ASSESSMENT**

23 ELIZABETH ST. N., 42, 44, 46 PARK ST. E., MISSISSAUGA ONTARIO, L5G 2Z4

#### **GROUNDWATER ELEVATION AND CONTOURS**



Date

JULY 2020

Scale


1:200

Job No

20-088

Figure No

FIGURE 4





1 Banigan Drive, Toronto, Ont., M4H1G3 www.groundedeng.ca

## LEGEND

PROPERTY BOUNDARY



GROUNDED BOREHOLE WITH

—— GAS — GAS

O/H OVERHEAD HYDRO



CATCH BASIN



SANITARY SEWER



CONVEYANCE LAND

#### Reference

Survey Drawing No. 3296-0T.DWG Project No. 3296-0 Certificate date: July 23, 2019. Prepared by

R. Avis Surveying Inc. Received on July 3, 2020 as part of the ROWE package prepared by IBI Group Architects

#### PHASE TWO **ENVIRONMENTAL SITE ASSESSMENT**

23 ELIZABETH ST. N., 42, 44, 46 PARK ST. E., MISSISSAUGA ONTARIO, L5G 2Z4

Figure Title

#### **CROSS - SECTION** LOCATIONS



JULY 2020

Scale

1:200

Job No

20-088

Figure No

FIGURE 5

