



1970 & 1980 Fowler Drive, Mississauga, Ontario

Proposed Residential Development

Type of Document:

Geotechnical investigation

Client Name:

IMH 1970 & 1980 Fowler Drive Ltd.

Project Number:

BRM-22022660-B0

Submitted By:

EXP Services Inc.
1595 Clark Boulevard
Brampton, ON L6T 4V1
t: +1.905.793.9800
f: +1.905.793.0641

Date Submitted:

November 5, 2025 (Revision 2)

Table of Contents

1. Introduction.....	1
2. Site Description and Regional Geology	2
3. Investigation Procedures.....	3
4. Subsurface Conditions.....	4
4.1 Subsoil Conditions.....	4
4.2 Groundwater Conditions	6
5. Geotechnical Recommandations	8
5.1 Foundation Considerations.....	8
5.2 Foundations - General	8
5.3 Excavation and Groundwater Control	9
5.4 Temporary Shoring	10
5.5 Basement Wall.....	12
5.6 Floor Slab Construction and Permanent Drainage	13
5.7 Earthquake Considerations.....	13
5.8 Potential for Sulphate Attack.....	14
6. General Comments.....	15

DRAWINGS

- Drawing 1: Borehole Location Plan
- Drawing 1A: Notes on Sample Descriptions
- Drawings 2 to 11: Borehole Logs
- Drawings 12 and 13: Drainage Drawings

APPENDICES

- Appendix A: Rock Lab Testing Results
- Appendix B: Rock Core Photographic
- Appendix C: Certificates of Analyses

1. Introduction

This report presents the findings of a geotechnical investigation carried out for the proposed residential development located at 1970 & 1980 Fowler Drive, Mississauga, Ontario.

It is understood that the proposed site will be developed to a high-rise development consisting of a 24-storey building with four (4) levels of underground parking and associated parking area and access road. The detailed design of the proposed development was provided for our review and preparing this report.

Our Terms of Reference also included hydrogeological investigation and Phase One Environmental Site Assessment (ESA) for the Site. The findings of these assessments will be reported under separate covers.

The purpose of this investigation was to obtain information on the subsurface conditions at the site by drilling ten (10) boreholes, located within the footprint of the proposed development and based on an assessment of the factual borehole data, to provide geotechnical engineering guidelines for the design and construction of the proposed residential development.

The comments and recommendations given in this report are based on the assumption the above-described design concept will proceed into construction. If changes are made either in the design phase or during construction, this office must be retained to review these modifications. The result of this review may be a modification of our recommendations or the requirement of additional field or laboratory work to check whether the changes are acceptable from a geotechnical viewpoint.

2. Site Description and Regional Geology

The Site is located on the east side of Fowler Drive, about 160 m south of the intersection of Fowler Drive and North Sheridan Way, in the City of Mississauga, Ontario. The site is currently a landscaping area east of the existing apartment buildings, 1970 & 1980 Fowler Drive.

The project area is situated in the transition zone of Lake Iroquois, beach or bar deposits: gravel, sand and Young tills: clayey silt till (Halton). as represented in Quaternary Geology: Toronto and Surrounding Area (Ministry of Natural Resources, Ontario Geological Survey, Preliminary Map P.2204).

The overburden soils at the site consist of shallow man-made fill underlain by silty clay till/shale complex. Bedrock at the site consists of grey shale of Georgian Bay Formation. The depth of bedrock in this general area ranges from approximately 3.3 to 4.7 m below the surface.

3. Investigation Procedures

The fieldwork for the geotechnical investigation was carried out in the period of June 20 to 23, 2023 and March 18 to 26, 2025. Prior to drilling, the borehole locations were cleared of underground services by the local utility companies and a private locator. Ten (10) sampled boreholes, designated as Borehole 1 to 6 and Borehole 25-1 to 25-4 were drilled to depths ranging from about 4.0 to 18.5 m below the existing grade. The location and ground surface elevation of the boreholes were obtained via GPS Instrument, SOKKIA GCX3 unit, which uses satellites to establish the UTM coordinates and geodetic elevations. The approximate borehole locations are shown on the attached Borehole Location Plan, Drawing No. 1.

The boreholes were advanced using a continuous flight solid/hollow stem augering drilling equipment owned and operated by a specialist drilling contractor. In each borehole, soil samples were recovered at regular intervals with a split barrel sampler in accordance with the standard penetration test (SPT) procedures. Bedrock was encountered in all boreholes. Boreholes 1, 25-1 to 25-4 were extended into the shale bedrock and rock coring drilling method was carried out using HQ size diamond coring equipment.

All of the boreholes from the investigation were instrumented with monitoring wells for subsequent groundwater level measurements and preliminary hydrogeological investigation.

The fieldwork was supervised by an EXP geotechnical technician who monitored the drilling operations and logged the borings. All split barrel samples were transported to our laboratory for detailed examination by the project engineer and for laboratory testing, which included natural moisture content determination on all recovered samples. Three (3) rock core sample was prepared and subjected to Unconfined Compressive Strength testing (UCS) and four (4) rock core samples were subjected to point load testing. Groundwater levels were observed on site upon completion of drilling operation as well as taken in the installed monitoring wells during the subsequent groundwater level reading. One (1) soil sample was also analyzed for pH & water-soluble sulphate.

4. Subsurface Conditions

The detailed soil profiles encountered in each borehole and the results of geotechnical laboratory testing are indicated on the attached borehole logs (Drawings No. 2 through 11) and in Appendix A. It should be noted that the soil boundaries indicated on the borehole logs are inferred from non-continuous sampling and observations during drilling. These boundaries are intended to reflect approximate transition zones for the purpose of geotechnical design and should not be interpreted as exact planes of geological change.

The “Notes on Sample Descriptions” and “Explanatory Sheet to Core Log” (Drawing 1A) preceding the borehole logs form an integral part of and should be read in conjunction with this report.

The following is a brief description of the subsurface conditions encountered during the current investigation.

4.1 Subsoil Conditions

Topsoil

Topsoil was encountered at the ground surface in all boreholes with a thickness ranging from about 150 to 250 mm.

Fill Materials

Fill materials were encountered below the topsoil in all boreholes. The fill typically consisted of brown sand, sand and gravel, and clayey silt with occasional rock fragments. The fill extended to depths ranging from 1.4 to 4.6 m (~Elevation 119.3 to 121.9 m). The moisture contents within the fill samples were found to range from 5 to 19 percent.

Silty Clay Till/Shale Complex

The silty clay till/shale complex was encountered in all boreholes below the fill material, except for Borehole 4 and 25-3. The till/shale complex extended to depths ranging from about 3.1 to 5.2 m (~Elevation 117.1 to 119.9 m). This deposit consists of a rather heterogeneous mixture of hard silty clay till with extensive amount of broken bedrock (shale and limestone/siltstone) slabs and fragments. This stratum was reportedly difficult to penetrate with the augers due to the fragmented shale/limestone content and given its hard condition. Cobbles and boulders are also anticipated in these deposits. The natural water contents measured in the test samples ranged from about 7% to 20%. This deposit gradually blends into the weathered shale and the transition between the two is difficult to estimate and some contractors may term this transition layer as weathered shale.

Shale Bedrock

Bedrock of the Georgian Bay Formation was encountered below the till/shale complex in all boreholes at depths ranging from about 3.3 to 4.7 m (~Elevation 117.1 to 119.9 m).

The shale bedrock was proven by rock core drilling in Boreholes 1 and 25-1 to 25-4. It should be noted that it was often difficult to distinguish where silty clay till/shale complex ends and bedrock begins, particularly where the bedrock surface is weathered. As such, the inferred bedrock surface can vary by approximately ± 1.0 m.

Bedrock of the Georgian Bay Formation consists typically of highly weathered to fresh, grey, fine to very fine grained fissile, weak to strong shale, interbedded with siltstone and limestone layers.

Shale bedrock was cored to a depth ranging from 12.4 to 18.5 m below the existing ground surface and detailed coring information is provided on the rock core log. Photographs of rock cores are presented in Appendix B of this report. Total Core Recovery (TCR) achieved with the HQ double tube size core bit ranged from 52 to 100%. The recorded RQD values for shale bedrock were generally ranging from 0 to 100%, indicating very poor to excellent rock quality.

Based on the visual examination of the rock cores, an attempt was made to identify and record the thickness and percentages of the relatively harder siltstone and limestone layers. At Boreholes 1 and 25-1 to 25-4 locations, the bedrock consists of 66% to 87% shale, 6% to 15% limestone, 4% to 15% siltstone and 1% to 3% clay and rubble layers/seams. It should be noted that in Borehole 25-1, there is a significant clay layer of up to 400 mm in thickness approximately 2 m into the bedrock. The total percentage of the “hard layers” is about 10% to 31%. The thickness of these layers varied but was generally less than 50mm. Although not encountered, the Georgian Bay formation is known to contain very strong limestone or siltstone layers of 600 to 900 mm thickness and layers of such thickness should be anticipated during construction. It is also common to encounter closely spaced groupings of thin strong limestone/siltstone layers which individually may only be 25 to 50 mm thick but collectively can be 1 m in thickness.

Four (4) samples of the rock cores were subjected to eight (8) point load index strength testing. The tested samples were generally shale. Unconfined compressive strength values were calculated as:

$$\text{UCS} = \text{Is50} \times K$$

where Is50 represents Point Load Index,

$$K = 12.6 \text{ for shale/limy shale}$$

The measured point load index strengths correspond roughly to unconfined compressive strengths ranging from about 10 to 40 MPa in axial; about 1 to 5 MPa in diametral, indicating weak to strong rock strength (Canadian Foundation Engineering Manual, 2023, 5th Edition, Table 4.21). The detailed point load test results on the rock core samples are included in Appendix A.

Test result of the unconfined compressive strength of rock core measured in the laboratory of EXP on three (3) sample is presented in Appendix A. The UCS test result was ranging from 48.9 to 76.2 MPa. Based on this result, the tested sample is classified as a 'Medium Strong to Strong' rock and likely belongs to the limestone/siltstone zones.

Although combustible gas was not measured in the open borings, the Georgian Bay Formation, as well as overburden directly above the shale, is known to contain pockets of methane.

4.2 Groundwater Conditions

Groundwater conditions were assessed by taking readings in monitoring wells installed in selected boreholes. Groundwater level observations in the monitoring wells are recorded on the attached borehole logs and summarized in Table 1.

Table 1: Measured Groundwater Levels

Borehole No.	Ground Elevation (m)	Groundwater Depth/Water Level Elevation (m)			Remark
		July 11, 2023	April 11, 2025	April 21, 2025	
1s*	123.30	3.68/119.6	4.45/118.9	4.49/118.8	In overburden
1d*	123.30	8.32/115.0	9.04/114.3	9.20/114.1	In bedrock
2	122.44	Dry (>3.4)	Dry (>3.4)	Dry (>3.4)	In overburden and bedrock
3	123.54	3.80/119.7	4.56/119.0	4.58/119.0	In overburden and bedrock
4	123.40	4.37/119.0	4.24/119.2	4.49/118.9	In overburden and bedrock
5	123.35	5.47/117.9	-	-	In overburden and bedrock
6	123.86	3.99/119.9	-	-	In overburden and bedrock
25-1	121.51	-	6.18/115.3	6.30/115.2	In bedrock
25-2	121.80	-	5.52/116.3	5.65/116.2	In bedrock
25-3	124.04	-	5.24/118.8	5.68/118.4	In bedrock
25-4	123.87	-	7.76/116.1	8.66/115.2	In bedrock

*Monitoring wells installed in different depths to monitoring the groundwater levels in overburden and bedrock.

It should be noted that the groundwater levels can vary seasonally and are subject to fluctuations in response to major weather events. A perched water table condition may occur due to the accumulation of surface water in the fill materials overlying the silty clay till/shale complex.

5. Geotechnical Recommendations

5.1 Foundation Considerations

Based on the limited information with regard to the proposed development, the following recommendations for foundation options are provided.

Spread and Strip Footings / Raft Foundation

For the proposed development, the building structure will consist of four (4) levels of underground parking. The proposed slab of the P4 underground parking of the building is designed to be at ~Elevation 110.15 m. The elevator pit will extend to about 2.6 m below the P4 slab. It is expected that founding level will extend approximately 1 m for spread footings and up to 3 m for raft foundations below the basement floor.

Based on the above summarized assumptions and borehole information, the proposed base floor slab of underground parking will be located in the shale bedrock of the Georgian Bay Formation.


The proposed structures can be supported by spread/strip footings or raft foundations founded in the sound shale bedrock of the Georgian Bay Formation. Spread/strip footings or raft foundations founded on sound shale bedrock below the P4 level can be designed using a factored ultimate bearing resistance of 7.5 MPa at Ultimate Limit States (ULS). The sound shale bedrock is considered to be an unyielding material; as such, SLS condition does not apply for this foundation type. A modulus of subgrade reaction of 600 MPa/m on sound shale with limestone and siltstone interbeds can be used for the raft design.

All footing bases must be reviewed by this office prior to pouring concrete. The shale bedrock weathers rapidly between wetting and drying cycles. In view of this, it is suggested that a lean concrete mat slab be placed immediately after the excavation is complete and approved to keep the shale intact unless the footings are poured immediately after excavating. The bearing shale bedrock and fresh concrete must be protected from freezing during cold weather construction.

5.2 Foundations - General

If footings are to be placed at different levels in the sound shale bedrock, the higher footings should be placed below an imaginary line with slope of one (1) Horizontal to one (1) Vertical (1H:1V) drawn from the bottom of the lower footing. This is assuming that the rock between the footings is not fractured during the excavation.

In case that footings are to be placed at different levels in the overburden, adjacent footings at different elevations should be located such that higher footings are set below a line drawn up at ten (10) Horizontal to seven (7) Vertical (10H:7V) from the near edge of the lower footing. This concept should also be applied to excavations for new foundations in relation to existing footings or underground services. The aforementioned concept is illustrated in the following sketch.



FOOTINGS NEAR SERVICE TRENCHES OR AT DIFFERENT ELEVATIONS

All footing caps exposed to freezing conditions must be provided with a minimum of 1.2 m of earth cover or equivalent insulation for frost protection, depending on the final grade requirements.

For footings founded on sound bedrock, the settlements are expected to be about 12 mm total and 6 mm differential.

The recommended bearing capacities have been calculated by EXP from the borehole information for the design stage only. The investigation and comments are necessarily on-going as new information of underground conditions becomes available. For example, it should be appreciated that modifications to bearing levels may be required if unforeseen subsoil conditions are revealed after the excavation is exposed to full view or if final design decisions differ from those assumed in this report. For this reason, this office should be retained to review final foundation drawings and to provide field inspections during the construction stage. As stated before, the results of this geotechnical study should therefore be regarded as very preliminary at best due to the limited number of boreholes drilled to the required depth for the proposed development.

5.3 Excavation and Groundwater Control

For the proposed development with four (4) levels of basement, the excavations will be carried out through the overburden followed by weathered and sound rock up to about 16 m below the existing grade. Sumps and elevator pits may require localized excavations to continue even deeper.

All excavations must be carried out in accordance with the most recent Occupational Health and Safety Act (OHSA). In accordance with OHSA, the fill can be classified as Type 3 Soil and the till/shale complex can be classified as Type 1 Soil.

It should be noted that the till/shale complex may contain cobbles, boulders and the shale bedrock may contain limestone/siltstone slabs. Their presence may influence the progress of excavation. Consequently, provisions should be made in the contract documents to cover any delays caused by these obstructions. In addition, perched water may be encountered at the transition zone between overburden and bedrock.

Excavation of the shale can be carried out using large backhoes equipped with single tooth ripper equipment. It should be noted that the limestone/siltstone (hard layers) are frequent and may overlie the shale bedrock surface at some locations. It may be necessary at some locations to utilize ripper and/or hoe ram to break up the limestone/siltstone layers. Contractor should be prepared to deal with the excavation difficulties caused by the anticipated hard layers.

Excavations cut into the bedrock can be on a near-vertical face. The face of the excavation, however, must be scaled off any loose rock to protect the workers working in the excavation. Rock cuts deeper than approximately 1.5 m, should also be covered with welded wire mesh rock fall protection or approved equivalent and anchored using rockbolts at strategic locations as per the supplier's recommendations.

No major problems with groundwater are anticipated for the excavations in the shallow overburden or into the shale bedrock. Perched water should be expected at the interface between the overburden and bedrock and also the fill. It should be possible to control and remove this perched water by pumping from temporary sumps. It should be noted that significant water loss was noted during the rock coring. Frequent fractures and/or bedding joints are inferred to be presented in the bedrock. The fractured bedrock may need to be grouted to stop groundwater seepage in the worst case. Regular cleaning of the sumps will be needed given the potential of accumulation of rock fines. It should be noted that the groundwater levels can vary and are subject to seasonal fluctuations in response to weather events. The groundwater levels measured on July 11, 2023, April 11 and 21, 2025 show that the groundwater levels ranged from 9.2 to 5.2 m in deep wells installed in bedrock and from 3.7 m to 5.5 m depth in shallow wells installed in overburden and bedrock.

5.4 Temporary Shoring

Excavations in overburden and upper highly weathered shale may be supported by a temporary shoring system consisting of soldier piles and lagging. A caisson wall may be required to support adjacent structures or settlement sensitive utilities. The temporary shoring system for this project should be designed on the basis of the state-of-the-art information given in the fifth edition of the Canadian Foundation Engineering Manual (CFEM). The parameters that are considered to be applicable for this project and have been used successfully on many other deep excavations in the downtown area, are as follows:

The shoring should be designed for lateral earth pressure using the following parameters:

Earth pressure coefficient:

= 0.25 where small movements permissible

= 0.35 where utilities, roads, sidewalks must be protected from significant movement, or where vibration from traffic is a factor

= 0.45 where the movements are to be limited

Unit weight of retained soil and rock (γ) = 22 and 24.5 kN/m³ respectively

The soldier piles should be installed in pre-augered holes and temporary liners may be required to help prevent the fills from caving during the installation period. Safe net bearing value for soldier pile holes in the sound shale bedrock can be taken as $q = 7500$ kPa, provided the embedment is at least 1 diameter into the sound rock and the holes are cleaned and dry prior to pouring concrete.

Should the caisson wall be selected, the caisson wall 'filler piles' must be drilled through the weathered zone and taken at least 0.5m into sound shale to provide lateral support. The depth of sound bedrock should be field-verified in selected piles using down-hole video inspection equipment or through field observation of the drilling and the rock cuttings.

Tieback anchors should be installed in the soil behind the excavation to a sufficient distance to allow mobilizing the desired lateral load resistance. The recommended configuration of the no-load zone is shown in Figure 26.16 of the Canadian Foundation Engineering Manual, 4th Edition. The minimum horizontal spacing between anchors should be 1.2 m to ensure that group effects between adjacent ground anchors are minimized and that anchor intersection (due to drilling deviations) is avoided. Group effects will reduce the load-carrying capacity of individual ground anchors. The anchors may be designed for the bond stresses shown in Table 2 following.

Table 2: Bond Stress for Tieback Anchors

Soil Type	Allowable Bond Stress (kPa)
Hard silty clay till/shale complex	100*
Shale bedrock	700

* higher bond will be available if re-groutable anchors are used.

The recommended design parameters should be confirmed by load testing a number of anchors to 200% design load in accordance with the current edition of the CFEM. As a minimum for this site, at least two 200% anchor load tests for each supporting soil or rock type should be carried out to verify the capacity of the anchors. The design for the production anchors should then be modified based on the test results, where necessary. All remaining anchors must be installed using similar procedures and proof tested to 1.33 times the design load.

During winter months, the shoring should be covered with thermal blankets to prevent frost penetration behind the shoring system which may result in unacceptable movements.

EXP should be retained to review the shoring design, to monitor installation and testing of the system, and to monitor the shoring during all phases of the excavation. Inclinometers should be installed at locations where sensitive buildings or services lie close to the excavation. Careful monitoring is needed in any shored excavation, especially when buildings are located in close proximity. This is necessary not only to anticipate when and if additional support is needed, but also to provide data to meet claims from adjacent property owners. In this regard, it is essential that detailed precondition surveys be made on adjacent buildings.

5.5 Basement Wall

In situations where the basements are drained, the lateral earth pressure acting on the basement walls may be calculated from the following expression:

$$p = k(\gamma h + q)$$

where p = the pressure in kPa acting against any subsurface wall at depth, h , below the ground surface;

k = the earth pressure coefficient considered to be 0.4;

γ = the bulk unit weight of the retained overburden soil, use 22.0 kN/m³;

h = the depth in m below the ground surface at which the pressure, p , is to be computed; and

q = the value of any adjacent surcharge in kPa which may be acting close to the wall.

The above expression assumes that the perimeter drainage system prevents the buildup of any hydrostatic pressure behind the wall and granular backfill will be used behind the wall.

For a waterproofed basement, the lateral earth pressures acting on basement walls may be calculated from the following expression:

$$p = k (\gamma h_1 + \gamma' h_2 + q) + \gamma w h_2$$

where p = lateral earth pressure in kPa acting at depth h

k = earth pressure coefficient, assumed to be 0.4 for vertical walls and horizontal backfill

γ & γ' = unit weight and submerged unit weight of overburden soil, a value of 22 and 12 kN/m³ may be assumed

γ_w = Unit weight of water, a value of 10 kN/m³ can be used

h_1 = depth to the groundwater table in metres

h2 Depth below water table in metres

q = equivalent value of surcharge on the ground surface in kPa

5.6 Floor Slab Construction and Permanent Drainage

The subgrade on which the underground parking floor slabs will rest will be shale bedrock of Georgian Bay Formation. Any softened/disturbed wet rock pieces must be removed and replaced with fill concrete.

For the raft foundation scenario, a secondary slab may be constructed with a clear stone layer separating the raft and the slab-on-grade. Underfloor drainage should be installed in the clear stone just above the raft foundation to collect any leakage from the slab on grade. Alternatively, the top of the raft itself can be used as the floor slab.

If footings are selected for support of the building structure, normal slab-on-grade type construction may be used on shale bedrock. 200 mm of 19 mm clear crushed stone should be installed under the floor slab. A perimeter drainage system will be required around the exterior basement walls. Underfloor drains, placed within the utility trenches should be installed. The recommendations for a perimeter and underfloor drainage system, where open cut procedures are used, are shown on Drawing No. 12. The perimeter drainage for shoring system is shown on Drawing No.13.

If the basement is to be constructed as a water-tight structure, waterproofing will be required below the raft foundation and around the perimeter walls. The basement walls and the raft in this case, would have to be designed for hydrostatic pressure. Perimeter and underfloor drains will not be required in this case.

5.7 Earthquake Considerations

The recommendations for the geotechnical aspects to determine the earthquake loading for design in accordance with Section 4.1.8 in the Ontario Building Code (OBC) 2024, are presented below..

Subsoil Conditions

The subsoil and groundwater information at this site have been examined in relation to Section 4.1.8.4 of the OBC (2024). The subsoils at this subject site generally consist of fill, till/shale complex and bedrock. It is anticipated that the proposed structures will be founded on footings or raft foundations on bedrock.

Depth of Boreholes

Table 4.1.8.4.-A Exceptions for Site Designation Using Vs30 Calculated from In Situ Measurements and Table 4.1.8.4.-B Site Classes, S, for Site Designation Xs in OBC (2024) indicated that to determine the site classification, the average properties in the top 30 m (below the lowest basement level) are to be used. Site Classification can be determined using the average shear wave velocity (Vs30) as per the classifications stated in Table 4.1.8.4.-A and Table 4.1.8.4.-B. If in-situ shear wave velocity measurements are not available, the site designation Xs shall be determined based on the energy-corrected average standard penetration resistance (SPT) N_{60} or the average undrained shear strength S_u in accordance with Table 4.1.8.4.-B.

There are no shear wave measurements carried out at this site and therefore, the Site Class will be determined based on the energy-corrected average SPT. The boreholes advanced at this site terminated at depths of about 4.0 to 18.5 m below existing grade. Therefore, the site classification recommendation would be based on the available information as well as our interpretation of conditions below the boreholes based on our knowledge of the soil conditions in the area

Site Classification

Based on the above assumptions and currently available information, the Site Class for the proposed development is “B” as per Table 4.1.8.4.B, Site Classification for Seismic Site Response, OBC 2024. According to Section A-4.1.8.4 of OBC 2024, the in-situ measurements of shear wave velocity can be utilized to lower the demand in the seismic design. Therefore, field shear wave velocity measurements are recommended to be performed through non-intrusive (e.g. multichannel analysis of surface waves) and / or intrusive (e.g. downhole / cross hole techniques, or SCPT) geophysical tests.

5.8 Potential for Sulphate Attack

One (1) sample from BH1 was analyzed for pH and water-soluble sulphate. The pH of the soil sample is 7.71. The soluble sulphate content in the sample analyzed was reported $<20 \mu\text{g/g}$ ($<0.002\%$). Table 3 of the Canadian Standards Association (CSA) A.23.1-09 lists 0.1 % sulphate as the minimum concentration of sulphate in soil that warrants additional requirements for concrete. At the measured concentration, the degree of exposure to sulphate attack is considered to be “negligible” and therefore normal Portland cement (Type 10) can be used in subsurface concrete.

6. General Comments

EXP should be retained for a general review of the final design and specifications to verify this report has been properly interpreted and implemented. If not accorded the privilege of making this review, EXP will assume no responsibility for interpretation of the recommendations in the report.

The comments given in this report are intended only for the guidance of design engineers. The number of boreholes required to determine the localized underground conditions between boreholes affecting construction costs, techniques, sequencing, equipment, scheduling, etc. could be greater than has been carried out for design purposes. Contractors bidding on or undertaking the works should, in this light, decide on their own investigations as well as their own interpretations of the factual borehole results so that they may draw their own conclusions as to how the subsurface conditions may affect them.

More specific information with respect to the conditions between samples or the lateral and vertical extent of materials may become apparent during excavation operations. The interpretation of the borehole information must, therefore, be validated during excavation operations. Consequently, during the future development of the property, conditions not observed during this investigation may become apparent; should this occur, EXP should be contacted to assess the situation and additional testing and reporting may be required. EXP has qualified personnel to provide assistance in regard to future geotechnical issues related to this property.

We trust this report is satisfactory for your purposes. Should you have any questions or comments, please do not hesitate to contact this office.


EXP Services Inc.

Jack Li, P.Eng.
Senior Engineer
Geotechnical Division



for Stephen S. M. Cheng, P.Eng.
Discipline Manager
Geotechnical Division

DRAWINGS



SCALE:
0 10 20 30 40 50 m

LEGEND:

- BOREHOLE / MONITORING WELL (EXP, 2023)
- APPROXIMATE SITE BOUNDARY
- PROPERTY BOUNDARY
- ◆ BOREHOLE LOCATION (EXP, 2025)



DRAWN BY: JW
CHECKED BY: FM

BOREHOLE / MONITORING WELL
LOCATION PLAN

FIGURE:

1

GEOTECHNICAL INVESTIGATION
1970 AND 1980 FOWLER DRIVE
MISSISSAUGA, ONTARIO

PROJECT NUMBER: BRM-22022660-B0

DATE: APRIL 2025

Notes on Sample Descriptions and Soil Types

Drawing 1A

1. All sample descriptions included in this report follow the Canadian Foundations Engineering Manual soil classification system. This system follows the standard proposed by the International Society for Soil Mechanics and Foundation Engineering. Laboratory grain size analyses provided by exp also follow the same system. Others may use different classification systems; one such system is the Unified Soil Classification. Please note that, with the exception of those samples where a grain size analysis has been made, all samples are classified visually. Visual classification is not sufficiently accurate to provide exact grain sizing or precise differentiation between size classification systems.

ISSMFE SOIL CLASSIFICATION											
CLAY	SILT			SAND			GRAVEL			COBBLES	BOULDERS
	FINE	MEDIUM	COARSE	FINE	MEDIUM	COARSE	FINE	MEDIUM	COARSE		
0.002	0.006	0.02	0.06	0.2	0.6	2.0	6.0	20	60	200	
EQUIVALENT GRAIN DIAMETER IN MILLIMETERS											
CLAY (PLASTIC) TO SILT (NONPLASTIC)			FINE	MEDIUM	COARSE	FINE	COARSE		GRAVEL		
			SAND								

UNIFIED SOIL CLASSIFICATION

2. Fill: Where fill is designated on the borehole log it is defined as indicated by the sample recovered during the boring process. The reader is cautioned that fills are heterogeneous in nature and variable in density or degree of compaction. The borehole description may therefore not be applicable as a general description of site fill materials. All fills should be expected to contain obstruction such as wood, large concrete pieces or subsurface basements, floors, tanks, etc., none of these may have been encountered in the boreholes. Since boreholes cannot accurately define the contents of the fill, test pits are recommended to provide supplementary information. Despite the use of test pits, the heterogeneous nature of fill will leave some ambiguity as to the exact composition of the fill. Most fills contain pockets, seams, or layers of organically contaminated soil. This organic material can result in the generation of methane gas and/or significant ongoing and future settlements. Fill at this site may have been monitored for the presence of methane gas and, if so, the results are given on the borehole logs. The monitoring process does not indicate the volume of gas that can be potentially generated nor does it pinpoint the source of the gas. These readings are to advise of the presence of gas only, and a detailed study is recommended for sites where any explosive gas/methane is detected. Some fill material may be contaminated by toxic/hazardous waste that renders it unacceptable for deposition in any but designated land fill sites; unless specifically stated the fill on this site has not been tested for contaminants that may be considered toxic or hazardous. This testing and a potential hazard study can be undertaken if requested. In most residential/commercial areas undergoing reconstruction, buried oil tanks are common and are generally not detected in a conventional geotechnical site investigation.
3. Till: The term till on the borehole logs indicates that the material originates from a geological process associated with glaciation. Because of this geological process the till must be considered heterogeneous in composition and as such may contain pockets and/or seams of material such as sand, gravel, silt or clay. Till often contains cobbles (60 to 200 mm) or boulders (over 200 mm). Contractors may therefore encounter cobbles and boulders during excavation, even if they are not indicated by the borings. It should be appreciated that normal sampling equipment cannot differentiate the size or type of any obstruction. Because of the horizontal and vertical variability of

till, the sample description may be applicable to a very limited zone; caution is therefore essential when dealing with sensitive excavations or dewatering programs in till materials.

4. Excerpt from "OHSA Regulations for Construction Projects," Part III, Section 226:

- **Soil Types**

Type 1 Soil

- a) is hard, very dense and only able to be penetrated with difficulty by a small sharp object;
- b) has a low natural moisture content and a high degree of internal strength;
- c) has no signs of water seepage; and
- d) can be excavated only by mechanical equipment.

Type 2 Soil

- a) is very stiff, dense and can be penetrated with moderate difficulty by a small sharp object;
- b) has a low to medium natural moisture content and a medium degree of internal strength; and
- c) has a damp appearance after it is excavated.

Type 3 Soil



- a) is stiff to firm and compact to loose in consistency or is previously excavated soil;
- b) exhibits signs of surface cracking;
- c) exhibits signs of water seepage;
- d) if it is dry, may run easily into a well-defined conical pile; and
- e) has a low degree of internal strength.

Type 4 Soil

- a) is soft to very soft and very loose in consistency, very sensitive and upon disturbance is significantly reduced in natural strength;
- b) runs easily or flows, unless it is completely supported before excavating procedures;
- c) has almost no internal strength;
- d) is wet or muddy; and
- e) exerts substantial fluid pressure on its supporting system. O. Reg. 213/91, s. 226.

EXPLANATORY SHEET TO CORE LOG

EXPLANATORY SHEET TO CORE LOG

<u>Column No.</u>		<u>Description</u>	
13	Strength of Rock Material :		<u>Uniaxial Compressive Strength</u>
		Very high strength = specimen can only be chipped by geological hammer	> 200 MPa
	High strength = specimen requires a number of blows to fracture it; cannot be scrapped with a pocket knife		50 - 200 MPa
	Medium strength = specimen can be fractured by a single blow of geological hammer; can be scrapped with pocket knife, not peeled		15 - 50 MPa
	Low strength = shallow indentations made with a firm blow of geological hammer; can be peeled by pocket knife with difficulty		4 - 15 MPa
	Very low strength = crumbles under firm blow with point of geological hammer; can be peeled by pocket knife		1 - 4 MPa
14	Fracture Frequency : Number of natural joints occurring over a metre length of core. All natural joints are counted irrespective of the number of joint sets.		
		<u>Fracture Frequency</u>	<u>Joint Spacing</u>
		< 0.3 /m 0.3 - 1 /m 1 - 3 /m 3 - 20 /m > 20 /m	= Very wide = 3 m = Wide = 1 - 3 m = Moderate = 30 cm - 1 m = Close = 5 - 30 cm = Very close ≤ 5 cm
15	Run Number : Drill run number		
16	Core Recovery : Core recovery is the total length of core pieces, irrespective of their individual lengths, obtained in a core run and expressed as a percentage of the length of that core run.		
17	Rock Quality Designation (RQD) : The total length of those pieces of sound core which are 10 cm or greater in length in a core run expressed as a percentage of the total length of that core run. Sound pieces of rock are those pieces separated by natural breaks and not machine breaks or subsequent artificial breaks.		
	<u>RQD</u>		<u>Rock Mass Classification (After Deere)</u>
	0 - 25%		very poor
	25 - 50%		poor
	50 - 75%		fair
	75 - 90%		good
	90 - 100%		excellent
18	Water Recovery : The estimated water returning out of the casing		
19	Water Colour : The colour of the water returning out of the casing		

Log of Borehole 1d

Project No. GTR-22022660-A0

Drawing No. 2

Project: Geotechnical Investigation

Sheet No. 1 of 2

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: Jue 23, 2023

Auger Sample



Combustible Vapour Reading



Natural Moisture



Plastic and Liquid Limit



Undrained Triaxial at



% Strain at Failure




Drill Type: Hollow Stem Auger / Rock Coring


Penetrometer



Datum: Geodetic



Continued Next Page



Date	Water Level (m)	Hole Open to (m)
July 11, 2023	8.32	
April 11, 2025	9.04	
April 21, 2025	9.20	

ROCK CORE LOG

BH 1

PROJECT			ORIENTATION		ELEVATION (m)		DATUM		PROJECT NUMBER								
Geotechnical Investigation			Vertical		123.3		GTR-22022660-A0		Geodetic								
LOCATION			DATE STARTED		COMPLETED		LOGGED BY		DRAWING NUMBER								
Starlight Developments			DRILLER		DRILL TYPE		CORE BARREL		SHEET								
			DBW		Track Mount CME 55 HQ				1 of 1								
ELEVATION (m)	DEPTH (m)	SYMBOL	JOINT CHARACTERISTICS									RECOVERY (%)	RQD	WATER RECOVERY (%)	WATER COLOUR		
			NO. OF SETS	JOINT TYPE	ORIENTATION	SPACING	ROUGHNESS	FILLING	APERTURE (mm)	WEATHERING	STRENGTH					FRACURE FREQUENCY	RUN NUMBER
1	2	3	GENERAL DESCRIPTION									16	17	18	19		
1	2	3	4									15	16	17	18	19	
120.3	-3		See Borehole Log for Details														
119.5	-4		GEORGIAN BAY FORMATION														
119.5			Shale with interbedded siltstone, and clay layers.														
119.2			Shale (87%) thinly bedded or laminated, grey, low strength, alternating between heavily and moderately weathered to 9.4 m and between														
118.9			moderately weathered to 9.4 m and between														
118.8			slightly weathered and fresh below.														
118.5	-5		Limestone (6%) fine grained, grey, medium strength, unweathered.														
118.4			Siltstone (4%) fine grained, grey, medium strength, unweathered.														
118.3			Discontinuities: bedding joints are rough planar to smooth undulating and at very close intervals.														
118.1			Vertical fractures were noted at 5.26 m and 7.04 m.														
116.5	-6		A clay (3%) layer, heavily weathered, very low strength were noted at ~4.98 m.														
116.4			Rubble layers were noted at ~3.84 m (305 mm) and 6.53 m (80 mm).														
116.3																	
116.2																	
115.8	-7																
115.8																	
113.4	-8																
113.3																	
112.0	-9																
111.8																	
111.7	-10																
110.9	-11																
	-12		END OF BOREHOLE End of Borehole at 12.4 m														

EXP_ROCKCORE_ROCK LOG.GPJ CORE LOG.GDT 7/12/23

Log of Borehole 1s

Project No. GTR-22022660-A0

Drawing No. 2

Project: Geotechnical Investigation

Sheet No. 1 of 1

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: Jue 21, 2023

Auger Sample



Combustible Vapour Reading



Natural Moisture



Plastic and Liquid Limit



Undrained Triaxial at



% Strain at Failure




Drill Type: Hollow Stem Auger / Rock Coring

Penetrometer



Datum: Geodetic



EXPLOGBRAMPTON FOWLER DRIVE-BHLOGS_JW GPJ NEW_GDT 4/22/25



Date	Water Level (m)	Hole Open to (m)
July 11, 2023	3.68	
April 11, 2025	4.45	
April 21, 2025	4.49	

Log of Borehole 2

Project No. GTR-22022660-A0

Drawing No. 3

Project: Geotechnical Investigation

Sheet No. 1 of 1

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan


Date Drilled: Jun 21, 2023

Auger Sample
SPT (N) Value
Dynamic Cone Test
Shelby Tube
Field Vane Test

Combustible Vapour Reading
Natural Moisture
Plastic and Liquid Limit
Undrained Triaxial at
% Strain at Failure
Penetrometer

Drill Type: Soild Stem Auger

Datum: Geodetic



Date	Water Level (m)	Hole Open to (m)

Log of Borehole 3

Project No. GTR-22022660-A0

Drawing No. 4

Project: Geotechnical Investigation

Sheet No. 1 of 1

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: Jue 20, 2023

Auger Sample



Combustible Vapour Reading



Natural Moisture



Plastic and Liquid Limit



Undrained Triaxial at



% Strain at Failure




Drill Type: Soild Stem Auger

Penetrometer



Datum: Geodetic



EXPLOGBRAMPTON FOWLER DRIVE-BHLOGS_JW GPJ NEW_GDT 4/22/25



Date	Water Level (m)	Hole Open to (m)
July 11, 2023	3.8	
April 11, 2025	4.56	
April 21, 2025	4.58	

Log of Borehole 4

Project No. BRM-22022660-A0

Drawing No. 5

Project: Geotechnical Investigation

Sheet No. 1 of 1

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: Jun 21, 2023

Auger Sample



Combustible Vapour Reading



Natural Moisture



Plastic and Liquid Limit



Undrained Triaxial at % Strain at Failure





Drill Type: Soild Stem Auger

Penetrometer



Datum: Geodetic



Date	Water Level (m)	Hole Open to (m)
July 11, 2023	4.37	
April 11, 2025	4.24	
April 21, 2025	4.49	

Log of Borehole 5

Project No. GTR-22022660-A0

Drawing No. 6

Project: Geotechnical Investigation

Sheet No. 1 of 1

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: Jun 21, 2023

Auger Sample



Combustible Vapour Reading



Natural Moisture



Plastic and Liquid Limit



Undrained Triaxial at



% Strain at Failure




Drill Type: Soild Stem Auger

Penetrometer



Datum: Geodetic



Date	Water Level (m)	Hole Open to (m)
July 11, 2023	5.47	

Log of Borehole 6

Project No. GTR-22022660-A0

Drawing No. 7

Project: Geotechnical Investigation

Sheet No. 1 of 1

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: Jue 20, 2023

Auger Sample



Combustible Vapour Reading



Natural Moisture



Plastic and Liquid Limit



Undrained Triaxial at



% Strain at Failure




Drill Type: Soild Stem Auger

Penetrometer



Datum: Geodetic



Date	Water Level (m)	Hole Open to (m)
July 11, 2023	3.99	

Log of Borehole 25-1

Project No. BRM-22022660-B0

Drawing No. 8

Project: Geotechnical Investigation

Sheet No. 1 of 2

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: March 19, 2025

Auger Sample



Combustible Vapour Reading



SPT (N) Value



Natural Moisture



Dynamic Cone Test



Plastic and Liquid Limit



Shelby Tube



Undrained Triaxial at



% Strain at Failure

% Strain at Failure


Field Vane Test



Penetrometer




Datum: Geodetic



Continued Next Page

Date	Water Level (m)	Hole Open to (m)
April 11, 2025	6.18	
April 21, 2025	6.30	



Date	Water Level (m)	Hole Open to (m)
April 11, 2025 April 21, 2025	6.18 6.30	

ROCK CORE LOG

BH 25-1

PROJECT										ORIENTATION		ELEVATION (m)		DATUM		PROJECT NUMBER								
Supplementary Geotechnical Investigation										Vertical		121.5		Geodetic		BRM-22022660-00								
LOCATION										DATE STARTED		COMPLETED		LOGGED BY		DRAWING NUMBER								
1970 & 1980 Fowler Drive, Mississauga										03/19/25		03/20/25		D. Panchal		8								
CLIENT										DRILLER		DRILL TYPE		CORE BARREL		SHEET								
Starlight Development										DBW		CME Track Mount		HQ		1 of 4								
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION										JOINT CHARACTERISTICS				WEATHERING	STRENGTH	FRACTURE FREQUENCY	RUN NUMBER	RECOVERY (%)	RQD	WATER RECOVERY (%)	WATER COLOUR
			5	6	7	8	9	10	11	12	13	14	15	16	17	18								
1	2	3	4																					
116.8				See Borehole Log for Details																				
116.4				GEORGIAN BAY FORMATION																				
116.3				Shale with interbedded siltstone, and clay layers.																				
116.2				Shale (71%) thinly bedded or laminated, grey, low strength, alternating between heavily and slightly weathered to 8.0 m and between moderately weathered and unweathered below.																				
116.1				Limestone (7%) fine grained, grey, medium strength, unweathered																				
115.8				Siltstone (21%) fine grained, grey, medium strength, unweathered.																				
115.7				Discontinuities: bedding joints are rough planar to smooth undulating and at wide to very close intervals.																				
115.6				Vertical fractures were noted at ~5.1 m, 5.3 m, 6.7 m, 7.0 m, 8.0 m, 10.0 m, 10.7 m, 11.4 m and 13.0 m.																				
115.5				A clay till (1%) layer, heavily weathered, very low strength were noted at ~5.2 m, 5.4 m, 5.8 m and 7.8 m.																				
115.4				Probably a lost clay or rubble layer were noted at ~7.1 m (420 mm)																				
115.3				Rubble layers was noted at ~5.2 m (50 mm), 5.3 m (30 mm), 6.5 m (40 mm), 6.8 m (200 mm), 7.6 m (160 mm), 13.1 m (50 mm) and 13.3 m.																				
114.4				Core Lost Possible Shale Rubble Layer low recovery possibly due to clay being washed out																				
113.8				1 B F C C RU RU NC 50 mm																				
113.7				2 52 0 70																				
113.6				Grey																				
112.8																								

ROCK CORE LOG

BH 25-1

ROCK CORE LOG

BH 25-1

ROCK CORE LOG

BH 25-1

PROJECT Supplementary Geotechnical Investigation				ORIENTATION Vertical		ELEVATION (m) 121.5		DATUM Geodetic		PROJECT NUMBER BRM-22022660-B0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
LOCATION 1970 & 1980 Fowler Drive, Mississauga				DATE STARTED 03/19/25		COMPLETED 03/20/25		LOGGED BY D. Panchal		DRAWING NUMBER 8																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
CLIENT Starlight Development				DRILLER DBW		DRILL TYPE CME Track Mount		CORE BARREL HQ		SHEET 4 of 4																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
ELEVATION (m)	DEPTH (m)	SYMBOL	JOINT CHARACTERISTICS										GENERAL DESCRIPTION																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140	141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160	161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180	181	182	183	184	185	186	187	188	189	190	191	192	193	194	195	196	197	198	199	200	201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220	221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240	241	242	243	244	245	246	247	248	249	250	251	252	253	254	255	256	257	258	259	260	261	262	263	264	265	266	267	268	269	270	271	272	273	274	275	276	277	278	279	280	281	282	283	284	285	286	287	288	289	290	291	292	293	294	295	296	297	298	299	300	301	302	303	304	305	306	307	308	309	310	311	312	313	314	315	316	317	318	319	320	321	322	323	324	325	326	327	328	329	330	331	332	333	334	335	336	337	338	339	340	341	342	343	344	345	346	347	348	349	350	351	352	353	354	355	356	357	358	359	360	361	362	363	364	365	366	367	368	369	370	371	372	373	374	375	376	377	378	379	380	381	382	383	384	385	386	387	388	389	390	391	392	393	394	395	396	397	398	399	400	401	402	403	404	405	406	407	408	409	410	411	412	413	414	415	416	417	418	419	420	421	422	423	424	425	426	427	428	429	430	431	432	433	434	435	436	437	438	439	440	441	442	443	444	445	446	447	448	449	450	451	452	453	454	455	456	457	458	459	460	461	462	463	464	465	466	467	468	469	470	471	472	473	474	475	476	477	478	479	480	481	482	483	484	485	486	487	488	489	490	491	492	493	494	495	496	497	498	499	500	501	502	503	504	505	506	507	508	509	510	511	512	513	514	515	516	517	518	519	520	521	522	523	524	525	526	527	528	529	530	531	532	533	534	535	536	537	538	539	540	541	542	543	544	545	546	547	548	549	550	551	552	553	554	555	556	557	558	559	560	561	562	563	564	565	566	567	568	569	570	571	572	573	574	575	576	577	578	579	580	581	582	583	584	585	586	587	588	589	590	591	592	593	594	595	596	597	598	599	600	601	602	603	604	605	606	607	608	609	610	611	612	613	614	615	616	617	618	619	620	621	622	623	624	625	626	627	628	629	630	631	632	633	634	635	636	637	638	639	640	641	642	643	644	645	646	647	648	649	650	651	652	653	654	655	656	657	658	659	660	661	662	663	664	665	666	667	668	669	670	671	672	673	674	675	676	677	678	679	680	681	682	683	684	685	686	687	688	689	690	691	692	693	694	695	696	697	698	699	700	701	702	703	704	705	706	707	708	709	710	711	712	713	714	715	716	717	718	719	720	721	722	723	724	725	726	727	728	729	730	731	732	733	734	735	736	737	738	739	740	741	742	743	744	745	746	747	748	749	750	751	752	753	754	755	756	757	758	759	760	761	762	763	764	765	766	767	768	769	770	771	772	773	774	775	776	777	778	779	780	781	782	783	784	785	786	787	788	789	790	791	792	793	794	795	796	797	798	799	800	801	802	803	804	805	806	807	808	809	810	811	812	813	814	815	816	817	818	819	820	821	822	823	824	825	826	827	828	829	830	831	832	833	834	835	836	837	838	839	840	841	842	843	844	845	846	847	848	849	850	851	852	853	854	855	856	857	858	859	860	861	862	863	864	865	866	867	868	869	870	871	872	873	874	875	876	877	878	879	880	881	882	883	884	885	886	887	888	889	890	891	892	893	894	895	896	897	898	899	900	901	902	903	904	905	906	907	908	909	910	911	912	913	914	915	916	917	918	919	920	921	922	923	924	925	926	927	928	929	930	931	932	933	934	935	936	937	938	939	940	941	942	943	944	945	946	947	948	949	950	951	952	953	954	955	956	957	958	959	960	961	962	963	964	965	966	967	968	969	970	971	972	973	974	975	976	977	978	979	980	981	982	983	984	985	986	987	988	989	990	991	992	993	994	995	996	997	998	999	1000	1001	1002	1003	1004	1005	1006	1007	1008	1009	10010	10011	10012	10013	10014	10015	10016	10017	10018	10019	10020	10021	10022	10023	10024	10025	10026	10027	10028	10029	10030	10031	10032	10033	10034	10035	10036	10037	10038	10039	10040	10041	10042	10043	10044	10045	10046	10047	10048	10049	10050	10051	10052	10053	10054	10055	10056	10057	10058	10059	10060	10061	10062	10063	10064	10065	10066	10067	10068	10069	10070	10071	10072	10073	10074	10075	10076	10077	10078	10079	10080	10081	10082	10083	10084	10085	10086	10087	10088	10089	10090	10091	10092	10093	10094	10095	10096	10097	10098	10099	100100	100101	100102	100103	100104	100105	100106	100107	100108	100109	100110	100111	100112	100113	100114	100115	100116	100117	100118	100119	100120	100121	100122	100123	100124	100125	100126	100127	100128	100129	100130	100131	100132	100133	100134	100135	100136	100137	100138	100139	100140	100141	100142	100143	100144	100145	100146	100147	100148	100149	100150	100151	100152	100153	100154	100155	100156	100157	100158	100159	100160	100161	100162	100163	100164	100165	100166	100167	100168	100169	100170	100171	100172	100173	100174	100175	100176	100177	100178	100179	100180	100181	100182	100183	100184	100185	100186	100187	100188	100189	100190	100191	100192	100193	100194	100195	100196	100197	100198	100199	100200	100201	100202	100203	100204	100205	100206	100207	100208	100209	100210	100211	100212	100213	100214	100215	100216	100217	100218	100219	100220	100221	100222	100223	100224	100225	100226	100227	100228	100229	100230	100231	100232	100233	100234	100235	100236	100237	100238	100239	100240	100241	100242	100243	100244	100245	100246	100247	100248	100249	100250	100251	100252	100253	100254	100255	100256	100257	100258	100259	100260	100261	100262	100263	100264	100265	100266	100267	100268	100269	100270	100271	100272	100273	100274	100275	100276	100277	100278	100279	100280	100281	100282	100283	100284	100285	100286	100287	100288	100289	100290	100291	100292	100293	100294	100295	100296	100297	100298	100299	100300	100301	100302	100303	100304	100305

Log of Borehole 25-2

Project No. BRM-22022660-B0

Drawing No. 9

Project: Geotechnical Investigation

Sheet No. 1 of 2

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: March 18, 2025

Auger Sample



Combustible Vapour Reading



Natural Moisture



Plastic and Liquid Limit



Undrained Triaxial at



% Strain at Failure




Drill Type: Hollow Stem Auger / Rock Coring

Penetrometer



Datum: Geodetic




EXPLOGBAMPTON FOWLER DRIVE-BHLOGS_JW GPJ NEW_GDT 4/22/25

Continued Next Page



Date	Water Level (m)	Hole Open to (m)
April 11, 2025 April 21, 2025	5.52 5.65	



EXPLOGBRAMPTON FOWLER DRIVE-BHLOGS_JW GPJ NEW.GDT 4/22/25

Date	Water Level (m)	Hole Open to (m)
April 11, 2025 April 21, 2025	5.52 5.65	

ROCK CORE LOG

BH 25-2

PROJECT									ORIENTATION		ELEVATION (m)		DATUM		PROJECT NUMBER					
Supplementary Geotechnical Investigation									Vertical		121.8		Geodetic		BRM-22022660-00					
LOCATION									DATE STARTED		COMPLETED		LOGGED BY		DRAWING NUMBER					
1970 & 1980 Fowler Drive, Mississauga									03/18/25		03/18/25		D. Panchal		9					
CLIENT									DRILLER		DRILL TYPE		CORE BARREL		SHEET					
Starlight Development									DBW		CME Track Mount		HQ		1 of 3					
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION	JOINT CHARACTERISTICS								WEATHERING	STRENGTH	FRACTURE FREQUENCY	RUN NUMBER	RECOVERY (%)	RQD	WATER RECOVERY (%)	WATER COLOUR	
				NO. OF SETS	JOINT TYPE	ORIENTATION	SPACING	ROUGHNESS	FILLING	APERATURE (mm)	12									13
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19		
117.3			See Borehole Log for Details																	
116.8	5		GEORGIAN BAY FORMATION																	
116.6			Shale with interbedded siltstone, and clay layers.																	
116.5			Shale (66%) thinly bedded or laminated, grey, low strength, alternating between heavily and slightly weathered to 7.2 m and between moderately weathered and unweathered below.		F	V														
116.4					F	V														
116.3																				
116.2			Limestone (15%) fine grained, grey, medium strength, unweathered																	
116.2																				
116.1																				
116.0			Siltstone (16%) fine grained, grey, medium strength, unweathered.	1	B	F	C	RU	RU								1	92	45	80
115.9	6		Discontinuities: bedding joints are rough planar to smooth undulating and at wide to very close intervals.																	
115.8																				
115.7			Vertical fractures were noted at ~5.1 m, 5.2 m, 5.4 m, 6.7 m, 7.5 m, 8.2 m, 9.1 m, 9.5 m, 9.8 m and 13.6 m.																	
115.5																				
115.5			A clay till (3%) layer, heavily weathered, very low strength were noted at ~5.3 m, 5.4 m, 5.7 m, 6.1 m and 7.0 m.																	
115.4																				
115.3			Probably a lost clay or rubble layer were noted at ~8.5 m (530 mm)																	
115.2																				
115.1			Rubble layers was noted at ~5.6 m (60 mm), 6.6 m (100 mm), 6.9 m (110 mm), 8.5 m (60 mm) and 9.3 m (100 mm).		F	V														
115.1																				
115.0																				
114.9	7																2	90	44	80
114.8																				
114.7																				
114.6																				
114.4																				
114.2																				
114.0																				
113.9																				
113.8	8																			

ROCK CORE LOG

BH 25-2

PROJECT							ORIENTATION		ELEVATION (m)		DATUM		PROJECT NUMBER															
Supplementary Geotechnical Investigation							Vertical		121.8		Geodetic		BRM-22022660-00															
LOCATION							DATE STARTED		COMPLETED		LOGGED BY		DRAWING NUMBER															
1970 & 1980 Fowler Drive, Mississauga							03/18/25		03/18/25		D. Panchal		9															
CLIENT							DRILLER		DRILL TYPE		CORE BARREL		SHEET															
Starlight Development							DBW		CME Track Mount		HQ		2 of 3															
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION				JOINT CHARACTERISTICS					WEATHERING	STRENGTH	FRACTURE FREQUENCY	RUN NUMBER	RECOVERY (%)	RQD	WATER RECOVERY (%)	WATER COLOUR									
1	2	3	4				5	NO. OF SETS	6	JOINT TYPE	7	ORIENTATION	8	SPACING	9	ROUGHNESS	10	FILLING	11	APERTURE (mm)	12	13	14	15	16	17	18	19
113.3		///	Core Lost Possible Shale Rubble Layer low recovery possibly due to clay being washed out				1		B	F	C	RP												3	62	17	60	Grey
112.7									F	V																		
112.6									F	V																		
112.5									F	V																		
112.4									F	V																		
112.3									F	V																		
112.1									F	V																		
112.0									F	V																		
111.9									F	V																		
10									F	V																		
111.4									F	V																		
111.4									F	V																		
11									F	V																		
110.6									F	V																		
110.5									F	V																		
109.8									F	V																		
109.7									F	V																		
109.5									F	V																		
109.4									F	V																		

ROCK CORE LOG

BH 25-2

PROJECT				ORIENTATION		ELEVATION (m)		DATUM		PROJECT NUMBER	
Supplementary Geotechnical Investigation				Vertical		121.8		Geodetic		BRM-22022660-BO	
LOCATION				DATE STARTED		COMPLETED		LOGGED BY		DRAWING NUMBER	
1970 & 1980 Fowler Drive, Mississauga				03/18/25		03/18/25		D. Panchal		9	
CLIENT				DRILLER		DRILL TYPE		CORE BARREL		SHEET	
Starlight Development				DBW		CME Track Mount		HQ		3 of 3	
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION	JOINT CHARACTERISTICS				WEATHERING			
1	2	3	4	5	6	7	8	9	10	11	12
109.2											
13											
108.3											
108.2											
108.0											
107.9											
14											
107.6											
107.5											
107.4											
107.3											
107.1											
107.0											
106.9											
15											
106.7											
106.5											
106.5											
106.4											
16											
End of Borehole at 15.4 m											

EXP_ROCKCORE_ROCK_LOG_22022660_BGPU CORE LOG_GDT 4/16/25

Log of Borehole 25-3

Project No. BRM-22022660-B0

Drawing No. 10

Project: Geotechnical Investigation

Sheet No. 1 of 2

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: March 25, 2025

Auger Sample



Combustible Vapour Reading



Natural Moisture



Plastic and Liquid Limit



Undrained Triaxial at



% Strain at Failure




Drill Type: Hollow Stem Auger / Rock Coring

Penetrometer



Datum: Geodetic



EXPLOGBRAMPTON FOWLER DRIVE-BHLOGS_JW GPJ NEW_GDT 4/22/25


Continued Next Page



Date	Water Level (m)	Hole Open to (m)
April 11, 2025 April 21, 2025	5.24 5.68	

Project: Geotechnical Investigation

Sheet No. 2 of 2



Date	Water Level (m)	Hole Open to (m)
April 11, 2025	5.24	
April 21, 2025	5.68	

ROCK CORE LOG

BH 25-3

PROJECT										ORIENTATION		ELEVATION (m)		DATUM		PROJECT NUMBER								
Supplementary Geotechnical Investigation										Vertical		124.0		Geodetic		BRM-22022660-00								
LOCATION										DATE STARTED		COMPLETED		LOGGED BY		DRAWING NUMBER								
1970 & 1980 Fowler Drive, Mississauga										03/25/25		03/26/25		D. Panchal		10								
CLIENT										DRILLER		DRILL TYPE		CORE BARREL		SHEET								
Starlight Development										DBW		CME Track Mount		HQ		1 of 4								
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION										JOINT CHARACTERISTICS				WEATHERING	STRENGTH	FRACTURE FREQUENCY	RUN NUMBER	RECOVERY (%)	RQD	WATER RECOVERY (%)	WATER COLOUR
			5	6	7	8	9	10	11	12	13	14	15	16	17	18								
1	2	3	4																					
119.5				See Borehole Log for Details																				
119.1	5			GEORGIAN BAY FORMATION																				
119.0				Shale with interbedded siltstone, and clay layers.																				
118.8				Shale (71%) thinly bedded or laminated, grey, low strength, alternating between heavily and slightly weathered to 6.5 m and between moderately weathered and unweathered below.																				
118.7				Limestone (13%) fine grained, grey, medium strength, unweathered																				
118.4				Siltstone (15%) fine grained, grey, medium strength, unweathered.																				
118.1	6			Discontinuities: bedding joints are rough planar to smooth undulating and at wide to very close intervals.																				
118.0				Vertical fractures were noted at ~6.8 m, 7.2 m, 8.2 m, 14.6 m.																				
117.9				A clay till (1%) layer, heavily weathered, very low strength were noted at ~5.4 m and 6.1 m.																				
117.7				Rubble layers was noted at ~5.1 m (130 mm).																				
117.6																								
117.5																								
117.3																								
117.2	7																							
116.8																								
116.7																								
116.5																								
116.4																								
116.2																								
115.9	8																							
115.9																								
115.7																								

ROCK CORE LOG

BH 25-3

PROJECT				ORIENTATION			ELEVATION (m)		DATUM		PROJECT NUMBER																												
Supplementary Geotechnical Investigation				Vertical			124.0		Geodetic		BRM-22022660-00																												
LOCATION				DATE STARTED			COMPLETED		LOGGED BY		DRAWING NUMBER																												
1970 & 1980 Fowler Drive, Mississauga				03/25/25			03/26/25		D. Panchal		10																												
CLIENT				DRILLER			DRILL TYPE		CORE BARREL		SHEET																												
Starlight Development				DBW			CME Track Mount		HQ		2 of 4																												
ELEVATION (m)			GENERAL DESCRIPTION				JOINT CHARACTERISTICS																																
1	2	DEPTH (m)	3	SYMBOL	4		5	NO. OF SETS	6	JOINT TYPE	7	ORIENTATION	8	SPACING	9	ROUGHNESS	10	FILLING	11	APERTURE (mm)	12	WEATHERING	13	STRENGTH	14	FRACURE FREQUENCY	15	RUN NUMBER	16	RECOVERY (%)	17	RQD	18	WATER RECOVERY (%)	19	WATER COLOUR			
115.5																																							
115.3																																							
115.1																																							
115.0	9																																						
114.5																																							
114.4																																							
114.1	10																																						
114.0																																							
113.8																																							
113.6																																							
113.6																																							
113.5																																							
112.9	11																																						
112.9																																							
112.8																																							
112.7																																							
112.6																																							
112.5																																							
112.0	12																																						
111.9																																							

ROCK CORE LOG

BH 25-3

PROJECT					ORIENTATION			ELEVATION (m)		DATUM		PROJECT NUMBER																															
Supplementary Geotechnical Investigation					Vertical			124.0		Geodetic		BRM-22022660-00																															
LOCATION					DATE STARTED			COMPLETED		LOGGED BY		DRAWING NUMBER																															
1970 & 1980 Fowler Drive, Mississauga					03/25/25			03/26/25		D. Panchal		10																															
CLIENT					DRILLER			DRILL TYPE		CORE BARREL		SHEET																															
Starlight Development					DBW			CME Track Mount		HQ		3 of 4																															
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION					JOINT CHARACTERISTICS																																			
1	2	3	4					5	NO. OF SETS	6	JOINT TYPE	7	ORIENTATION	8	SPACING	9	ROUGHNESS	10	FILLING	11	APERTURE (mm)	12	WEATHERING	13	STRENGTH	14	FRACTURE FREQUENCY	15	RUN NUMBER	16	RECOVERY (%)	17	RQD	18	WATER RECOVERY (%)	19	WATER COLOUR						
111.4																																											
111.3																																											
111.1																																											
111.0			13																																								
110.3																																											
110.2																																											
109.4			14																																								
109.3																																											
109.2																																											
109.2																																											
108.1			15																																								
108.1																																											
107.9																																											
107.7			16																																								

ROCK CORE LOG

BH 25-3

PROJECT				ORIENTATION		ELEVATION (m)		DATUM		PROJECT NUMBER	
Supplementary Geotechnical Investigation				Vertical		124.0		Geodetic		BRM-22022660-BO	
LOCATION				DATE STARTED		COMPLETED		LOGGED BY		DRAWING NUMBER	
1970 & 1980 Fowler Drive, Mississauga				03/25/25		03/26/25		D. Panchal		10	
CLIENT				DRILLER		DRILL TYPE		CORE BARREL		SHEET	
Starlight Development				DBW		CME Track Mount		HQ		4 of 4	
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION	JOINT CHARACTERISTICS							
1	2	3	4	5	6	7	8	9	10	11	12
107.5				1	B	F	W W	SP SP			
107.1											
107.1		17									
106.8											
106.7											
106.6											
106.5											
106.2											
106.2		18									
105.6			End of Borehole at 18.5 m								
19											
20											

Log of Borehole 25-4

Project No. BRM-22022660-B0

Drawing No. 11

Project: Geotechnical Investigation

Sheet No. 1 of 2

Location: 1970&1980 Fowler Drive, Mississauga, Ontario

See Borehole Location Plan

Date Drilled: March 21, 2025

Auger Sample

Combustible Vapour Reading



SPT (N) Value



Dynamic Cone Test

Natural Moisture



Shelby Tube

Plastic and Liquid Limit



Field Vane Test

Undrained Triaxial at % Strain at Failure




Drill Type: Hollow Stem Auger / Rock Coring

Penetrometer



Datum: Geodetic



EXPLOGRAMPTON FOWLER DRIVE-BHLOGS_JW GPJ NEW_GDT 4/22/25


Continued Next Page



Date	Water Level (m)	Hole Open to (m)
April 11, 2025	7.76	
April 21, 2025	8.66	

Project: Geotechnical Investigation

Sheet No. 2 of 2



Date	Water Level (m)	Hole Open to (m)
April 11, 2025	7.76	
April 21, 2025	8.66	

ROCK CORE LOG

BH 25-4

PROJECT				ORIENTATION			ELEVATION (m)		DATUM		PROJECT NUMBER									
Supplementary Geotechnical Investigation				Vertical			123.9		Geodetic		BRM-22022660-00									
LOCATION				DATE STARTED			COMPLETED		LOGGED BY		DRAWING NUMBER									
CLIENT				DRILLER			DRILL TYPE		CORE BARREL		SHEET									
Starlight Development				DBW			CME Track Mount		HQ		1 of 3									
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION	JOINT CHARACTERISTICS								WEATHERING	STRENGTH	FRACTURE FREQUENCY	RUN NUMBER	RECOVERY (%)	RQD	WATER RECOVERY (%)	WATER COLOUR	
				NO. OF SETS	JOINT TYPE	ORIENTATION	SPACING	ROUGHNESS	FILLING	APERTURE (mm)	12									13
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19		
119.1	5		See Borehole Log for Details																	
118.5																				
118.3			Core Lost Possible Shale Rubble Layer low recovery possibly due to clay being washed out																	
118.2			GEORGIAN BAY FORMATION																	
117.9	6		Shale with interbedded siltstone, and clay layers.	1	B	F	C	RU								1	82	60	80	Grey
117.7			Shale (71%) thinly bedded or laminated, grey, low strength, alternating between heavily and slightly weathered to 6.5 m and between moderately weathered and unweathered below.		F	V	C	RU												
117.7			Limestone (13%) fine grained, grey, medium strength, unweathered																	
117.6			Siltstone (15%) fine grained, grey, medium strength, unweathered.																	
117.3			Discontinuities: bedding joints are rough planar to smooth undulating and at wide to very close intervals.		F	V														
117.3			Vertical fractures were noted at ~6.8 m, 7.2 m, 8.2 m, 14.6 m.																	
116.9	7		A clay till (1%) layer, heavily weathered, very low strength were noted at ~5.4 m and 6.1 m.		F	V														
116.8			Rubble layers was noted at ~5.1 m (130 mm).		F	V														
116.6				1	B	F	C	RU								2	100	55	90	Grey
116.6																				
116.4																				
116.4																				
116.0																				
116.0																				
115.9	8																			
115.8																				
115.7																				
115.6																				
115.5																				
115.4																				
115.3																				
115.2																				

ROCK CORE LOG

BH 25-4


PROJECT Supplementary Geotechnical Investigation				ORIENTATION Vertical		ELEVATION (m) 123.9		DATUM Geodetic		PROJECT NUMBER BRM-22022660-B0								
LOCATION 1970 & 1980 Fowler Drive, Mississauga				DATE STARTED 03/24/25		COMPLETED 03/25/25		LOGGED BY D. Panchal		DRAWING NUMBER 11								
CLIENT Starlight Development				DRILLER DBW		DRILL TYPE CME Track Mount		CORE BARREL HQ		SHEET 2 of 3								
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION	JOINT CHARACTERISTICS				WEATHERING				RECOVERY (%)						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
114.9	9			1	B	F	C	RP						3	100	87	100	Grey
114.9						V	M	RP										
114.7				1	B	F	M	RP										
114.7																		
114.5				1	B	F	M	RP										
114.5																		
114.1																		
114.0	10																	
113.7																		
113.6																		
113.2																		
113.2																		
113.1																		
113.0	11																	
112.7																		
112.4																		
112.2																		
112.1																		
111.8	12																	
111.8																		
111.3																		
111.2																		

ROCK CORE LOG

BH 25-4

PROJECT				ORIENTATION		ELEVATION (m)		DATUM		PROJECT NUMBER														
Supplementary Geotechnical Investigation				Vertical		123.9		Geodetic		BRM-22022660-BO														
LOCATION				DATE STARTED		COMPLETED		LOGGED BY		DRAWING NUMBER														
1970 & 1980 Fowler Drive, Mississauga				03/24/25		03/25/25		D. Panchal		11														
CLIENT				DRILLER		DRILL TYPE		CORE BARREL		SHEET														
Starlight Development				DBW		CME Track Mount		HQ		3 of 3														
ELEVATION (m)	DEPTH (m)	SYMBOL	GENERAL DESCRIPTION	NO. OF SETS		JOINT CHARACTERISTICS			WEATHERING		STRENGTH		FRACTURE FREQUENCY		RUN NUMBER		RECOVERY (%)		RQD		WATER RECOVERY (%)		WATER COLOUR	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	
13																								
110.4																								
109.7																								
109.5																								
109.4																								
109.3																								
109.1																								
108.8																								
108.1				End of Borehole at 15.8 m																				
16																								

EXP_ROCKCORE_ROCK_LOG_22022660_BGPU CORE LOG.GDT 4/16/25




Notes:

1. Drainage tile to consist of 100 mm (4") diameter weeping tile or equivalent perforated pipe leading to a positive sump or outlet.
2. Concrete sand - 150 mm (6") top and side of drain. If drain is not on footing, place 100 mm (4 inches) of pea gravel below drain. 20 mm (3/4") clear stone is an alternative provided it is surrounded by an approved filter fabric (Terrafix 600R or equivalent).
3. C.S.A. fine concrete aggregate to act as filter material. Minimum 300 mm (12") top and side of tile drain. This may be replaced by an approved filter fabric as indicated in (2).
4. Free Draining backfill - OPSS Granular B or equivalent compacted to the specified density. Do not use heavy compaction equipment within 450 mm (18") of the wall. Use hand controlled light compaction equipment within 1.8 m (6') of wall.
5. Impermeable backfill seal - compacted clay, clayey silt or equivalent. If original soil is free-draining, seal may be omitted.
6. Do not backfill until wall is supported by basement and floor slabs or adequate bracing.
7. Moisture barrier to be at least 200 mm (8") of compacted clear 20 mm (3/4") stone.
8. Basement wall to be damp-proofed or waterproofed as per report.
9. Exterior grade to slope away from building.
10. Slab on grade should not be structurally connected to the wall or footing.
11. Underfloor drain invert to be at least 300 mm (12") below underside of floor slab. Drainage tile placed in parallel rows 6 to 8 m (20 to 25') centres one way. Place drain below subgrade with 150 mm (6") of concrete sand on top and sides.
12. Do not connect the underfloor drains to perimeter drains.
13. If the 20 mm (3/4") stone requires surface blinding, use 6 mm (1/4") clear stone chips.

**DRAINAGE AND BACKFILL RECOMMENDATIONS
BASEMENT WITH UNDERFLOOR DRAINAGE**

(not to scale)



**SUGGESTED EXTERIOR DRAINAGE AGAINST
SOLDIER PILE AND LAGGING SHORING SYSTEM**

APPENDICES

APPENDIX A

Rock Lab Testing Results

Table - Results of Point Load Index Strength Tests (Georgian Bay Formation)

BH No.	Run No.	Loading	Oil Pressure (kPa)	Force P (kN)	Distance D (mm)	De (mm)	Rock Type	Is (kPa)	F	Point Load Index $I_{S(50)}$ (MPa)	Approximate Uniaxial Compressive Strength (MPa)*
BH1	Run5	Diametral	300	0.3	62.00	62	Shale	78	1.11	0.1	1
		Axial	3980	3.8	41.00	57		1170	1.07	1.2	16
BH1	Run6	Diametral	1340	1.3	62.00	62	Shale	338	1.11	0.4	5
		Axial	2860	2.8	50.00	63		705	1.12	0.8	10

*UCS \approx 12.6 $I_{S(50)}$ [MPa] for Shale/Limy Shale;

UCS \approx 24 $I_{S(50)}$ [MPa] for Limestone/Siltstone

Force P = Pressure (kPa) x Ram Area (0.000967 m²)

Is (kPa) = P/(De/1000)²

Is(50) = F x Is

where F = sqrt (De/50)

Table - Results of Point Load Index Strength Tests (Georgian Bay Formation)

BH No.	Depth	Loading	Oil Pressure (kPa)	Force P	Distance	De	Rock Type	Is (kPa)	F	Point Load Index $I_{S(50)}$ (MPa)	Approximate Uniaxial Compressive Strength (MPa)*
				(kN)	D (mm)	(mm)					
BH25-2	13.72	Diametral	400	0.4	63.00	63.0	Limy Shale	97	1.12	0.1	1.4
		Axial	9490	9.2	38.00	55.2		3011	1.05	3.2	39.9
BH25-4	13.41	Diametral	210	0.2	63.00	63.0	Shale	51	1.12	0.1	0.7
		Axial	3670	3.5	32.00	50.7		1383	1.01	1.4	17.5

*UCS \approx 12.6 $I_{S(50)}$ [MPa] for Shale/Limy Shale;

UCS \approx 24 $I_{S(50)}$ [MPa] for Limestone/Siltstone

Force P = Pressure (kPa) \times Ram Area (0.000967 m²)

Is (kPa) = P/(De/1000)²

$I_{S(50)}$ = F \times Is

where F = sqrt (De/50)



exp Services Inc.
1595 Clark Boulevard
Brampton, Ontario, L6T 4V1
Tel: (905) 793-9800
Fax: (905) 793-0641
www.exp.com

Rock Core Test UCS

Project No.: GTR-22022660-A0

Project Name: 1970 & 1980 Fowler Dr.

Uniaxial Compressive Strength of Intact Rock Core Specimens

Core No.	BH1 R5				
Depth (m)	10.59				
Date Sampled	N/A				
Date Received	June 26 th , 2023				
Date Tested	June 27 th , 2023				
Lithology	N/A				
Length - (mm)	128.0				
Average Diameter - (mm)	63.0				
L/D Ratio	2.03				
Rate of Loading (MPa/Sec)	0.30				
Uniaxial Compressive Strength - (MPa)	76.2				
Moisture Condition at Time Of Test	Dry				
Remarks	Tested by E.Jageshur				

Tested in accordance with ASTM D3967, unless otherwise indicated.

E.Jageshur

Testing Laboratory Representative Signature
Eric Jageshur - Concrete Supervisor

June 28th, 2023

Date



Exp Services Inc.
Brampton Laboratory
1595 Clark Boulevard, Brampton ON L6T4V1
Tel: (905) 793 - 9800
Fax: (905) 793-0641
www.exp.com

Standard Test Method for Compressive Strength & Elastic Moduli of Intact Rock Core Specimens Under Varying States of Stress & Temperature
ASTM D7012 "Method C"

Project No.: BRM-22022660-B0

Project Name: 1980 Fowler Dr.

Test Results

Uniaxial Compressive Strength of Intact Rock Core Specimens

Core No.	BH25 - 1 R8	BH25 - 1 R10				
Depth (m)	16.46 - 16.57	17.34 - 17.50				
Date Sampled	N/A					
Date Received	April 2, 2025					
Date Tested	April 4, 2025					
Lithology	N/A					
Length (mm)	121.0	122.0				
Average Diameter - (mm)	60.0					
L/D Ratio	2.02	2.03				
Rate of Loading (MPa/Sec)	0.30					
Uniaxial Compressive Strength - (MPa)	48.9	65.1				
Moisture Condition at Time of Test	Dry					


*Tests in accordance with D7012 "Method C", unless otherwise indicated.

Testing Laboratory Approving Supervisor
Eric Jageshur - Concrete Supervisor

April 4, 2025

Date


APPENDIX B
Rock Core Photographic



EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337
2650 Queensview Drive, Suite 100
Ottawa, ON K2B 8H6, Canada


borehole no. Borehole 1	core runs Run 1 to 6: 3.84 - 12.4 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. GTR-22022660-A0
date cored Jun 23, 2023		Rock Core Photographs	FIG 1



EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337
 2650 Queensview Drive, Suite 100
 Ottawa, ON K2B 8H6, Canada


borehole no. BH 25-1	core runs Run 1 to 3: 5.08 - 9.50 m Run 4 to 6: 9.50 - 14.07 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. BRM-22022660-B0
date cored Mar 19, 2025		Rock Core Photographs	FIG 2



EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337
2650 Queensview Drive, Suite 100
Ottawa, ON K2B 8H6, Canada

borehole no. BH 25-1	core runs Run 7 to 9: 14.07 - 18.54 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. BRM-22022660-B0
date cored Mar 19, 2025		Rock Core Photographs	FIG 3



EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337
 2650 Queensview Drive, Suite 100
 Ottawa, ON K2B 8H6, Canada

borehole no. BH 25-2	core runs Run 1 to 3: 5.00 - 9.60 m Run 4 to 6: 9.60 - 14.20 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. BRM-22022660-B0
date cored Mar 18, 2025		Rock Core Photographs	FIG 4

BEDROCK CORES


Start of Run 7



EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337
2650 Queensview Drive, Suite 100
Ottawa, ON K2B 8H6, Canada

borehole no. BH 25-2	core runs Run 7: 14.20 - 15.42 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. BRM-22022660-B0
date cored Mar 18, 2025		Rock Core Photographs	FIG 5



EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337
 2650 Queensview Drive, Suite 100
 Ottawa, ON K2B 8H6, Canada

borehole no. BH 25-3	core runs Run 1 to 3: 4.88 - 8.13 m Run 4 to 6: 8.13 - 12.70 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. BRM-22022660-B0
date cored Mar 26, 2025		Rock Core Photographs	FIG 6

BEDROCK CORES

Start of Run 7

Start of Run 8



Start of Run 9

Start of Run 10




EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337

2650 Queensview Drive, Suite 100

Ottawa, ON K2B 8H6, Canada

borehole no. BH 25-3	core runs Run 7 to 8: 12.70 - 15.80 m Run 4 to 6: 15.80 - 18.49 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. BRM-22022660-B0
date cored Mar 26, 2025		Rock Core Photographs	FIG 7



EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337
 2650 Queensview Drive, Suite 100
 Ottawa, ON K2B 8H6, Canada

borehole no. BH 25-4	core runs Run 1 to 3: 5.33 - 9.65 m Run 4 to 5: 9.65 - 12.70 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. BRM-22022660-B0
date cored Mar 24, 2025		Rock Core Photographs	FIG 8

BEDROCK CORES

Start of Run 6

Start of Run 7



EXP Services Inc. www.exp.com

t: +1.613.688.1899 | f: +1.613.225.7337
2650 Queensview Drive, Suite 100
Ottawa, ON K2B 8H6, Canada

borehole no. BH 25-4	core runs Run 6 to 7: 12.70 - 15.82 m	project Location: 1970 & 1980 Fowler Drive, Mississauga	project no. BRM-22022660-B0
date cored Mar 24, 2025		Rock Core Photographs	FIG 9

APPENDIX C

Certificates of Analyses



BUREAU
VERITAS

Your Project #: GTR-22022660-A0
Site Location: 1970 & 1980 FOWLER DRIVE, MISSISSAUGA,
ON
Your C.O.C. #: N/A

Attention: Jack Li

exp Services Inc
Brampton Branch
1595 Clark Blvd
Brampton, ON
CANADA L6T 4V1

Report Date: 2023/07/06

Report #: R7703364

Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C3J1752

Received: 2023/06/29, 12:00

Sample Matrix: Soil
Samples Received: 1

Analyses	Quantity	Date Extracted	Date Analyzed	Laboratory Method	Analytical Method
pH CaCl ₂ EXTRACT	1	2023/07/05	2023/07/05	CAM SOP-00413	EPA 9045 D m
Sulphate (20:1 Extract)	1	2023/07/06	2023/07/06	CAM SOP-00464	MOE E3013 m

Remarks:

Bureau Veritas is accredited to ISO/IEC 17025 for specific parameters on scopes of accreditation. Unless otherwise noted, procedures used by Bureau Veritas are based upon recognized Provincial, Federal or US method compendia such as CCME, MELCCFP, EPA, APHA.

All work recorded herein has been done in accordance with procedures and practices ordinarily exercised by professionals in Bureau Veritas' profession using accepted testing methodologies, quality assurance and quality control procedures (except where otherwise agreed by the client and Bureau Veritas in writing). All data is in statistical control and has met quality control and method performance criteria unless otherwise noted. All method blanks are reported; unless indicated otherwise, associated sample data are not blank corrected. Where applicable, unless otherwise noted, Measurement Uncertainty has not been accounted for when stating conformity to the referenced standard.

Bureau Veritas liability is limited to the actual cost of the requested analyses, unless otherwise agreed in writing. There is no other warranty expressed or implied. Bureau Veritas has been retained to provide analysis of samples provided by the Client using the testing methodology referenced in this report. Interpretation and use of test results are the sole responsibility of the Client and are not within the scope of services provided by Bureau Veritas, unless otherwise agreed in writing. Bureau Veritas is not responsible for the accuracy or any data impacts, that result from the information provided by the customer or their agent.

Solid sample results, except biota, are based on dry weight unless otherwise indicated. Organic analyses are not recovery corrected except for isotope dilution methods.

Results relate to samples tested. When sampling is not conducted by Bureau Veritas, results relate to the supplied samples tested.

This Certificate shall not be reproduced except in full, without the written approval of the laboratory.

Reference Method suffix "m" indicates test methods incorporate validated modifications from specific reference methods to improve performance.

* RPDs calculated using raw data. The rounding of final results may result in the apparent difference.



BUREAU
VERITAS

Your Project #: GTR-22022660-A0
Site Location: 1970 & 1980 FOWLER DRIVE, MISSISSAUGA,
ON
Your C.O.C. #: N/A

Attention: Jack Li

exp Services Inc
Brampton Branch
1595 Clark Blvd
Brampton, ON
CANADA L6T 4V1

Report Date: 2023/07/06
Report #: R7703364
Version: 1 - Final

CERTIFICATE OF ANALYSIS

BUREAU VERITAS JOB #: C3J1752

Received: 2023/06/29, 12:00

Encryption Key

Please direct all questions regarding this Certificate of Analysis to:

Patricia Legette, Project Manager
Email: Patricia.Legette@bureauveritas.com
Phone# (905)817-5799

=====
This report has been generated and distributed using a secure automated process.

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by Rodney Major, General Manager responsible for Ontario Environmental laboratory operations.

Total Cover Pages : 2
Page 2 of 9

Bureau Veritas 6740 Campobello Road, Mississauga, Ontario, L5N 2L8 Tel: (905) 817-5700 Toll-Free: 800-563-6266 Fax: (905) 817-5777 www.bvna.com

Microbiology testing is conducted at 6660 Campobello Rd. Chemistry testing is conducted at 6740 Campobello Rd.



BUREAU
VERITAS

Bureau Veritas Job #: C3J1752

Report Date: 2023/07/06

exp Services Inc

Client Project #: GTR-22022660-A0

Site Location: 1970 & 1980 FOWLER DRIVE, MISSISSAUGA, ON

Sampler Initials: JL

RESULTS OF ANALYSES OF SOIL

Bureau Veritas ID		WGF372		
Sampling Date		2023/06/27 15:00		
COC Number		N/A		
	UNITS	BH1 SS4	RDL	QC Batch
Inorganics				
Available (CaCl ₂) pH	pH	7.71		8768951
Soluble (20:1) Sulphate (SO ₄)	ug/g	<20	20	8771696
RDL = Reportable Detection Limit				
QC Batch = Quality Control Batch				



BUREAU
VERITAS

Bureau Veritas Job #: C3J1752

Report Date: 2023/07/06

exp Services Inc

Client Project #: GTR-22022660-A0

Site Location: 1970 & 1980 FOWLER DRIVE, MISSISSAUGA, ON

Sampler Initials: JL

TEST SUMMARY

Bureau Veritas ID: WGF372
Sample ID: BH1 SS4
Matrix: Soil

Collected: 2023/06/27
Shipped:
Received: 2023/06/29

Test Description	Instrumentation	Batch	Extracted	Date Analyzed	Analyst
pH CaCl ₂ EXTRACT	AT	8768951	2023/07/05	2023/07/05	Surinder Rai
Sulphate (20:1 Extract)	KONE/EC	8771696	2023/07/06	2023/07/06	Massarat Jan



BUREAU
VERITAS

Bureau Veritas Job #: C3J1752

Report Date: 2023/07/06

exp Services Inc

Client Project #: GTR-22022660-A0

Site Location: 1970 & 1980 FOWLER DRIVE, MISSISSAUGA, ON

Sampler Initials: JL

GENERAL COMMENTS

Each temperature is the average of up to three cooler temperatures taken at receipt

Package 1	1.0°C
-----------	-------

Results relate only to the items tested.



BUREAU
VERITAS

Bureau Veritas Job #: C3J1752

Report Date: 2023/07/06

QUALITY ASSURANCE REPORT

exp Services Inc

Client Project #: GTR-22022660-A0

Site Location: 1970 & 1980 FOWLER DRIVE, MISSISSAUGA, ON

Sampler Initials: JL

QC Batch	Parameter	Date	Matrix Spike		SPIKED BLANK		Method Blank		RPD	
			% Recovery	QC Limits	% Recovery	QC Limits	Value	UNITS	Value (%)	QC Limits
8768951	Available (CaCl ₂) pH	2023/07/05			100	97 - 103			0.56	N/A
8771696	Soluble (20:1) Sulphate (SO ₄)	2023/07/06	94	70 - 130	92	70 - 130	<20	ug/g	2.8	35

N/A = Not Applicable

Duplicate: Paired analysis of a separate portion of the same sample. Used to evaluate the variance in the measurement.

Matrix Spike: A sample to which a known amount of the analyte of interest has been added. Used to evaluate sample matrix interference.

Spiked Blank: A blank matrix sample to which a known amount of the analyte, usually from a second source, has been added. Used to evaluate method accuracy.

Method Blank: A blank matrix containing all reagents used in the analytical procedure. Used to identify laboratory contamination.



BUREAU
VERITAS

Bureau Veritas Job #: C3J1752

Report Date: 2023/07/06

exp Services Inc

Client Project #: GTR-22022660-A0

Site Location: 1970 & 1980 FOWLER DRIVE, MISSISSAUGA, ON

Sampler Initials: JL

VALIDATION SIGNATURE PAGE

The analytical data and all QC contained in this report were reviewed and validated by:

Anastassia Hamanov, Scientific Specialist

Bureau Veritas has procedures in place to guard against improper use of the electronic signature and have the required "signatories", as per ISO/IEC 17025, signing the reports. For Service Group specific validation, please refer to the Validation Signatures page if included, otherwise available by request. For Department specific Analyst/Supervisor validation names, please refer to the Test Summary section if included, otherwise available by request. This report is authorized by {0}, {1} responsible for {2} {3} laboratory operations.



Invoice Information				Invoice to (requires report) <input type="checkbox"/>		Report Information (If differs from invoice)						Project Information																	
Company : EXP Services Inc.				Company:								Quotation #:		Stream 3															
Contact Name:		Jack Li		Contact Name:								P.O. #/ AFEW#:																	
Street Address: 1595 Clark Boulevard				Street Address:								Project #:		GTR-22022660-AD															
City: Brampton		Prov: ON	Postal Code: L6T 4V1	City:		Prov:	Postal Code:							Site #:															
Phone:		416-319-5773		Phone:								Site Location:		1970 & 1980 Fowler Drive, Mississauga															
Email:		jack.li@exp.com		Email:								Site Location Province:		ON															
Copies:				Copies:								Sampled By:		Jack Li															
Regulatory Criteria																													
REG LS	<input type="checkbox"/> Table 1	<input type="checkbox"/> Res/Park	<input type="checkbox"/> Med/Fine	<input type="checkbox"/> Course	<input type="checkbox"/> CMIE	<input type="checkbox"/> Reg 406, Table: 55B*	<input type="checkbox"/> Sanitary Sewer Bylaw	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9	<input type="checkbox"/> 10	<input type="checkbox"/> 11	<input type="checkbox"/> 12	<input type="checkbox"/> 13	<input type="checkbox"/> 14	<input type="checkbox"/> 15	<input type="checkbox"/> 16	<input type="checkbox"/> 17	<input type="checkbox"/> 18	<input type="checkbox"/> 19	<input type="checkbox"/> 20	<input type="checkbox"/> 21	<input type="checkbox"/> 22
	<input type="checkbox"/> Table 2	<input type="checkbox"/> Ind/Comm	<input type="checkbox"/> OTHER	<input type="checkbox"/> For RSC	<input type="checkbox"/> *min 3 day TAT	<input type="checkbox"/> Storm Sewer Bylaw	<input type="checkbox"/> Municipality	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9	<input type="checkbox"/> 10	<input type="checkbox"/> 11	<input type="checkbox"/> 12	<input type="checkbox"/> 13	<input type="checkbox"/> 14	<input type="checkbox"/> 15	<input type="checkbox"/> 16	<input type="checkbox"/> 17	<input type="checkbox"/> 18	<input type="checkbox"/> 19	<input type="checkbox"/> 20	<input type="checkbox"/> 21	<input type="checkbox"/> 22
	<input type="checkbox"/> Table 3	<input type="checkbox"/> Agri/other	<input type="checkbox"/> OTHER	<input type="checkbox"/> VVQA	<input type="checkbox"/> OTHER	<input type="checkbox"/> Other:	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9	<input type="checkbox"/> 10	<input type="checkbox"/> 11	<input type="checkbox"/> 12	<input type="checkbox"/> 13	<input type="checkbox"/> 14	<input type="checkbox"/> 15	<input type="checkbox"/> 16	<input type="checkbox"/> 17	<input type="checkbox"/> 18	<input type="checkbox"/> 19	<input type="checkbox"/> 20	<input type="checkbox"/> 21	<input type="checkbox"/> 22	
	<input type="checkbox"/> Table 4	<input type="checkbox"/> OTHER	<input type="checkbox"/> VVQA	<input type="checkbox"/> OTHER	<input type="checkbox"/> Other:	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9	<input type="checkbox"/> 10	<input type="checkbox"/> 11	<input type="checkbox"/> 12	<input type="checkbox"/> 13	<input type="checkbox"/> 14	<input type="checkbox"/> 15	<input type="checkbox"/> 16	<input type="checkbox"/> 17	<input type="checkbox"/> 18	<input type="checkbox"/> 19	<input type="checkbox"/> 20	<input type="checkbox"/> 21	<input type="checkbox"/> 22		
Include Criteria on Certificate of Analysis (check if yes): <input type="checkbox"/>																													
SAMPLES MUST BE KEPT COOL (<10°C) FROM TIME OF SAMPLING UNTIL DELIVERY TO BUREAU VERITAS																													
Sample Identification						Date Sampled		Time (24hr)		Matrix	FIELD FILTERED	FIELD PRESERVED	LAB FILTRATION REQUIRED	Regular Turnaround Time (TAT)															
						YY	MM	DD	HH					MM	B1EV/F1	F2/F4	VOCs	Reg 153 metals and inorganics	Reg 153 ICPMS metals	Reg 153 metals	Reg 153 metals	Reg 153 metals	Reg 153 metals	Reg 153 metals	Reg 153 metals	Reg 153 metals	Reg 153 metals	Reg 153 metals	Reg 153 metals
1	BH1 SS4					23	06	27	15	00	Soil																		
2																													
3																													
4																													
5																													
6																													
7																													
8																													
9																													
10																													
11																													
12																													
*UNLESS OTHERWISE AGREED TO IN WRITING, WORK SUBMITTED ON THIS CHAIN OF CUSTODY IS SUBJECT TO BUREAU VERITAS STANDARD TERMS AND CONDITIONS. SIGNING OF THIS CHAIN OF CUSTODY DOCUMENT IS ACKNOWLEDGMENT AND ACCEPTANCE OF OUR TERMS AND CONDITIONS WHICH ARE AVAILABLE FOR VIEWING AT WWW.BVNA.COM/TERMS-AND-CONDITIONS OR BY CALLING THE LABORATORY LISTED ABOVE TO OBTAIN A COPY																													
LAB USE ONLY		Yes	No	°C	LAB USE ONLY*			Yes	No	°C	LAB USE ONLY			Yes	No	°C	LAB USE ONLY			Yes	No	°C	Temperature reading by:						
Seal present		<input checked="" type="checkbox"/>	<input type="checkbox"/>		1	3	7	Seal present			Seal present			Seal present			Seal present			Seal present			Seal present						
Seal intact		<input type="checkbox"/>	<input checked="" type="checkbox"/>		1	2	3	Seal intact			Seal intact			Seal intact			Seal intact			Seal intact			Seal intact						
Cooling media present		<input checked="" type="checkbox"/>	<input type="checkbox"/>	1	2	3	Cooling media present			Cooling media present			Cooling media present			Cooling media present			Cooling media present			Cooling media present			Cooling media present				
Relinquished by: (Signature/ Print)						Date						Time						Received by: (Signature/ Print)						Date					
						YY	MM	DD	HH	MM							YY	MM	DD	HH	MM								
1 <i>Jack Li</i>						23	06	28	15	00	2 <i>NIRAL PATEL</i>						2023	06	29	12	00								
																								Special Instructions					



CHAIN OF CUSTODY RECORD

ENY.COC - 00014v0

Page 1 of 1

Invoice Information			Invoice to (requires report) <input type="checkbox"/>			Report Information (if differs from invoice)						Project Information																																					
Company: EXP Services Inc.			Company: Jack Li									Quotation #: Stream 3		 C3J1752 IIOVA-06-442																																			
Contact Name: Street Address: 1595 Clark Boulevard			Contact Name: Street Address:									P.O. #/ AFE #: GTR-22022660-A0																																					
City: Brampton Prov: ON Postal Code: L6T 4V1			City: Prov: Postal Code:									Project #: Site #:																																					
Phone: 416-319-5773			Phone:									Site Location: 1970&1980 Fowler Drive, Mississauga																																					
Email: jack.li@exp.com			Email:									Site Location: Province: ON																																					
Copies:			Copies:									Sampled By: Jack Li																																					
Reg 153 Regulatory Criteria <table border="1" style="display: inline-table; vertical-align: middle;"> <tr><td>Table 1</td><td>Res/Park</td><td>Med/Fine</td><td>Reg 406, Table: CME</td></tr> <tr><td>Table 2</td><td>Ind/Comm</td><td>Course</td><td>Sanitary Sewer Bylaw</td></tr> <tr><td>Table 3</td><td>Agri/other</td><td>For RSC</td><td>*min 3 day TAT</td></tr> <tr><td>Table</td><td>OTHER</td><td></td><td>Storm Sewer Bylaw</td></tr> <tr><td></td><td></td><td></td><td>Municipality</td></tr> <tr><td></td><td></td><td></td><td>VISA</td></tr> <tr><td></td><td></td><td></td><td>WQO</td></tr> <tr><td></td><td></td><td></td><td>Other:</td></tr> </table> <div style="display: inline-table; vertical-align: middle;"> Include Criteria on Certificate of Analysis (check if yes): <input type="checkbox"/> </div>																		Table 1	Res/Park	Med/Fine	Reg 406, Table: CME	Table 2	Ind/Comm	Course	Sanitary Sewer Bylaw	Table 3	Agri/other	For RSC	*min 3 day TAT	Table	OTHER		Storm Sewer Bylaw				Municipality				VISA				WQO				Other:
Table 1	Res/Park	Med/Fine	Reg 406, Table: CME																																														
Table 2	Ind/Comm	Course	Sanitary Sewer Bylaw																																														
Table 3	Agri/other	For RSC	*min 3 day TAT																																														
Table	OTHER		Storm Sewer Bylaw																																														
			Municipality																																														
			VISA																																														
			WQO																																														
			Other:																																														
SAMPLES MUST BE KEPT COOL (<10°C) FROM TIME OF SAMPLING UNTIL DELIVERY TO BUREAU VERITAS																																																	
Sample Identification						Date Sampled		Time (24hr)		Matrix	FIELD FILTRATED		FIELD PRESERVED		LAB FILTRATION REQUIRED		VOCs		Reg 153 metals and inorganics		Reg 153 ICP/ICPMS metals		Reg 153 metals		Reg 153 ICP/ICPMS metals, HWS - B		pH & Sulphate																						
						YY	MM	DD	HH		MM	BTEX/ F1	F2 - F4																																				
1	BH1 SS4					23	06	27	15	00	Soil					v																																	
2																																																	
3																																																	
4																																																	
5																																																	
6																																																	
7																																																	
8																																																	
9																																																	
10																																																	
11																																																	
12																																																	
*UNLESS OTHERWISE AGREED TO IN WRITING, WORK SUBMITTED ON THIS CHAIN OF CUSTODY IS SUBJECT TO BUREAU VERITAS STANDARD TERMS AND CONDITIONS. SIGNING OF THIS CHAIN OF CUSTODY DOCUMENT IS ACKNOWLEDGMENT AND ACCEPTANCE OF OUR TERMS AND CONDITIONS WHICH ARE AVAILABLE FOR VIEWING AT WWW.BVNA.COM/TERMS-AND-CONDITIONS OR BY CALLING THE LABORATORY LISTED ABOVE TO OBTAIN A COPY																																																	
LAB USE ONLY			Yes	No	°C	7	3	7	LAB USE ONLY			Yes	No	°C	1	2	3	LAB USE ONLY			Yes	No	°C	1	2	3	Temperature reading by:																						
Seal present			Seal present						Seal present			Seal present						Seal present			Seal present						Seal present			Seal present																			
Seal intact			Seal intact						Seal intact			Seal intact						Seal intact			Seal intact						Seal intact			Seal intact																			
Cooling media present			Cooling media present			Cooling media present			Cooling media present			Cooling media present			Cooling media present			Cooling media present			Cooling media present																												
Relinquished by: (Signature/ Print)						Date		Time		Received by: (Signature/ Print)						Date		Time		Special Instructions																													
1 Jack Li						YY	MM	DD	HH	MM	1 Minal Patel						YY	MM	DD	HH	MM																												
2											2																																						